

# **Creating global HMI solutions**

# AGRICULTURAL MACHINERY



APEM is a leading manufacturer of highreliability Human Machine Interface (HMI) products with more than 20 years' experience in the agricultural industry.

With vertically integrated manufacturing, APEM offers its agricultural customers uncompromised reliability through its custom product development, AGRICULTURAI

manufacturing excellence and out-standing service.

APEM offers a broad range of HMI components designed for the agricultural market, including toggles,

rockers and pushbutton switches, LED indicators, paddle controls as well as switch panels and joysticks.




**APEM IN** 

MACHINERY

# A BROAD RANGE OF PRODUCTS AND SOLUTIONS

### APEM OFFERS



### CUSTOMIZED PRODUCTS

With robust development processes, and with the support of ergonomics experts, APEM offers a unique expertise in HMI customization. APEM engineers will propose you the best ergonomics, shape, marking, backlighting, material, waterproofing, connection... in line with your expectations and environment.

Depending on your need, APEM can propose fully customized products ("customer exclusive") or a custom design with already qualified HMI components, joystick handles and joystick bases.




### CAPABILITY TO BUILD PANEL SOLUTIONS



With quality components and 9 keyboard technologies available, APEM can provide sub-assemblies, design and build a remote control or a complete HMI precisely to your need.

APEM can provide you with full service capabilities, including studies and testing. With control of all stages of production, you can be sure that the solution will perform to mechanical, electrical, environmental and EMC/EMI standards. Our internal electronic teams manage the integration of communication protocols as well as protection filters and power supplies.

# YOU HAVE SPECIFIC NEEDS, WE HAVE DEDICATED SOLUTIONS





# PREVENT ACCIDENTS DUE TO UNINTENDED OPERATION Choose a rocker with a reliable interlocking mechanism.

# **KL SERIES**

The KL Series features a small switch at the top that, once pressed, will prevent the switch from being turned on unless it is pressed down.



# **IMPROVE ERGONOMICS**

Integrate a mini joystick on your main joystick.

### **TS SERIES**

This proportional two axis joystick is similar in size and operation to «gamepad» controls, but in a rugged industrial package.



# OPTIMIZED SPECIFIC FUNCTIONS ON ONE HANDGRIP

Differentiate your HMI with a custom joystick using qualified and field proven components.

### XD RT HANDLE

A multi-axis Hand Grip joystick with ergonomics designed specifically by APEM for demanding vehicle applications.



# NAVIGATE THE TOUCH PANEL WHILE KEEPING YOUR HAND ON THE JOYSTICK

Integrate a navigation joystick on you handgrip.

### **NV SERIES**

Contrary to most navigators currently on the market, the NV series provides enhanced tactile feedback in 4 directions plus pushbutton. This results in improved haptics and extremely precise control.

# THE XD SERIES RT HANDLE

# CONFIGURE YOUR JOYSTICK WITH QUALIFIED OFF-THE-SHELF HMI COMPONENTS

The following HMI components can be used on the face and rear plates of our handles:



### **NV SERIES**

- 4 and 5 way operation
- Momentary actuation with tactile feedback
- IP67 panel sealed



### **FNR SERIES**

- Ideal for forwardneutral-reverse functions
- Momentary and latching operations
- Morneritary and latering operation
- Panel sealing to IP69K



### IX SERIES

- Momentary tactile operation
- Elastomer boot provides IP67 panel sealing
- LED backlighting options

# APIER

- HR SERIES
- Hall effect roller
- Spring centering or friction hold
- IP67 sealed electronics
  - and panel sealed options

# XD SERIES

Challow mounting depth < 60 mm Extremely robust, resists high axial load (1780 N - 400 lbf)

# PANEL SOLUTIONS


APEM offers dedicated solutions of complete HMIs or remote controls, based on its knowledge of keyboard technologies and their integration, but also the right selection of high-quality components.

By combining the expertise acquired in the agriculture market and its environment during the last decades, APEM provides the most suitable solution to its customers.

# TECHNOLOGIES MASTERED BY APEM AND ADAPTED TO AGRICULTURAL EQUIPMENTS:

### **ELECTRONIC & SOFTWARE**

**PERFORMANCE** - APEM's Panel Solutions ensure the highest performance to electronics, environmental and EMC/EMI standards. **EFFICIENT INTEGRATION** - APEM designs electronics and connector systems to fit most applications.



### SAFETY

APEM offers standard SIL2 compliant components but also develops custom PLx (AgPLx, MPLx, ...), SILx solutions as per customer requests.

# CUSTOMER EXCLUSIVE

CUSTOM PRODUCTS CO-DEVELOPED WITH CUSTOMERS

APEM FULLY CUSTOM

APEM EXCLUSIVE

- dilli

MULTIPLE SWITCH TECHNOLOGIES ELASTOMERIC MEMBRANE PROPORTIONAL ROLLER & ROCKER PROPORTIONAL THUMBSTICK ELECTRO-MECHANICAL SWITCHES

ROBUST ERGONOMIC DESIGN

DEDICATED COMPONENT DEVELOPMENT

> CUSTOM INTEGRATED CAN PROTOCOL

### APEM develops complete interface solutions

combining components (switches, keypads, indicators, joysticks), with standard electronic boards and programming.

An APEM team professional is happy to assist you in the development of these complete turnkey solutions meeting your specific requirements with responsiveness and flexibility.

# OUR **PRODUCTS**

APEM OFFERS THE WIDEST RANGE OF HMI **COMPONENTS & SOLUTIONS WITH OVER** 125,000 STANDARD PART NUMBERS INCLUDING SWITCHES, JOYSTICKS, SWITCH PANELS, INDICATORS.

# CONTENT

PANEL SWITCHES

### Sealed & customizable rockers switches

	FNR SERIES				
ř.	EFFORTLESS FORWARD/REVERSE CONTROL				
	ROCKERMEC SERIES	10			
	KL SERIES STRONG LOCKING MECHANISM	11			



SEALED, CUSTOMIZABLE ROCKER **KH SERIES** 13

12

PROTECTED AGAINST ACCIDENTAL ACTUATION

### High

**KR SERIES** 

4	C	5
2		
	-	-1
1		

lly	versatile pushbuttons	
	IX SERIES	14
	THE NEXT STANDARD	



High

ę	IA SERIES LOW PROFILE & HIGH RELIABILITY	15
	IP SERIES HIGHLY VERSATILE PUSHBUTTON	16
	FD SERIES DOUBLE ICON ILLUMINATED PUSHBUTTON	17
	AV SERIES RUGGED START/STOP METALIC PUSHBUTTON	<u>18</u> v
	FP SERIES DESIGNED TO ATTRACT ATTENTION	19
	E-STOP SOLUTIONS "SAFE BREAK ACTION" TECHNOLOGY	20
High p	erformance toggles	
ł	5000 SERIES HIGH PERFORMANCE MINIATURE TOGGLE	21
l t		21
Protect	HIGH PERFORMANCE MINIATURE TOGGLE 600 & 600NH SERIES SUPERIOR QUALITY TOGGLE SWITCH	
Protect	HIGH PERFORMANCE MINIATURE TOGGLE 600 & 600NH SERIES SUPERIOR QUALITY TOGGLE SWITCH	
Protect Construction Constructi	HIGH PERFORMANCE MINIATURE TOGGLE 600 & 600NH SERIES SUPERIOR QUALITY TOGGLE SWITCH Ctions MSG & CSG SERIES	22 23 24
Protect	HIGH PERFORMANCE MINIATURE TOGGLE  600 & 600NH SERIES SUPERIOR QUALITY TOGGLE SWITCH  Ctions  MSG & CSG SERIES DESIGNED TO PROTECT  SEALING BOOTS	22 23 24



JOYSTICKS

### Hand grip

	XD SERIES	27
	DESIGNED FOR DEMANDING APPLICATIONS	
	CJ SERIES	28
¥	AVAILABLE WITH ANALOG OUTPUT	
Finge	rtip	

3000 SERIES



COMPACT, PRECISION HALL EF	FECT JOYSTICK
HF SERIES	30
AVAILABLE WITH CAN BUS	

29

33



1000 SERIES	31
COMPACT SWITCH JOYSTICK	
BHN & BL SERIES	32

### Thumb control

L	TS SERIES
	PRECISION FINGERTIP CONTROL

**PROPORTIONAL PADDLE** 



NV SERIES	34
IDEAL AS A DISPLAY CONTROLLER	



HR & CW SERIES. 35 UNIQUE THUMB CONTROL MECHANISM

PANEL SOLUTIONS



ELASTOMERIC KEYPAD 36 SOLUTION FOR MULTIPLE BUTTON APPLICATIONS



ENHANCED MEMBRANE KEYPAD 37 SEALED AND SHOCK RESISTANT KEYPAD



STAINLESS STEEL KEYPAD 38 RUGGED, CUSTOMIZABLE BACKLIT KEYPAD

# **FNR SERIES**

# FNR ROCKER SWITCH

# **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# FOR EFFORTLESS FORWARD/REVERSE CONTROL

• 2 or 3 positions, momentary or maintained

- Sealed up to IP67
- 1 NO/NC in each direction
- Illumination with marking
- SIL2 / PLd capable

SERIES	POLES	POLES MAXIMUM BUSHING TERMINAL OPTIONS		MOUNTING OPTIONS	SEALING	
FNR	1 NO/NC	1A /24V	Ø20 mm (787 in)	Flying leads, solder lugs	Panel	IP67

# **ROCKERMEC / 10A**

SEALED PCB ROCKER SWITCH

## **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# COMPACT ROCKER SWITCH

- 2 or 3 positions, momentary
- Illumination of marking from PCB
- Sealead up to IP67
- Customization possibilities
- Plug & play PCB module available

SERIES	POLES	MAXIMUM RATINGS	MECHANICAL LIFE	MOUNTING OPTIONS	SEALING	ILLUMINATION
10A	1 NO or 1 NC/NO	50mA - 24DVC	500.000 operations	Through hole or SMT mounting	IP67	Single/bi-color/RGB

PANEL SWITCHES PCB SWITCHES

# **KL SERIES**

### LOCKING POWER ROCKER SWITCH

### **TOP APPLICATIONS:** PTO ENGAGEMENT & OTHER CRITICAL FUNCTIONALITIES IN TRACTORS, COMBINES, SPECIALTY HARVESTERS & SELF-PROPELLED SPRAYERS



# STRONG LOCKING MECHANISM

- Field proven reliability
- Solid construction
- Elastomer membrane option

- Intuitive ergonomics
- Easy-operation one hand activation

SERIES	POLES		BUSHING MOUNTING	MOUNTING	MOUNTING TERMINAL OPTIONS		SEALING	ILLUMINATION	
SERIES	POLES	MAXIMUM RATINGS	DIMENSIONS	OPTIONS	Solder lugs	Quick connect	Connector	SEALING	ILLUMINATION
KL	1,2	10A 24VDC	36.8 x 21.08 mm	Panel	х	х	х	IP69K	x

# **KR SERIES**

POWER ROCKER SWITCH

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# SEALED, CUSTOMIZABLE ROCKER

• Large variety of colors & laser etched symbols  Infinite number of options available for cost effective customization solutions • Connectors and mounting panel accessories available  Illuminated and non-illuminated

SERIES	POLES	MAXIMUM RATINGS	BUSHING	MOUNTING	TE	RMINAL OPTIO	NS		
SERIES	DIMENSIONS		OPTIONS	Solder lugs	Quick connect	Screw	SEALING	ILLUMINATION	
KR	1,2	20A 12VDC	36.8 x 21.08 mm	Panel	x	x	х	IP69K	х

PANEL SWITCHES PCB SWITCHES

LED INDICATORS

# **KH SERIES**

## POWER ROCKER SWITCH WITH PROTECTION GUARD

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# PROTECTED AGAINST ACCIDENTAL ACTUATION

- Available on 2 or 4 sides
- Customized laser etched legends

- Illuminated versions
- Sealed up to IP68/IP69K

SERIES	POLES	MAXIMUM RATINGS	BUSHING	MOUNTING	TE	RMINAL OPTIO	NS	SEALING	ILLUMINATION	
SERIES	POLES	DIMENSIONS		OPTIONS	Solder lugs	Quick connect	Screw	SEALING	ILLOWINATION	
КН	1,2	10 A 24 VDC	36.8 x 21.08 mm	Panel	х	х	х	IP69K	х	

# **IX SERIES**

### COMPACT PUSHBUTTON SWITCH

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# THE NEXT STANDARD

### • Compact

- Available with backlit marking
- Dustproof: Membrane on top with no gap between actuator and panel

- Frost, sand and hydrocarbon resistant
- Flush on panel
- Sealed up to IP67/IP69K

no gap t	between actua	ator and panel	• SI	IL2/PLd capable		
SERIES	POLES	MAXIMUM RATINGS	BUSHIND DIMENSIONS	TERMINAL OPTIONS	MOUNTING OPTIONS	SEALING
IX	2	50 mA - 24 VDC	Ø 12 mm (.472 in)	Solder lugs	Panel	IP67/IP69K

# IA SERIES

### DUSTPROOF PUSHBUTTON SWITCH

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# LOW PROFILE & HIGH RELIABILITY

• Dustproof: Membrane on top with no gap between actuator and panel

- Frost, sand and
- hydrocarbon resistant
- Flush on panel

- Sealed up to IP67
- SIL2/PLd capable

SERIES	POLES	MAXIMUM RATINGS	BUSHING DIMENSIONS	TERMINAL OPTIONS	MOUNTING OPTIONS	SEALING
IA	1 NO/NC	2A 24VDC	Ø 16 mm (.629 in)	Flying leads	Panel	IP67

# **IP SERIES**

### COMPACT PUSHBUTTON SWITCH

### **TOP APPLICATIONS:** SPRAYERS, TRACTORS, COMBINES, SPECIALTY HARVESTERS



# HIGHLY VERSATILE PUSHBUTTON

- High performance pushbuttons
- Largest selection of color, shapes, terminals, markings, backlighting
- Unified look, differentiated functions, simplified purchasing

			MAXIMUM	BUSHING			TERM	IINAL OPT	TIONS			MOUNTING		
SERIES	APPROVALS	POLES	RATINGS	DIMENSIONS	Solder lugs	Quick connect	Screw	PCB	Flying leads	Wire Wrap	Cable	OPTIONS	SEALING	ILLUMINATION
IP	UL	1	5A 28VDC 4A 12VDC	Ø12 (.472)	x	x		x	x			Panel	IP67	X

# **FD SERIES**

# DOUBLE ICON ILLUMINATED PUSHBUTTON SWITCH

### **TOP APPLICATIONS:** AGRICULTURAL MACHINERY DASHBOARD (ENGINE START)



# DOUBLE ICON ILLUMINATED PUSHBUTTON

- 3 standard legends (0/1, START/STOP, ON/OFF)
- Threaded or snap-in versior

• Sealed up to IP69K

		MAXIMUM	BUSHING			TERM	IINAL OPT	IONS		MOUNTING		
SERIES	POLES	RATINGS	DIMENSIONS	Solder lugs	Quick connect	Screw	PCB Flying Wire Wire Cable OPTIONS		SEALING	ILLUMINATION		
FD	1,2	4A 12VDC 200mA 12VDC	Ø24 (.944) Ø26 (1,024)	х						Panel, Snap-in or threaded bushing	IP69K (threaded bushing)	X

# AV30 START STOP

METAL PUSHBUTTON

## **TOP APPLICATIONS:** AGRICULTURAL MACHINERY DASHBOARD (ENGINE START)



# RUGGED METALIC PUSHBUTTON

### Robust pushbutton

• Stainless steel actuator and bushing

- Appealing aesthetics
- Easily customizable: marking, illumination

		MAXIMUM	BUSHING			TERM	IINAL OPT	IONS			MOUNTING			
SERIES			DIMENSIONS	Solder lugs	Quick connect	Screw	PCB	Flying leads	Wire Wrap	Cable	OPTIONS	SEALING	ILLUMINATION	
AV	NO/NC	1 A 30 VDC	Ø30 (1.18)	х	x		x	x		х	Panel	IP67	х	

PANEL SWITCHES PCB SWITCHES

LED INDICATORS

JOYSTICKS

# **FP SERIES**

# FULLY ILLUMINATED PUSHBUTTON SWITCH

### **TOP APPLICATIONS:** IN-CAB CONTROL PANELS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# DESIGNED TO ATTRACT ATTENTION

- Full actuator or symbol illumination
- Sealed up to IP69K
- 24/26/30mm diameters
- Threaded or snap-in versions

						TERM	IINAL OPT							
SERIES	POLES	MAXIMUM RATINGS	BUSHING DIMENSIONS	Solder lugs	Quick connect	Screw	PCB	Flying leads	Wire Wrap	Cable	MOUNTING OPTIONS	SEALING	ILLUMINATION	
FP	1,2	4A 12VDC 200mA 12VDC	Ø24 (.944) Ø26 (1.024) Ø30 (1.18)	x				x		x	Panel, Snap-in or threaded bushing	Up to IP69K	Х	

• Fully customizable

# **EMERGENCY STOPS**

ROBUST EMERGENCY STOP

# **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# "SAFE BREAK ACTION" TECHNOLOGY

that the	ive safety tec e machinery or is broken		1.10	l up to IP67 act behind panel		able with illuminatior t or pull to release	
SERIES	SAFE BREAK TECHNOLOGY	PANEL CUT OUT	OPERATOR SIZES	NUMBER OF CONTACTS	TERMINAL CONNECTION	OPERATION	ILLUMINATION
XA	x	16 mm	Ø29 mm (1.141 in) Ø40 mm (1.574 in)	Up to 4 NC : 1,2,3,4 / NO : 0,1	Solder, PCB	Push to lock, pull or turn to reset	Option
XW	x	22 mm	Ø38 mm (1.496 in) Ø40 mm (1.574 in) Ø60 mm (2.362 in)	Up to 4 NC : 1,2,3,4 / NO : 0,1	Screw, solder, PCB	Push to lock, pull or turn to reset	Option





# COMPACT SAFETY SWITCHES

• Seal	ed up to IP65, IP67	7 & IP69K	Compact body	y • Comp	olies with E	N60947-5-1	L • In	npact resist	tant to IK10	
SERIES		DOLES		BUSHING	TER	MINAL OPTION	s	MOUNTING	SEALING	
SERIES	S APPROVALS POLES MAXIMUM RATINGS		DIMENSIONS	Solder lugs	Connector	PCB	OPTIONS	SEALING		
ES	EN60947-5-1	2, 3	1A 24VDC	Ø22 (.877) Ø28 (.1.102)	х		х	Panel	IP65, IP67 & IP69K	
EC	EN60947-5-1 EN60947-5-5	2 154 24/110		Ø22 (.877)	х	х	х	Panel	IP65	

# **5000 SERIES**

### **TOGGLE SWITCH**

### **TOP APPLICATIONS:** NAVIGATION & CONTROL SYSTEMS FOR PRECISION FARMING APPLICATIONS



# HIGH PERFORMANCE MINIATURE TOGGLE

• High performance, sturdy construction

- Widest variety of actuators, contact materials, functions, poles, terminals, bushings, finishes & sealings
- Visual versatility: sealing boots in 6 different colors
- Easily adaptable to final application
- Available with low level contact

			MAXIMUM	BUSHING			TERM	INAL OPT	TIONS			MOUNTING		
SERIES	APPROVALS	POLES	RATINGS	DIMENSIONS	Solder lugs	Quick connect	Screw	PCB	Flying leads	Wire wrap	Cable	OPTIONS	SEALING	ILLUMINATION
5000	VDE-UL- CSA-CECC	1,2,3,4	3A 250VAC 4A 30VDC	Ø6 (.236) Ø6,35 (1/4) Ø11,9 (15/32)	x	x		х		х		Panel, Vertical - Through hole, Horizontal- Through hole, Vert. right angle- Through hole	Optional	

# 600 & 600NH SERIES

### **POWER TOGGLE SWITCH**

# **TOP APPLICATIONS:** TRACTOR ATTACHMENTS & IMPLEMENTS, SPRAYERS & HARVESTING EQUIPMENT LIVESTOCK HOUSING, GREENHOUSES, CONTROL UNITS



# SUPERIOR QUALITY TOGGLE SWITCH

- Superior reliability and longer life
- Great sealing
- Visual versatility

 Sealing boots in a wide range of colors and lever choices including paddle levers for at-a-glance directional control

			MAXIMUM	BUSHING			TERM	INAL OPT	IONS			MOUNTING		
SERIES	APPROVALS	POLES	RATINGS	DIMENSIONS	Solder lugs	Quick connect	Screw	PCB	Flying leads	Wire wrap	Cable	OPTIONS	SEALING	ILLUMINATION
600H	NF-VDE-UL-CSA	1,2,3	15A 250VAC 10A 24VDC	Ø12 (.472)	х	x	х					Panel	Optional	
600NH	NF-VDE-UL-CSA	1,2,3	15A 250VAC 10A 24VDC	Ø12 (.472)	х	x	х					Panel	No	

PANEL SWITCHES PCB SWITCHES

# MSG & CSG SERIES

SWITCH GUARDS

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# DESIGNED TO PROTECT

- High robustness with
- no risk of jamming
- Variety of locking options (MSG)
- Hydrocarbon/acid/chemical resistant (MSG)
- Easy marking on top (MSG)
- Complements APEM's toggle range
- Anti-tamper wire seal hole as standard

SERIES	CAP MATERIAL	SUPPORT PLATE	OPERATING TEMPERATURE	MECHANICAL LIFE	SWITCHES	LEVER LENGTH
CSG	Thermoplastic	Thermoplastic	-20°C to + 55°C		Ø11.9mm, Ø12mm threaded bushing	17.5mm outside bushing
MSG	Thermoset	Matte black stainless steel	-40°C to +85°C	20,000 cycles	Ø11.9mm, Ø12mm threaded bushing	17.5mm outside bushing

# **SEALING BOOT SERIES**

### SEALING BOOTS

## **TOP APPLICATIONS:** IN CAB & FENDER IN AGRICULTURAL EQUIPMENT, REMOTE CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# PROTECTS AGAINST DUST, SAND AND WATER

• Wide variety of shapes & colors

• Available in silicone and neophrene

• Fast customization to accommodate any actuator length

CEDIEC	SERIES BOOT MATERIAL NUT MATERIAL OPERA				TEMPERAT	JRE RANGE	ELASTICITY	MECHANICAL	
SERIES	BOOT MATERIAL	NUT MATERIAL	OPERATING TEMPERATURE		Low	High	ELASTICITY	RESISTANCE	
	ROOTE Neoprene Brass, nickel		Silicone	-40°C to +85°C	Best	Best	Best	Good	
SEALING BOOTS	or silicone	plated, matte black	Neoprene	-20°C to +50°C	Good	Better	Good	Best	

# **MULTIMEC 5 SERIES**

HIGH PERFORMANCE PCB SWITCHES

### **TOP APPLICATIONS:** TRACTORS, COMBINES, SPECIALTY HARVESTERS



# ABSOLUTE RELIABILITY AND FUNCTIONALITY

- 10 million trouble-free actuations
- Superior sealing
- Large selection of standard caps
- Available in NC/NO
- Superior illumination with integrated chip-LEDs

SERIES	POLES	MAXIMUM RATING	MOUNTING OPTIONS	SEALING	MECHANICAL LIFE
Multimec 5 series - 5E & 5G	Single pole / momentary	50mA - 24VDC	Trough hole or SMT mounting	IP67	10,000,000 operations

AGRICULTURAL MACHINERY

# Q SERIES PANEL MOUNT LED INDICATORS

# TOP APPLICATIONS: ALL AGRICULTURAL MACHINERY



# LARGE VARIETY OF SIZES AND COLORS

- Reverse diode protection available
- Wide variety of LED colors
- Wire customization available
- Optional sealing up to IP67
- Many different panel cut-out sizes
- Available with custom and secret until lit legends

SERIES	PANEL	MAXIMUM	BEZEL STYLES	BEZEL	TE	RMINAL OPTIO	NS	TYPE	LED COLORS
SERIES	CUT-OUT	RATINGS	BEZEL STILES	FINISHES	Fastons	Pins	Wire	OF ILLUMINATION	LED COLORS
Q	Ø6, 8, 10, 12, 14, 16, 19, 22, 25, 30	2VDC -220VAC	Prominent, recessed & flushed	Bright, satin & black	х	х	х	Fixed light, bi-color, RGB, night vision	Suitable for in cab use and outside use which are daylight viewable

# **XD SERIES**

## HALL EFFECT ROBUST JOYSTICK

### **TOP APPLICATIONS:** SPRAYERS, TRACTORS, COMBINES, SPECIALTY HARVESTER



# DESIGNED FOR DEMANDING APPLICATIONS

- Available with CAN bus J1939-71
- Shallow mounting depth
- IP67 above panel sealing
- Up to 1780 N 400 lbf horizontal load (depending on handle)
- SIL2 / Pld capable

SERIES	MECHANICAL	AXIS	TECHNICLOCY			OUTPUT	OPTIONS			MOUNTING	ABOVE PANEL SEALING	
SERIES	LIFECYCLES	AXIS	TECHNOLOGY	Single	Dual	Analog	PWM	USB	CAN bus	OPTIONS	ABOVE PANEL SEALING	
XD	10 million	1 to 2 axis	Hall effect	х	х				х	Drop-in	IP67	

# **CJ SERIES**

MULTIFUNCTION JOYSTICK

### **TOP APPLICATIONS:** TRACTORS, COMBINES, SPECIALTY HARVESTERS



# AVAILABLE WITH ANALOG OUTPUT

• Configurable upper & lower faceplates

 Optional operator presence paddle switch reducing the risk of inadvertent actuation

SERIES	MECHANICAL	AXIS	TECHNOLOGY			OUTPUT	OPTIONS			MOUNTING	ABOVE PANEL SEALING	
SERIES	LIFECYCLES	AXIS	TECHNOLOGY	Single	Dual	Analog	PWM	USB	CAN bus	OPTIONS	ABOVE PANEL SEALING	
CJ	5 million	1, 2	Hall effect	х	х	х		х	х		Up to IP67	

• Easy mounting with standard cut-out and hole pattern

# 3000 SERIES

# PREMIUM HALL EFFECT JOYSTICK

### TOP APPLICATIONS:

REMOTE CONTROLS, REACH ARM MOWERS, VEGETATION CONTROL MACHINERY



# COMPACT, PRECISION HALL EFFECT JOYSTICK

Precision contactless Hall effect technology

• Compact for low profile applications

 Robust with over 10 million mechanical lifecycles

SERIES	MECHANICAL	AXIS	TECHNOLOGY	OUTPUT OPTIONS						MOUNTING	SEALING
SERIES	LIFECYCLES	ANIS	TECHNOLOGY	Single	Dual	Analog	PWM	USB	CAN bus	OPTIONS	SEALING
3000	10 million	1, 2, 3	Hall effect	х	х	х	х			Drop-in or rear mounting	IP67

# **HF SERIES**

SMALL HALL EFFECT JOYSTICK

## **TOP APPLICATIONS:** TRACTORS, COMBINES, SPECIALTY HARVESTERS



# AVAILABLE WITH CAN BUS

• 5 million lifecycles

including CAN bus J1939

- Available with 1, 2 or 3
- Very compact
- SIL2 / Pld capable

### OUTPUT OPTIONS MECHANICAL MOUNTING SERIES TECHNOLOGY SEALING AXIS LIFECYCLES OPTIONS Single Dual PWM USB CAN bus Analog HF 5 million 1, 2, 3 Hall effect Х Х Х Х Х Drop-in or rear mounting IP67

• Up to IP67 above panel sealing

# 1000 / 1000 HE SERIES

### COMPACT SWITCH JOYSTICKS

### **TOP APPLICATIONS:** REMOTE CONTROLS FOR AGRICULTURAL EQUIPMENT, SELF PROPELLED SPECIALTY TRACTORS MOWERS, SPRAYERS, HYDRAULIC VALVE CONTROLS, MENU SELECTION FOR SCREEN NAVIGATION



# COMPACT SWITCH JOYSTICK

• Configurable with single or double pole switching

• Versatile, compact and cost-effective

• Large selection of robust, ergonomic handles

SERIES	MECHANICAL	AXIS	TECHNOLOGY			OUTPUT	OPTIONS			MOUNTING	SEALING	
SERIES	LIFECYCLES	AAIS	TECHNOLOGY	Single	Dual	Analog	PWM	USB	CAN bus	OPTIONS	SEALING	
1000	5 million (HE version: 1 million)	1, 2,	Switching (1, 2 poles)	х						22mm bushing, 4 point screw	Up to IP67	

# **BHN/BL SERIES**

**PROPORTIONAL PADDLES** 

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, ARMRESTS & DASHBOARDS



# STYLISH AND ROBUST

	able in 2 heiç touch sculpte		• 5 color optic • Sealed up t				stom act request	tuator		• SIL2 / PLd ca	apable
SERIES	MECHANICAL LIFECYCLES	AXIS	TECHNOLOGY	Single	Dual	OUTPUT	OPTIONS PWM	USB	CAN bus	MOUNTING OPTIONS	SEALING
BHN/BL	10 million	Single	Hall effect	х	х	х	х			Drop-in	IP67

# **TS SERIES**

# **PROPORTIONAL HALL EFFECT THUMBSTICK**

## **TOP APPLICATIONS:** TRACTORS, COMBINES, SPECIALTY HARVESTERS, REMOTE CONTROLS, ARMRESTS & DASHBOARDS



# PRECISION FINGERTIP CONTROL

• Illuminated version available

- Ergonomically designed for repetitive operation over extended periods
- Highly reliable: up to IP67 and IP69K sealing
- Easy integration with rear or drop-in mounting & compact size
- Available with multiple handle options and materia

SERIES	MECHANICAL	AXIS	TECHNOLOGY			OUTPUT	OPTIONS			MOUNTING	PANEL SEALING	
SERIES	LIFECYCLES	ANIS	TECHNOLOGY	Single	Dual	Analog	PWM	USB	CAN bus	OPTIONS	PANEL SEALING	
TS	1 million	1, 2	Hall effect	х	х	х		х		Drop-in or rear mounting	IP67, IP69K	

# **NV SERIES**

NAVIGATOR SWITCH

# **TOP APPLICATIONS:** TRACTORS, COMBINES, SPECIALTY HARVESTERS



# IDEAL AS DISPLAY CONTROLLER

- Compact momentary micro switching thumbstic
- Available with "push to validate" option, ideal for navigation in display menu
- Enhanced tactile feedback
- Easy integration in joystick handle
- Sealed up to IP69K

SERIES	MECHANICAL LIFECYCLES	AXIS	BUSHING DIMENSIONS	TECHNOLOGY	TERMINAL OPTIONS	MOUNTING OPTIONS	SEALING
NV	1 million	1,2	Ø16.2 mm (.637 in)	Switching	Wire leads or connector	Panel	IP69K

# HR & CW SERIES

## **PROPORTIONAL THUMBWHEELS**

### **TOP APPLICATIONS:** TRACTORS, COMBINES, SPECIALTY HARVESTERS, REMOTE CONTROLS, ARMRESTS & DASHBOARDS



# ROLLER AVAILABLE WITH MANY OPTIONS

- Backlighting & detent options available (up to 11)
- Self centering spring return mechanism

Non-contacting Hall effect technologyChoice of 4 actuator styles

OF DU	MECHANICAL	47/10	TECHNOLOGY				MOUNTING				
SERIE	S LIFECYCLES	AXIS	TECHNOLOGY	Single	Dual	Analog	PWM	USB	CAN bus	OPTIONS	SEALING
HR	5 million	1	Hall effect	х	х	х				Rear mounting	IP68





# MINIATURE ROLLER

• Up to 3 million lifecycles			• Snap-in m		Custom actuator on request				Spring to center		
SERIES	MECHANICAL LIFECYCLES	AXIS	TECHNOLOGY	OUTPUT OPTIONS           Single         Dual         Analog         PVM         USB         CAN bus					MOUNTING OPTIONS	SEALING	
CW	3 million	Single	Hall effect	х	х	х	Х			Snap-in	-

PANEL SOLUTIONS

# ELASTOMERIC KEYPAD

### **RUBBER KEYPAD**

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# STANDARD SOLUTION FOR MULTIPLE BUTTON APPLICATIONS

- CAN bus or direct wiring output options
- CAN solution e-marking qualified (EMI, EMC)
- Backlit and quick front assembly

- Bargraph & indicators available
- Braille usage and glove usage compatible

# 6 BUTTON KEYPADS Sealed up to IP67 Can J1939 or discrete 12 to 24 VDC operating voltage Easy front mounting

PANEL SOLUTIONS

# ENHANCED MEMBRANE KEYPAD

### MEMBRANE KEYPAD

### **TOP APPLICATIONS:** IN-CAB CONTROLS, TRACTORS, COMBINES, SPECIALTY HARVESTERS, SELF-PROPELLED SPRAYERS



# SEALED AND SHOCK RESISTANT KEYPAD

• Sealed up to IP69K

Fertilizer and hydrocarbon resistar

- Impact resistant IK10
- UV resistant
- ENHANCED MEMBRANE KEYPADS

Panel mounted or remote control formats available

Standard 2 or 3 buttons available

Custom graphic marking

# STAINLESS STEEL KEYPAD

### STAINLESS STEEL KEYPAD

### **TOP APPLICATIONS:** SCREEN NAVIGATION IN SELF PROPELLED VEHICLES AND FOR ATTACHMENTS, REMOTE CONTROLS



# RUGGED, CUSTOMIZABLE BACKLIT KEYPAD

- Outdoor use (greenhouse environment resistant)
- Customizable selection of key legends and symbols
- Single or multi color options available

- Fully customizable keyboard size and button position/ configuration
- Current switching up to 150 mA

### STAINLESS STEEL KEYPADS

Sealed up to IP67 & impact resistant up to IK09

Diameter 17 mm and 20 mm pushbuttons available

Backlighting and LED indicators windows available

High resistance to agricultural chemicals (fertilizer, gasoline, oil, ...)

Button legends resistant to heavy extended use

Thin design to 7,1 mm below panel



70 70 years of trust built on quality

1,400 EMPLOYEES WORLDWIDE (5))

+ 50,000 PART NUMBERS 

## WORLDWIDE SALES & CUSTOMER SUPPORT

### USA

970 Park Center Drive VISTA, CA 92081 Tel: (+1) 760 598 2518 info@apem.com

USA 63 Neck Road HAVERHILL, MA 01835 Tel: (+1) 978 372 1602 info@apem.com

CHINA IDEC Shanghai 8th Floor, Tower 2, Enterprise Centre, No.209 Gong He Road, Shanghai, 200040, P.R.C Tel: +86 21 6076 1355 apem@apem.com.cn

BENELUX Belgicastraat 7/1 1930 ZAVENTEM 1930 2AVENTEM Belgium Tel B: (+32) 27 25 05 00 Tel NL: (+31) (70) 799 91 51 sales@apem.be

55, avenue Edouard Herriot BP1 82303 CAUSSADE Cedex Tel: (+33) 5 63 93 14 98 Fax: (+33) 5 63 93 19 03 commercial@apem.fr

**GERMANY** Gewerbehof Giesing Paulsdorfferstr. 34, 2. OG D-81549 MUNICH Tel: (+49) 89 45 99 11 0 Fax: (+49) 89 48 10 39 info@apem.de

ITALY Via Marconi 147G 12030 MARENE (CN) Tel: (+39) 0172 74 31 70 Fax: (+39) 0172 74 31 71 apem.italia@apem.it

Torshamnsgatan 39 S-16440 KISTA Tel: (+46) 8 626 38 00 Fax: (+46) 8 626 82 49 info@apem.se

Drakes Drive LONG CRENDON, Bucks HP18 9BA England Tel: (+44) 1 844 202400 Fax: (+44) 1 844 202500 sales@apem.co.uk

MORE THAN 130 DISTRIBUTORS WORLDWIDE

# APEM reserves the right to amend specifications without notice - Design: E3 Créa - Photos: iStock photo - Shutterstock - Jojo & Co - EDITED IN APRIL 2021