

### Data Sheet

**Total Power:** 600 W  
**# of Outputs:** Single  
**Outputs:** 12, 28, 36, 48 Vdc

### SPECIAL FEATURES

- 600 W full power at elevated temperatures
- Wide operating temperature range (-40 °C to 85 °C Baseplate)
- Adjustable output
- Remote output On/Off
- AC\_OK; DC\_OK signals
- 5V standby voltage
- Active current share
- Conduction-cooled / Fanless
- I<sup>2</sup>C / PMBus™
- Medical and ITE Safety<sup>3</sup>
- Suited for BF Type applications
- Active power factor correction
- Optional IP65 variant
- Optional 277 Vac input variant

### COMPLIANCE

- EMI Class B
- EN61000 Immunity

### SAFETY

- UL + CSA:** 60950-1 2nd Ed. ANSI ES60601-1<sup>3</sup>
- TUV:** 60950-1 2nd Ed. 60601-1 3rd Ed.<sup>3</sup>
- CB Scheme:** IEC 60950-1 IEC 60601-1
- China** CCC
- CE Mark**



### Electrical Specifications

Input													
Input range	U Suffix: 90 - 264 Vac (Safety rating: 100 - 240 Vac) 127 - 374 Vdc <sup>4</sup> H Suffix: 180 - 305 Vac (Safety rating: 200 - 277 Vac) 254 - 420 Vdc <sup>4</sup>												
Frequency	47 - 63 / 440 Hz (Safety rating: 50/60 Hz)												
Input fusing	Internal fuse on both L and N lines (12.5 A - U suffix; 7 A - H suffix)												
EMI/RFI	FCC Class B, CISPR22/EN55022 Class B												
MIL-STD-461F EMI <sup>1</sup>	Compliance to CE101, 102; CS101, 114, 115, 116 (with external filter <sup>1</sup> )												
Inrush current	≤ 25 A peak												
Power factor	0.99 typical												
Harmonics	Meets EN61000-3-2 Class A and Class C <sup>2</sup>												
Input current	< 10 Arms @ 100 Vac												
Hold up time	20 ms min for Main Output (230 Vac) @ 100% Load												
Efficiency	93.3% typical @ 230 Vac; 100% Load; 28 Vdc												
Leakage current	< 200 µA (per ANSI/ES60601; 264 Vac split-phase / 60 Hz) < 400 µA (per IEC60601; 264 Vac / 50 Hz)												
Isolation voltage	<table border="0"> <tr> <td></td> <td>U Suffix</td> <td>H Suffix</td> </tr> <tr> <td>PRI-SEC:</td> <td>4,000 VAC (2X MOPP)</td> <td>3,000 Vac</td> </tr> <tr> <td>PRI-Chassis:</td> <td>1,500 VAC (1X MOPP)</td> <td>2,000 Vac</td> </tr> <tr> <td>SEC-Chassis:</td> <td>1,500 VAC (1X MOPP)</td> <td>1,500 Vac</td> </tr> </table>		U Suffix	H Suffix	PRI-SEC:	4,000 VAC (2X MOPP)	3,000 Vac	PRI-Chassis:	1,500 VAC (1X MOPP)	2,000 Vac	SEC-Chassis:	1,500 VAC (1X MOPP)	1,500 Vac
	U Suffix	H Suffix											
PRI-SEC:	4,000 VAC (2X MOPP)	3,000 Vac											
PRI-Chassis:	1,500 VAC (1X MOPP)	2,000 Vac											
SEC-Chassis:	1,500 VAC (1X MOPP)	1,500 Vac											

1. Consult productsupport.ep@artesy.com for external filter details.  
 2. Meets Class C ≥ 50% load.  
 3. U suffix have both ITE and Medical Safeties. H suffix carries ITE approval only.  
 4. DC input rating not part of product's Safety approval.

## Electrical Specifications

Output		
Output rating	See Ordering Information Table	
Standby output	5.0 Vdc @ 1.5 A Max	
Set point	± 0.5%	Factory set point
Total regulation	Main Output: ± 2.0% 5 Vsb: ± 5%	Combined Line / Load / Temperature
Rated load	600 W maximum	600 W from -40 °C to 85 °C Baseplate Temp. Derate output to 28 W @ 95 °C Baseplate Temp
Minimum load	0 A	For both Main and 5 Vsb Outputs
Output voltage adjust range	See Ordering Information Table	Max power limited to 600 W
Output noise	Main Output: 1.0% max p-p 5 Vsb: 60 mV max p-p	Measured with 0.1 µF Ceramic and 10 µF Tantalum Cap, 20 MHz BW
Remote sense	Compensation up to 500 mV	Pin 10: +Vout_RS / Pin4: -Vout_RS
Over current protection	105 - 130% of full load current	Default is Shutdown mode with Auto-retry every 2-4 sec. Output latches after 20 sec of continuous OCP fault presence. Restart after latch possible through AC recycle, Inhibit toggle or through PMBus.
Over voltage protection	125 - 145% Vo, nom Main Output 125 - 130% 5 Vsb	Latching / AC Recycle or Inhibit toggle required for PSU restart
Over temperature protection	> 95 °C Baseplate Temp	Output Shutdown / Auto-recovery
AC_OK	Open Collector; 0.8 Vdc max / 10 mA	Active low when AC is present
DC_OK	Open Collector; 0.8 Vdc max / 10 mA	Active low when Main Output is within regulation
Remote inhibit	Contact Closure	Pin 19: Open/Float = ON; Close/Ground = OFF
# Units in parallel operation	Qualified up to 5 units in parallel. Consult factory if more than 5 are required.	Pin 5: IShare pin for main output only.

## Environmental Specifications

Operating temperature range	-40 °C to +85 °C Baseplate temperature
Storage temperature	-40 °C to +85 °C
Humidity	10% to 95%
Altitude	16,402 ft (Operating) / 50,000 ft (Non-Operating)
Shock	MIL-STD-810F 516.5 Procedure I, VI
Vibration	MIL-STD-810F 514.5 Cat. 4, 10
Ingress protection	IP65 (for suffix "-4P")
MTBF (calculated)	>2M Hrs, 25 °C per SR-332 Issue 3
Electromagnetic immunity	Designed to meet EN61000-4-3, -4, -5, -8, -11 (Level 3); EN61000-4-2 (Level 4); EN60601-1-2 and EN55024
	For H suffix, Level 4 for EN61000-4-5

## Ordering Information

Model Number*	AC Input	Output Setpoint	Setpoint Tolerance	Adjustment Range	Output Current [A]		Max O/P Power [W]	Typical Efficiency**	Standby Output	Combined Line/Load Regulation	Output Ripple
					Min	Max					
LCC600-48U-9P	90 - 264	48 V	±0.5%	44 - 54	0	12.5	600	93.0%	5 Vdc @ 1.5 A	2%	1%
LCC600-48H-9P	180 - 305										
LCC600-36U-9P	90 - 264	36 V	±0.5%	32 - 38	0	16.7	600	92.0%	5 Vdc @ 1.5 A	2%	1%
LCC600-36H-9P	180 - 305										
LCC600-28U-9P	90 - 264	28 V	±0.5%	24 - 30	0	25	600	93.5%	5 Vdc @ 1.5 A	2%	1%
LCC600-28H-9P	180 - 305										
LCC600-12U-9P	90 - 264	12 V	±0.5%	12 - 15	0	50	600	92.3%	5 Vdc @ 1.5 A	2%	1%
LCC600-12H-9P	180 - 305										

\*Change suffix "-9P" to "-4P" for IP65 rated enclosure with fly lead wires


\*Change suffix "-4P" to "-4PR" for IP65 rated enclosure with right angle fly lead wires (applies to 28, 36, 48 Vdc)

\*Change suffix "-4P" to "-4PV" to omit the control cable (applies to 28, 36, 48 Vdc)

\*\*Typical efficiency at high line, factory default voltage and full load


## Mechanical Drawings

### -9P Suffix




## Mechanical Drawings

### -4P Suffix (28, 36, 48 Vdc)



### -4P Suffix (12 Vdc)



**Pin Assignment (INPUT)**

DESCRIPTION	-9Px Suffix		-4Px Suffix	
	DESIGNATION	NOTES	DESIGNATION	NOTES
Live	L1	Mating Connector: 350766-1 (Housing); 350536-1 (Contact Terminals)	Brown	SJTW 18AWGX3C; PVC jacket; 105 °C / 300 V
Neutral	L2		Blue	
Ground	G		Y/GR	

**Pin Assignment (MAIN OUTPUT)**

DESCRIPTION	-9Px Suffix		-4Px Suffix (28, 36, 48 Vdc)		-4Px Suffix (12 Vdc)	
	DESIGNATION	NOTES	DESIGNATION	NOTES	DESIGNATION	NOTES
Main Output	+Vout	4 Position Terminal Block: M4 Screw/10mm Pitch; 12kgf-cm Torque; Accepts 14-16AWG Ring Tongue - Spade Terminals MOLEX BB-124-08 (19141- 0058) or EQUIVALENT	Red	14AWGX4C; PVC jacket; 105 °C / 300 V	Red	6AWG Multi-Strand; PVC jacket; 105 °C / 600 V
Main Output Return GND	-Vout		Black		Black	
			Black		Black	

**Pin Assignment**

J1501 - Signal & Control		-9Px Suffix		-4Px Suffix	
SIGNALS	DESCRIPTION	PIN #	NOTES	WIRE COLOR	NOTES
A2_OUT	EEPROM Address	1	J1501 Mating Connector: JST PN PHDR-20VS  Contact Pins: JST PN SPHD- 001T-P0.5	BLACK	26AWGX20C+AL; PVC jacket; 105 °C / 300 V
GND	Ground	2		BROWN	
A1_OUT	EEPROM Address	3		RED	
-VOUT_RS	Remote Sense Return (Main O/P)	4		ORANGE	
ISHARE	Load Share Voltage	5		YELLOW	
A0_OUT	EEPROM Address	6		GREEN	
SDA	Serial Data Signal (I <sup>2</sup> C)	7		BLUE	
SPARE_1	Spare/Unused Pin	8		VIOLET	
SCL	Serial clock Signal (I <sup>2</sup> C)	9		GRAY	
+VOUT_RS	Remote Sense (Main O/P)	10		WHITE	
5VSB	5V Standby (1.5A Max)	11		PINK	
SGND	5V Standby Return	12		LIGHT BLUE	
SPARE_2	Spare/Unused Pin	13		WHITE/VIOLET	
G_DCOK_C	Global DC_OK Collector	14		WHITE/YELLOW	
WP	EEPROM Write Protect	15		WHITE/ORANGE	
G_DCOK_E	Global DC_OK Emitter (GND)	16		WHITE/BLACK	
GND	Return GND for O/P Signal and I <sup>2</sup> C communication	17		WHITE/RED	
G_ACOK_C	Global AC_OK Collector	18		WHITE/BROWN	
INH_EN	Output Inhibit_Enable Pin (turns output off)	19		WHITE/GREEN	
G_ACOK_E	Global AC_OK Emitter (GND)	20		WHITE/BLUE	

## Power Derating Curves




Figure 1. Output Power vs. Baseplate Temperature




Figure 2. Output Power vs. Input Voltage

## Efficiency Curves




Figure 3. Typical Efficiency for 28 V output




Figure 4. Typical Efficiency for 48 V output




Figure 5. Typical Efficiency for 36 V output




Figure 6. Typical Efficiency for 12 V output

## WORLDWIDE OFFICES

### Americas

2900 S.Diablo Way  
Tempe, AZ 85282  
USA  
+1 888 412 7832

### Europe (UK)

Waterfront Business Park  
Merry Hill, Dudley  
West Midlands, DY5 1LX  
United Kingdom  
+44 (0) 1384 842 211

### Asia (HK)

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
+852 2176 3333

**ARTESYN**<sup>™</sup>  
EMBEDDED TECHNOLOGIES

[www.artesyn.com](http://www.artesyn.com)

Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. © 2016 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit [www.artesyn.com/legal](http://www.artesyn.com/legal).

For more information: [www.artesyn.com/power](http://www.artesyn.com/power)  
For support: [productsupport.ep@artesyn.com](mailto:productsupport.ep@artesyn.com)