

BOURNS® PV SERIES

THROUGH-HOLE TRIMPOT® POTENTIOMETERS

PV32	Rotational Life	Number of Turns	Power Rating	Resistance Range	Resistance Tolerance	Temperature Coefficient	Temperature Range	Features
	200 Cycles	1	0.5 Watts @ 70 °C	10 ohms to 1 megaohm	±20 %	± 100 ppm/°C	-55 °C to +125 °C	• 1/4" Round • PV32P is the part with the plastic spacer • Sealed to IP67 • RoHS Compliant*
PV36	Rotational Life	Number of Turns	Power Rating	Resistance Range	Resistance Tolerance	Temperature Coefficient	Temperature Range	Features
	200 Cycles	25	0.5 Watts @ 70 °C	10 ohms to 2 megaohms	±10 %	± 100 ppm/°C	-55 °C to +125 °C	• 3/8" Square • Sealed to IP67 • Mounting hardware available • RoHS Compliant*
PV37	Rotational Life	Number of Turns	Power Rating	Resistance Range	Resistance Tolerance	Temperature Coefficient	Temperature Range	Features
	200 Cycles	12	0.25 Watts @ 85 °C	10 ohms to 2 megaohms	±10 %	± 150 ppm/°C	-55 °C to +125 °C	• 1/4" Square • Sealed to IP67 • Standoffs allow thorough PCB washing • RoHS Compliant*
PV12	Rotational Life	Number of Turns	Power Rating	Resistance Range	Resistance Tolerance	Temperature Coefficient	Temperature Range	Features
	200 Cycles	4	0.5 Watts @ 70 °C	10 ohms to 1 megaohms	±10 %	± 100 ppm/°C	-55 °C to +125 °C	• 5/16" Round • Unique planetary drive offers precise wiper setting • Sealed to IP67 • Top and side adjust styles • RoHS Compliant*


Model	Numbr of Turns		Size		Packaging Options	Adjustment
	Single-turn	Multiturn	3 mm	4 mm	See Note 1	See Note 2
PV32	X		X		T, R	T, S
PV36		X		X	T, R	T, S
PV37		X	X		T, R	T, S
PV12		X	X		T	T, S

BOURNS®

BOURNS® PV SERIES

SURFACE MOUNT TRIMPOT® POTENTIOMETERS

PVG5	Rotational Life	Number of Turns	Power Rating	Resistance Range	Resistance Tolerance	Temperature Coefficient	Temperature Range	Features
	200 Cycles	1	0.25 Watts @ 70 °C	10 ohms to 2 megaohms	±10 %	± 150 ppm/ °C	-55 °C to +125 °C	• 4 mm SMD • Meets EIA SMD standard trimmer footprint • Available in top and side adjust pin styles • Sealed to IP67 • RoHS Compliant* & Halogen free

PVG3	Rotational Life	Number of Turns	Power Rating	Resistance Range	Resistance Tolerance	Temperature Coefficient	Temperature Range	Features
	50 Cycles	1	0.25 Watts @ 70 °C	10 ohms to 2 megaohms	±20 %	± 150 ppm/ °C	-55 °C to +125 °C	• 3 mm SMD • Meets EIA SMD standard trimmer footprint • Available in top and side adjust pin styles • Metal cover for thermal protection • RoHS Compliant*

Model	Numbr of Turns		Size		Packaging Options	Adjustment
	Single-turn	Multiturn	3 mm	4 mm	See Note 1	See Note 2
PVG5		X		X	R	T, S
PVG3	X		X		R	T

Note 1: T = Tubes, B = Bulk, R = Tape and Reel

Note 2: T = Top Adjust, S = Side Adjust, R = Rear Adjust

BOURNS®

www.bourns.com

COPYRIGHT© 2018 • BOURNS, INC. • 01/18 • PSG • e/T1801
“Bourns” and “Trimpot” are registered trademarks of Bourns, Inc.
in the U.S. and other countries.

RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast
2011/65/EU June 8, 2011.

Americas: Tel: +1-951 781-5500
Email: americus@bourns.com

EMEA: Tel: +36 88 520 390
Email: eurocus@bourns.com

Asia-Pacific: Tel: +886-2 256 241 17
Email: asiacus@bourns.com