




Eaton high-power TVS diodes

High-power SMD and through-hole TVS diodes for lightning, EFT and ESD protection



Eaton's high-power transient voltage suppression diodes provide reliable overvoltage protection with very fast response times, low clamping voltage, and high peak current capability.

Extensive offering

Eaton's high-power transient voltage suppression diodes provide reliable overvoltage protection with very fast response times, low clamping voltage, and high peak current capability in a wide range of applications, including consumer, computing, energy, industrial, and medical devices.

These products are available in surface mount and radial or through-hole footprints and utilize silicon avalanche technology for excellent protection against damaging transients, from ESD up to lightning strikes. The high peak power and current capability of Eaton's TVS diodes combined with very fast-acting response times make them ideal for protecting critical circuits. TVS diode product lines are available in industry-standard sizes for both ESD and high-power suppression.

Features and benefits

- Common diode packages with multiple reverse working and clamping voltages
- Multiple surface mount and radial or through-hole footprints
- Very fast operation during overvoltage events
- Multiple power ratings within the same package size
- Low clamping voltage to provide superior protection
- A broad product offering for high-power transients






EAT•N

Powering Business Worldwide






High-power TVS diodes: sizes and selection


Standard TVS diode - surface mount

Photo	Series	Package type	Reverse working voltage	Peak pulse power (10/1000 μ s)	Peak pulse current (10/1000 μ s)
	SMF	SOD-123FL	5 to 220 V	200 W	Up to 21.7 A
	SMAJ	SMA	5 to 440 V	400 W	Up to 43.5 A
	P4SMA		5 to 440 V	400 W	Up to 43.5 A
	SMBJ	SMB	5 to 512 V	600 W	Up to 65.2 A
	P6SMB		5 to 512 V	600 W	Up to 65.2 A
	10BJ		5 to 200 V	1000 W	Up to 108.7 A
	15BJ	SMBF	5 to 440 V	1500 W	Up to 163 A
	SMCJ	SMC	5 to 440 V	1500 W	Up to 163 A
	SMDJ		5 to 220 V	3000 W	Up to 326 A
	5.0SMDJ		11 to 170 V	5000 W	Up to 275 A

High-power TVS diode

Photo	Series	Package type	Reverse working voltage	Peak pulse power (10/1000 μ s)	Peak pulse current (8/20 μ s)
	15KPE	Axial (P600/R6)	58 to 200 V	15000 W	-
	SMTJ	SMT-4	58 to 86 V	-	3500 A
	AK1E	Radial (0.95" pin to pin)	76 to 430 V	-	1000 A
	AK6E		15 to 430 V		6000 A
	AK10E		15 to 430 V		10000 A

Surface mount thyristor

Photo	Series	Package type	Peakoff-state voltage	Switching voltage range	Peak pulse current (10/1000 μ s)
	CPxxxSC	SMB	6 to 340 V	15 to 450 V	100 A