

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 23- 22, cable outlet: straight, color: yellow, Ethernet

Your advantages

- Easy and time-saving assembly with IDC fast connection technology
- Can be used internationally due to EAC, UL 1863, and CAN/CSA C22.2
- Ideal companion for servicing or repairs in the field: no special tools required for mounting
- 360° shielding ensures reliable transmission, even in industrial applications
- Ideal companion for servicing or repairs in the field: no special tools required for mounting

Commercial Data

Item number	1149847
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	ABNAAB
Product Key	ABNAAB
GTIN	4063151144562
Weight per Piece (including packing)	16.2 g
Weight per Piece (excluding packing)	15.8 g
Customs tariff number	85366990
Country of origin	PL

1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Technical Data

Product properties

Type	RJ45
Product type	Data connector (cable side)
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45
No. of cable outlets	1
Type	RJ45
Locking type	Locking clips
Shielded	yes
Cable outlet	straight
Positions/contacts	8P8C

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/3)	72 V (DC)
Rated current	1.75 A
Contact resistance	< 20 mΩ (Contact) < 100 mΩ (shield)
Frequency range	500 Hz
Insulation resistance	> 500 MΩ
Dielectric strength	1000 V (Conductor-Conductor) 1500 V (Wire/shield)
Contact resistance per contact pair	< 20 Ω
Contact resistance	> 10 mΩ (Wire – IDC) 0.005 Ω (Litz wire)
Transmission characteristics (category)	CAT6 _A
Transmission speed	10 Gbps
Power transmission	PoE++
Wave impedance	100 Ω

Connection data

Connection technology

Connection method	Insulation displacement connection
Connection cross section AWG	23 ... 22 (solid) 23 ... 22 (flexible)
Conductor cross section	0.25 mm ² ... 0.34 mm ² (solid) 0.25 mm ² ... 0.34 mm ² (flexible)

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Connection in acc. with standard	IEC 60603-7-51
----------------------------------	----------------

Dimensions

Width	13.65 mm
Height	14.4 mm
Orientation to	180.00 °
Length	53 mm

Material specifications

Color	yellow
Color of the housing part	silver
Material	Plastic
Flammability rating according to UL 94	V0
Housing surface material	Ni
Cable seal material	NBR
Contact material	CuSn
Contact surface material	Au/Ni
Contact carrier material	PC
Material, protective cover	PE
Locking latch material	Stainless steel
Material for screw connection	PA
Housing material	Metal

Cable/line

External cable diameter	5 mm ... 9 mm
Wire diameter including insulation	≤ 1.6 mm
Test voltage Core/Core	1000 V
Test voltage Core/Shield	1500 V
Wave impedance	100 Ω

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 750
Insertion force per signal contact	20.00 N
Extraction force per signal contact	20 N

Environmental and real-life conditions

Specification	IEC 60068-2-6
Frequency	2-2000 Hz
Sweep speed	1 octave/min
Amplitude	1 mm
Acceleration	200 m/s ²
Test duration	20 s
Specification	IEC 60068-2-27

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Acceleration	491 m/s ²
Number of shocks per direction	5

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (assembly)	-40 °C ... 85 °C

Mounting

Mounting type	For field assembly
Connection method	Insulation displacement connection

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1149847>



EAC

Approval ID: B.01687



cULus Recognized

Approval ID: E335024-20170228

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	56.5 V	0.175 A	-	-

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Classifications

ECLASS

ECLASS-11.0	27440101
ECLASS-12.0	27440113
ECLASS-13.0	27440113

ETIM

ETIM 8.0	EC002636
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

Accessories

MICROFOX-SP-1 - Diagonal cutter

1212487

<https://www.phoenixcontact.com/gb/products/1212487>



Electronic diagonal cutter, tapered head, without chamfer, with opening spring, non-reflective phosphate-treated surface, punched version

VS-CABLE-STRIP-VARIO - Stripping tool

1657407

<https://www.phoenixcontact.com/gb/products/1657407>

Stripping tool, for the multi-level stripping of shielded cables



CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector

1149847

<https://www.phoenixcontact.com/gb/products/1149847>



CUC-IND-C1ZNI-S/R4IE10G8 - RJ45 connector

1149846

<https://www.phoenixcontact.com/gb/products/1149846>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Metal, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: yellow, Ethernet

CUC-IND-J1ST-A/R4LS-LED-PG - RJ45 PCB connectors

1099281

<https://www.phoenixcontact.com/gb/products/1099281>



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector

1149847

<https://www.phoenixcontact.com/gb/products/1149847>



CUC-IND-J1ST-S/R4LS-LED-PG - RJ45 PCB connectors

1099282

<https://www.phoenixcontact.com/gb/products/1099282>



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

CUC-IND-J1ST-A/R4LS-PG - RJ45 PCB connectors

1099280

<https://www.phoenixcontact.com/gb/products/1099280>



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector

1149847

<https://www.phoenixcontact.com/gb/products/1149847>

CUC-IND-J1ST-S/R4LS-PG - RJ45 PCB connectors

1099279

<https://www.phoenixcontact.com/gb/products/1099279>



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

CUC-IND-J1ST-A/R4LS-LED - RJ45 PCB connectors

1091950

<https://www.phoenixcontact.com/gb/products/1091950>



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector

1149847

<https://www.phoenixcontact.com/gb/products/1149847>

CUC-IND-J1ST-S/R4LS-LED - RJ45 PCB connectors

1091947

<https://www.phoenixcontact.com/gb/products/1091947>



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

CUC-IND-J1ST-A/R4LS - RJ45 PCB connectors

1091946

<https://www.phoenixcontact.com/gb/products/1091946>



RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector

1149847

<https://www.phoenixcontact.com/gb/products/1149847>



CUC-IND-J1ST-S/R4LS - RJ45 PCB connectors

1091942

<https://www.phoenixcontact.com/gb/products/1091942>




RJ45 PCB connectors, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, material: Metal, connection method: THR reflow/THT wave

UCT-TMF 5 GN - Marker for terminal blocks

0829193

<https://www.phoenixcontact.com/gb/products/0829193>



Marker for terminal blocks, Sheet, green, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector


1149847

<https://www.phoenixcontact.com/gb/products/1149847>

UCT-TMF 5 RD - Marker for terminal blocks

0829189

<https://www.phoenixcontact.com/gb/products/0829189>




Marker for terminal blocks, Sheet, red, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

UCT-TMF 5 BU - Marker for terminal blocks

0829192

<https://www.phoenixcontact.com/gb/products/0829192>



Marker for terminal blocks, Sheet, blue, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector




1149847

<https://www.phoenixcontact.com/gb/products/1149847>

UCT-TMF 5 YE - Marker for terminal blocks

0828745

<https://www.phoenixcontact.com/gb/products/0828745>




Marker for terminal blocks, Sheet, yellow, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

UCT-TMF 5 OG - Marker for terminal blocks

0829190

<https://www.phoenixcontact.com/gb/products/0829190>



Marker for terminal blocks, Sheet, orange, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.4 x 4.7 mm, Number of individual labels: 72

CUC-IND-C1ZNI-S/R4IP10G8 - RJ45 connector



1149847

<https://www.phoenixcontact.com/gb/products/1149847>

TMT 5 R - Marker for terminal blocks

0816430

<https://www.phoenixcontact.com/gb/products/0816430>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, perforated, mounting type: snapped, snap into flat marker groove, for terminal block width: 5.2 mm, lettering field size: 6.4 x 5.15 mm, Number of individual labels: 19000

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

Halesfield 13, Telford

Shropshire, TF7 4PG

01952 681700

info@phoenixcontact.co.uk