


















1 Amp <i>Rated</i>						
<b>TE CII Series</b>	<b>MA, HM</b>	<b>1MA</b>	<b>MS, HS</b>	<b>1MS</b>	<b>MGA, HC</b>	<b>MGS, HCS</b>
<b>Relay Type</b>	Standard T0-5	Standard T0-5	Sensitive T0-5	Sensitive T0-5	Standard Minigrad	Sensitive Minigrad
<b>Contacts</b>	DPDT	SPDT	DPDT	SPDT	DPDT	DPDT
<b>Contact Rating</b>	1 Amp	1 Amp	1 Amp	1 Amp	1 Amp	1 Amp
<b>Coil Voltages</b>	5 to 30 Vdc	5 to 26.5 Vdc	5 to 48 Vdc	5 to 40 Vdc	5 to 26.5 Vdc	5 to 48 Vdc
<b>Mil Spec Qualifications</b>	M39016/9, 15, 20 M28776/1	M39016/7, 23, 24 M28776/5	M39016/11, 16, 21 M28776/3	M39016/10, 25, 26 M28776/4	M39016/17, 18, 19 M28776/6	M39016/41, 42, 43 M28776/7
1-2 Amp <i>Rated</i>						
<b>TE CII Series</b>	<b>SMGA, SHC</b>	<b>SMGS, SHCS</b>	<b>HMS</b>	<b>HMB</b>	<b>LS</b>	<b>SR, SS</b>
<b>Relay Type</b>	Std. SMT Grid	Sens. SMT Grid	Sensitive 1/2 Size	Bifilar 1/2 Size	Latching 1/2 Size	4P, 6P 1/2 Size
<b>Contacts</b>	DPDT	DPDT	DPDT	DPDT	DPDT	4PDT, 6PDT
<b>Contact Rating</b>	1 Amp	1 Amp	2 Amp	2 Amp	2 Amp	2 Amp
<b>Coil Voltages</b>	5 to 26.5 Vdc	5 to 48 Vdc	5 to 36 Vdc	6 to 26.5 Vdc	5 to 48 Vdc	5 to 26.5 Vdc
<b>Mil Spec Qualifications</b>	Designed to meet M39016	Designed to meet M39016	M39016/44	M39016/22	Designed to meet M39016/45	M39016/40
2-5 Amp <i>Rated</i>						
<b>TE CII Series</b>	<b>3SBC</b>	<b>3SBH</b>	<b>3SBM</b>	<b>3SAM</b>	<b>RD, 02, 03</b>	<b>HFW, HFW4A, 5A</b>
<b>Relay Type</b>	Standard 1/5 Size	4 Pole 1/5 Size	Latching 1/5 Size	Latching Full Size	Multi-Pole	Standard 1/2 Size
<b>Contacts</b>	DPDT	4PDT	4PDT	DPDT	2, 4 & 6PDT	DPDT
<b>Contact Rating</b>	2 Amp	2 Amp	2 Amp	2 Amp	2 Amp	2, 4 & 5 Amp
<b>Coil Voltages</b>	5 to 36 Vdc	6 to 36 Vdc	6 to 26.5 Vdc	6 to 24 Vdc	6 to 26.5 Vdc	5 to 48 Vdc
<b>Mil Spec Qualifications</b>	M39016/13, 37, 38	M39016/14, 53, 54	M39016/31, 35, 36	M39016/32	M5757/1, 7, 8	M39016/6

Contact ratings shown are 28 Vdc Resistive ratings.



# CII Short Form Reference Guide

High Performance Electromechanical Relays



<b>2-15 Amp</b> <i>Rated</i>							
<b>TE CII Series</b>		<b>FW, FW5A</b>	<b>SF, SF5A</b>	<b>FCB-205</b>	<b>FCB-405</b>	<b>07</b>	<b>FCA-210, 215</b>
<b>Relay Type</b>		Standard Full Size	Standard Tall	Std. Midrange	Std. Midrange	Std. Full Size	Std. Midrange
<b>Contacts</b>		DPDT	DPDT	DPDT	4PDT	DPDT	DPDT
<b>Contact Rating</b>		3 & 5 Amp	2 & 5 Amp	5 Amp	5 Amp	10 Amp	10 & 15 Amp
<b>Coil Voltages</b>		6.3 to 110 Vdc	1.8 to 40 Vdc	6 to 48 Vdc	6 to 48 Vdc	6 to 20Vdc, 115Vac	6 to 48Vdc, 115Vac
<b>Mil Spec Qualifications</b>		M5757/10	Designed to meet M5757	M83536/1, 2	M83536/5, 6	M5757/23, MS27245 & 27247	M83536/9, 10
<b>10-50 Amp</b> <i>Rated</i>							
<b>TE CII Series</b>		<b>FCA-410, 415</b>	<b>TD2</b>	<b>FCA-125</b>	<b>FCA-325, FCAC-325</b>	<b>FC-325</b>	<b>FCA-150, FCAC-150</b>
<b>Relay Type</b>		Std. Midrange	Time Delay	Std. Midrange	Std. Midrange	High Capacity	Std. Midrange
<b>Contacts</b>		4PDT	DPDT	SPDT	3PDT, 3PST w/ aux	3PST	SPST, SPST w/ aux
<b>Contact Rating</b>		10 & 15 Amp	10 Amp	25 Amp	25 Amp	25 Amp	50 Amp
<b>Coil Voltages</b>		6 to 48Vdc, 115Vac	28Vdc	6 to 48Vdc, 115Vac	6 to 48Vdc, 115Vac	28Vdc, 115Vac	6 to 28 Vdc
<b>Mil Spec Qualifications</b>		M83536/15, 16	M83726/28, 29 M83726/30, 31	M83536/36, 37 M6106/19	M83536/32, 33	MS27418	Designed to meet M6106

Contact ratings shown are 28 Vdc Resistive ratings.