

Document Receipt Acknowledgement
Date:
Section:
Name:



Document Number: D10149-A-D7300

PD Ref.: HEMCG0-1588

Date: Sep. 7, 2026

Attention:

TTI

Withdrawal of MLCC products due to lineup optimization in 2026FY

Chip Multilayer Ceramic Capacitor

A portion of the GRM/GRJ/GRT/GXM/GXT/GCM/GCJ/GCG/ZRA Series

Dear. Valued Customer

Thank you very much for your great and continued support for business with Murata.
This is the official notification that some of our products will be discontinued as detailed below.
Please review this, and approve in writing by Approval Due Date.
Also, please place Last Time Buy Order by the Last Time Order Due Date as needed.
Your understanding and support are highly appreciated.

1. Product Type, Customer/Murata/Alternative Part Numbers:

Product Type: A portion of the GRM/GRJ/GRT/GXM/GXT/GCM/GCJ/GCG/ZRA Series

Please refer to the attached documents for detailed Part Numbers' information.

2. Reasons/Background:

In order to stabilize the supply of MLCCs and improve the support system,
we are reviewing the lineup of our MLCC products,
and we will end the production of the corresponding part number in order to
expand the production capacity of other products.
Please exchange it for a replacement by the due date or place an order
for the future lifetime quantity of the target part number.

3. Approval Due: Dec., 31, 2027

Please review this, and reply to Sales for this Notice in writing by Due Date.
In case we do not get any contacts by the Due Date,
we will assume that this Notice with all its contents has been accepted.

4. Product Withdrawal Schedule:

Last Time Order Due (*): Mar., 31, 2028

Last Shipment Date: Mar., 31, 2029

* : Last Time Order is the subject to Minimum Order Quantity and Package Quantity.
Order Cancel and Product Return can be accepted only in the case of quality issue.
Please place Last Time Buy Order by the Last Time Order Due Date as needed.
We cannot receive any orders after Last Time Order Due.

5. Contact Window:

Should you have any questions or concerns,
please contact Murata Sales, Representative, or Distributor in your area.

Truly Yours. Thank you.

Fukui Murata MFG. Co., Ltd.

Product Engineering Department, Marketing Group

Ceramic Capacitor Business Unit

Senior Manager Takatsugu Sakamoto



Document Number: D10149-A-D7300
PD Ref.: HEMCG0-1588

Confirmation Letter

TTI

Fukui Murata MFG. Co., Ltd.

Product Withdrawal Confirmation

Product Type: Chip Multilayer Ceramic Capacitor
A portion of the GRM/GRJ/GRT/GXM/GXT/GCM/GCJ/GCG/ZRA Series

Last Time Order Due: Mar., 31, 2028

Last Shipment Date: Mar., 31, 2029

Product Withdrawal detailed below is

- ☐ accepted, and we will not place Last Time Order.
☐ accepted, and we will place Last Time Order as below.

Last Time Order Schedule:

Last Shipment Schedule:

Comments, Questions, etc.

Signature

Date: (MM, DD, YYYY)

Title:

Name:

現行品/Current PN	代替品番/Alternative PN
GRM185R61A105KE26_	GRM033R61A105ME01_
GRM185R61A105KE36_	GRM033R61A105ME01_
GRM185B31A105KE25_	GRM033R61A105ME01_
GRM185B31A105KE25_	GRM033R61A105ME01_
GRM185B31A105KE35_	GRM033R61A105ME01_
GRM185C80G225KE26_	GRM033C80G225ME01_
GRM185C80J105ME26_	GRM033C80J105ME05_
GRM188R61A124KA01_	GRM033R61A224KE90_
GRM188R61A124MA01_	GRM033R61A224ME90_
GRM188R61A154KA01_	GRM033R61A224KE90_
GRM188R61A154MA01_	GRM033R61A224ME90_
GRM188R61A184KA01_	GRM033R61A224KE90_
GRM188R61A184MA01_	GRM033R61A224ME90_
GRM188B11A124KA01_	GRM033R61A224KE90_
GRM188B11A124KA01_	GRM033R61A224KE90_

GRM188B11A124KA01_	GRM033R61A224KE90_
GRM188B11A124MA01_	GRM033R61A224ME90_
GRM188B11A154KA01_	GRM033R61A224KE90_
GRM188B11A154KA01_	GRM033R61A224KE90_
GRM188B11A154KA01_	GRM033R61A224KE90_
GRM188B11A154KA01_	GRM033R61A224KE90_
GRM188B11A154KA01_	GRM033R61A224KE90_
GRM188B11A154KC01_	GRM033R61A224KE90_
GRM188B11A154MA01_	GRM033R61A224ME90_
GRM188B11A184KA01_	GRM033R61A224KE90_
GRM188B11A184KA01_	GRM033R61A224KE90_
GRM188B11A184KA01_	GRM033R61A224KE90_
GRM188B11A184MA01_	GRM033R61A224ME90_
GRM185R61E105KA12_	GRM155R61E105KA12_
GRM185R61E105MA12_	GRM155R61E105MA12_

GRM185C80G225ME26_	GRM155C80G225ME15_
GRM185R61A225KE43_	GRM155R61A225KE01_
GRM185R61A225ME43_	GRM155R61A225ME01_
GRM185R60G475ME15_	GRM155R60G475ME47_
GRM185R60J475ME15_	GRM155R60J475ME47_
GRM185R60J475ME15_	GRM155R60J475ME47_
GRM185R60J475ME15_	GRM155R60J475ME47_
GRM185C80J105KE26_	GRM155C80J105KA12_
GRM185C80J105KE26_	GRM155C80J105KA12_
GRM185C81A105KE36_	GRM155C81A105KA12_
GRM185C81A105ME36_	GRM155C81A105MA12_
GRM185R61C105KE44_	GRM155R61C105KA12_
GRM185R61C105KE44_	GRM155R61C105KA12_
GRM185R61C105KE44_	GRM155R61C105KA12_
GRM185R61C105ME44_	GRM155R61C105MA12_
GRM185R60J225KE26_	GRM155R60J225KE01_
GRM185R60J225KE26_	GRM155R60J225KE01_
GRM185R60J225KE63_	GRM155R60J225KE01_
GRM185R60J225ME26_	GRM155R60J225ME01_
GRM185R60J225ME63_	GRM155R60J225ME01_
GRM185B31E105KA12_	GRM155R61E105KA12_
GRM185R60J105ME26_	GRM153R60J105ME15_
GRM185R61A105ME26_	GRM153R61A105ME95_
GRM185R61A105ME36_	GRM153R61A105ME95_
GRM185B10J105ME21_	GRM153R60J105ME15_
GRM185B30J105ME25_	GRM153R60J105ME15_
GRM185B31A105ME25_	GRM153R61A105ME95_
GRM185B31A105ME35_	GRM153R61A105ME95_
GRM188R71A224KA01_	GRM155R71A224KE01_
GRM188R71A224KA30_	GRM155R71A224KE01_
GRM188R71A224KA36_	GRM155R71A224KE01_
GRM188R71A224KC01_	GRM155R71A224KE01_

GRM188R71A224MA01_	GRM155R71A224ME01_
GRM188B11A224JA01_	GRM155R71A224KE01_
GRM188R71A224JA01_	GRM155R71A224KE01_
GRM188R71A124KA01_	GRM155R71A224KE01_
GRM188R71A124MA01_	GRM155R71A224ME01_
GRM188R71A124JA01_	GRM155R71A224KE01_
GRM188R71A154KA01_	GRM155R71A224KE01_
GRM188R71A154KA36_	GRM155R71A224KE01_
GRM188R71A154MA01_	GRM155R71A224ME01_
GRM188R71A154JA01_	GRM155R71A224KE01_
GRM188R71A184KA01_	GRM155R71A224KE01_
GRM188R71A184MA01_	GRM155R71A224ME01_
GRM188R71A184JA01_	GRM155R71A224KE01_
GRM188B11A224KA01_	GRM155R71A224KE01_
GRM188B11A224KA01_	GRM155R71A224KE01_

GRM188B11A224KA01_	GRM155R71A224KE01_
GRM188B11A224KA01_	GRM155R71A224KE01_
GRM188B11A224KA01_	GRM155R71A224KE01_
GRM188B11A224KC01_	GRM155R71A224KE01_
GRM188B11A224MA01_	GRM155R71A224ME01_
GXM188B11A224KA01_	GXM155R71A224KE01_
GRM188B11A124JA01_	GRM155R71A224KE01_
GRM188B11A154JA01_	GRM155R71A224KE01_
GRM188B11A184JA01_	GRM155R71A224KE01_
GRM188R11A224KA01_	GRM155R71A224KE01_
GRM188R11A224KA01_	GRM155R71A224KE01_
GRM188R11A224KA01_	GRM155R71A224KE01_
GRM188R11A224KA01_	GRM155R71A224KE01_
GRM188R11A224KA22_	GRM155R71A224KE01_

GRM188R11A224KC01_	GRM155R71A224KE01_
GRM188R11A224MA01_	GRM155R71A224ME01_
GRM188R11A224JA01_	GRM155R71A224KE01_
GRM188R11A124KA01_	GRM155R71A224KE01_
GRM188R11A124KA01_	GRM155R71A224KE01_
GRM188R11A124MA01_	GRM155R71A224ME01_
GRM188R11A124JA01_	GRM155R71A224KE01_
GRM188R11A154KA01_	GRM155R71A224KE01_
GRM188R11A154KA01_	GRM155R71A224KE01_
GRM188R11A154KC01_	GRM155R71A224KE01_
GRM188R11A154MA01_	GRM155R71A224ME01_
GRM188R11A154JA01_	GRM155R71A224KE01_

GRM188R11A184KA01_	GRM155R71A224KE01_
GRM188R11A184KA01_	GRM155R71A224KE01_
GRM188R11A184MA01_	GRM155R71A224ME01_
GRM188R11A184JA01_	GRM155R71A224KE01_
GRM188R61A224KA01_	GRM155R71A224KE01_
GRM188R61A124JA01_	GRM155R71A224KE01_
GRM188R61A154JA01_	GRM155R71A224KE01_
GRM188R61A184JA01_	GRM155R71A224KE01_
GRM185B31E105MA12_	GRM155R61E105MA12_
GRM185B31C105KE43_	GRM155R61C105KA12_
GRM185B31C105KE43_	GRM155R61C105KA12_
GRM185B31C105KE43_	GRM155R61C105KA12_
GRM185B31C105ME43_	GRM155R61C105MA12_
GRM185B30J225KE25_	GRM155R60J225KE01_
GRM185B30J225KE25_	GRM155R60J225KE01_

GRM185B30J225KE42_	GRM155R60J225KE01_
GRM185B30J225KE42_	GRM155R60J225KE01_
GRM185B30J225ME25_	GRM155R60J225ME01_
GRM185B31A225KE43_	GRM155R61A225KE01_
GRM185B31A225ME43_	GRM155R61A225ME01_
GRM185B30G475ME15_	GRM155R60G475ME47_
GRM185B30J475ME15_	GRM155R60J475ME47_
GRM185B30J475ME15_	GRM155R60J475ME47_
GRM185B10J105KE21_	GRM155R70J105KA12_
GRM185B30J105KE25_	GRM155R70J105KA12_
GRM185B30J105KE25_	GRM155R70J105KA12_
GRM185R60J105KE21_	GRM155R70J105KA12_
GRM185R60J105KE26_	GRM155R70J105KA12_
GRM185C80E475ME15_	GRM155D80E475ME47_
GRM185D71A105KE36_	GRM155C71A105KE11_
GRM185D71A105ME36_	GRM155C71A105ME11_
GRM216B11A224KC01_	GRM033R61A224KE90_
GRM216B11A224MC01_	GRM033R61A224ME90_
GRM219B11C224KA01_	GRM033R61C224KE14_
GRM219B11C224KA01_	GRM033R61C224KE14_
GRM219B11C224KC01_	GRM033R61C224KE14_
GRM219B11C224KC01_	GRM033R61C224KE14_

GRM219B11C224KC01_	GRM033R61C224KE14_
GRM219B11C224MA01_	GRM033R61C224ME14_
GRM219B11C224JA01_	GRM033R61C224KE14_
GRM219R11C224KA01_	GRM033R61C224KE14_
GRM219R11C224KC01_	GRM033R61C224KE14_
GRM219R11C224KC01_	GRM033R61C224KE14_
GRM219R11C224MA01_	GRM033R61C224ME14_
GRM219R11C224JA01_	GRM033R61C224KE14_
GRM219R11C224JA01_	GRM033R61C224KE14_
GRM216R11A334KA01_	GRM155R71A474KE01_
GRM216R11A334KC01_	GRM155R71A474KE01_
GRM216R11A334MA01_	GRM155R71A474ME01_
GRM216R61A105MA01_	GRM153R61A105ME95_
GRM216B11A105MA01_	GRM153R61A105ME95_
GRM216R61A105KA01_	GRM033R61A105ME01_

GRM216B11A105KA01_	GRM033R61A105ME01_
GRM216R71A224KC01_	GRM155R71A224KE01_
GRM216C81C105KA12_	GRM155C81C105KE15_
GRM216C81C105MA12_	GRM155C81C105ME15_
GRM216R61C105KA30_	GRM155R61C105KA12_
GRM216R61C105KA88_	GRM155R61C105KA12_
GRM216R61C105MA30_	GRM155R61C105MA12_
GRM216R61C105MA88_	GRM155R61C105MA12_
GRM216R61E105KA12_	GRM155R61E105KA12_
GRM216R61E105KA12_	GRM155R61E105KA12_
GRM216R61E105MA12_	GRM155R61E105MA12_
GRM216R71A334KA01_	GRM155R71A474KE01_
GRM216R71A334KC01_	GRM155R71A474KE01_
GRM216R71A334MA01_	GRM155R71A474ME01_
GRM216B31C105KA87_	GRM155R61C105KA12_
GRM216B31C105KA87_	GRM155R61C105KA12_
GRM216B31C105MA87_	GRM155R61C105MA12_
GRM216B31C105MA87_	GRM155R61C105MA12_
GRM216B31E105KA75_	GRM155R61E105KA12_

GRM216B31E105KA75_	GRM155R61E105KA12_
GRM216B31E105KA75_	GRM155R61E105KA12_
GRM216B31E105MA75_	GRM155R61E105MA12_
GRM216B31E105MA75_	GRM155R61E105MA12_
GRM216B11A274KC01_	GRM155R71A474KE01_
GRM216B11A334KA01_	GRM155R71A474KE01_
GRM216B11A334KA01_	GRM155R71A474KE01_
GRM216B11A334KC01_	GRM155R71A474KE01_
GRM216B11A334MA01_	GRM155R71A474ME01_
GRM216B11A394KC01_	GRM155R71A474KE01_
GRM216R11A224KC01_	GRM155R71A224KE01_
GRM216R11A224MC01_	GRM155R71A224ME01_
GRM216R11A274KC01_	GRM155R71A474KE01_
GRM216R11A394KC01_	GRM155R71A474KE01_

GRM216R61A334KA01_	GRM155R71A474KE01_
GRM216R61A334MA01_	GRM155R71A474ME01_
GRM216D71C105KA12_	GRM155C71C105KE11_
GRM216D71C105MA12_	GRM155C71C105ME11_
GRT216R61A225KE13_	GRT155R61C225KE13_
GRT216R61A225ME13_	GRT155R61C225KE13_
GRM219R61A105MA01_	GRM153R61A105ME95_
GRM219B11A105MA01_	GRM153R61A105ME95_
GRM219R71C224KA01_	GRM155R71C224KA12_
GRM219R71C224KC01_	GRM155R71C224KA12_
GRM219R71C224MA01_	GRM155R71C224MA12_
GRT219R61A225KE01_	GRT155R61C225KE13_
GRM219C80G106KE19_	GRM155C80G106ME18_
GRT219R61A225ME01_	GRT155R61C225KE13_
GRM219R71C224JA01_	GRM155R71C224KA12_
GRM219R60J155KC01_	GRM155R60J225KE01_
GRM219R61A105KA01_	GRM155R61C105KA12_

GRM219R61A105KC01_	GRM155R61C105KA12_
GRM219B11C564KA01_	GRM155R61C105KA12_
GRM219B11C564KA01_	GRM155R61C105KA12_
GRM219B11C564KC01_	GRM155R61C105KA12_
GRM219B11C564MA01_	GRM155R61C105MA12_
GRM219B11C564JA01_	GRM155R61C105KA12_
GRM219B11C684KA01_	GRM155R61C105KA12_
GRM219B11C684KA01_	GRM155R61C105KA12_
GRM219B11C684KC01_	GRM155R61C105KA12_
GRM219B11C684MA01_	GRM155R61C105MA12_
GRM219B11C684JA01_	GRM155R61C105KA12_
GRM219B31A335ME18_	GRM155R61A475ME01_

GRM219B31A335ME18_	GRM155R61A475ME01_
GRM219B31A335KE18_	GRM155R61A475ME01_
GRM219B31A335KE18_	GRM155R61A475ME01_
GRM219B11A105KA01_	GRM155R61C105KA12_
GRM219B11A105KA01_	GRM155R61C105KA12_
GRM219B11A105KC01_	GRM155R61C105KA12_
GRM219B11A105KC01_	GRM155R61C105KA12_
GRM219R11C564MA01_	GRM155C71C105ME11_
GRM219R11C564KA01_	GRM155C71C105KE11_
GRM219R11C564KC01_	GRM155C71C105KE11_
GRM219R11C564JA01_	GRM155C71C105KE11_
GRM219R11C684MA01_	GRM155C71C105ME11_

GRM219R11C684MC01_	GRM155C71C105ME11_
GRM219R11C684KA01_	GRM155C71C105KE11_
GRM219R11C684KA01_	GRM155C71C105KE11_
GRM219R11C684KC01_	GRM155C71C105KE11_
GRM219R11C684JA01_	GRM155C71C105KE11_
GRM219R71C564MA01_	GRM155C71C105ME11_
GRM219R71C564KA01_	GRM155C71C105KE11_
GRM219R71C564KC01_	GRM155C71C105KE11_
GRM219R71C564JA01_	GRM155C71C105KE11_
GRM219R71C684MA01_	GRM155C71C105ME11_
GRM219R71C684KA01_	GRM155C71C105KE11_
GRM219R71C684KC01_	GRM155C71C105KE11_

GRM219R71C684KC37_	GRM155C71C105KE11_
GRM219R71C684JA01_	GRM155C71C105KE11_
GRT219C80J475ME01_	GRT155C81A475ME13_
GRT219C80J475KE01_	GRT155C81A475ME13_
GRM21BR61A684MA01_	GRM153R61A105ME95_
GRM21BR61A824MA01_	GRM153R61A105ME95_
GRM21BB11A684MA01_	GRM153R61A105ME95_
GRM21BB11A824MA01_	GRM153R61A105ME95_
GRM21BR61C824KA01_	GRM155R61C105KA12_
GRM21BR61C824MA01_	GRM155R61C105MA12_
GRM21BR61C824JA01_	GRM155R61C105KA12_
GRM21BR61A684KA01_	GRM155R61C105KA12_
GRM21BR61A824KA01_	GRM155R61C105KA12_

GRM21BB31H154JA88_	GRM155R61H224KE01_
GRM21BB31H184KA88_	GRM155R61H224KE01_
GRM21BB31H184MA88_	GRM155R61H224ME01_
GRM21BB31H184JA88_	GRM155R61H224KE01_
GRM21BB31E564KA87_	GRM155R61E105KA12_
GRM21BB31E564KA87_	GRM155R61E105KA12_
GRM21BB31E564MA87_	GRM155R61E105MA12_
GRM21BB31E684KA87_	GRM155R61E105KA12_
GRM21BB31E684KA87_	GRM155R61E105KA12_
GRM21BB31E684MA87_	GRM155R61E105MA12_
GXM21BB31E684KA87_	GXM155R61E105KA10_
GRM21BB31E824KA87_	GRM155R61E105KA12_

GRM21BB31E824MA87_	GRM155R61E105MA12_
GRM21BB11C824KA01_	GRM155R61C105KA12_
GRM21BB11C824KA01_	GRM155R61C105KA12_
GRM21BB11C824KA01_	GRM155R61C105KA12_
GRM21BB11C824KC01_	GRM155R61C105KA12_
GRM21BB11C824MA01_	GRM155R61C105MA12_
GRM21BB11C824JA01_	GRM155R61C105KA12_
GRM21BB11A684KA01_	GRM155R61C105KA12_
GRM21BB11A684KA01_	GRM155R61C105KA12_
GRM21BB11A684KA01_	GRM155R61C105KA12_
GRM21BB11A684KA01_	GRM155R61C105KA12_

GRM21BB11A824KA01_	GRM155R61C105KA12_
GRM21BB11A824KA01_	GRM155R61C105KA12_
GRM21BB11E334KA01_	GRM155R61H334KE01_
GRM21BB11E334KA01_	GRM155R61H334KE01_
GRM21BB11E334KA01_	GRM155R61H334KE01_
GRM21BB11E334KA01_	GRM155R61H334KE01_
GRM21BB11E334KA01_	GRM155R61H334KE01_
GRM21BB11E334KC01_	GRM155R61H334KE01_
GRM21BB11E334KC01_	GRM155R61H334KE01_
GRM21BB11E334MA01_	GRM155R61H334ME01_
GRM21BR11E564MA88_	GRM155R61E105MA12_
GRM21BR11E684MA88_	GRM155R61E105MA12_
GRM21BR11E824MA88_	GRM155R61E105MA12_

GRM21BR11A684MA01_	GRM155C71A105ME11_
GRM21BR11A684KA01_	GRM155C71A105KE11_
GRM21BR11A824MA01_	GRM155C71A105ME11_
GRM21BR11C824MA01_	GRM155C71C105ME11_
GRM21BR11A824KA01_	GRM155C71A105KE11_
GRM21BR11C824KA01_	GRM155C71C105KE11_
GRM21BR11C824JA01_	GRM155C71C105KE11_
GRM21BR11E564KA88_	GRM155D71E105KE11_
GRM21BR11E684KA88_	GRM155D71E105KE11_
GRM21BR11E684KA88_	GRM155D71E105KE11_
GRM21BR11E824KA88_	GRM155D71E105KE11_
GRM21BR71E684MA88_	GRM155R61E105MA12_

GRM21BR71E824MA88_	GRM155R61E105MA12_
GRM21BR71A684MA01_	GRM155C71A105ME11_
GRM21BR71A684KA01_	GRM155C71A105KE11_
GRM21BR71A684KA36_	GRM155C71A105KE11_
GRM21BR71A824MA01_	GRM155C71A105ME11_
GRM21BR71C824MA01_	GRM155C71C105ME11_
GRM21BR71A824KA01_	GRM155C71A105KE11_
GRM21BR71C824KA01_	GRM155C71C105KE11_
GRM21BR71C824KC01_	GRM155C71C105KE11_
GRM21BR71C824JA01_	GRM155C71C105KE11_
GRM21BR71H154JA01_	GRM155D71H224KE01_

GRM21BR71H184JA01_	GRM155D71H224KE01_
GRM21BR71E564KA88_	GRM155D71E105KE11_
GRM21BR71E564MA88_	GRM155D71E105KE11_
GRM21BR71E564JA88_	GRM155D71E105KE11_
GRM21BR71E684KA88_	GRM155D71E105KE11_
GRM21BR71E684KA88_	GRM155D71E105KE11_
GRM21BR71E684JA88_	GRM155D71E105KE11_
GRM21BR71E824KA88_	GRM155D71E105KE11_
GRM21BR71E824JA88_	GRM155D71E105KE11_
GRM216R61C225KA12_	GRM155R61C225KE11_
GRM216R61C225MA12_	GRM155R61C225ME11_
GRM216B31C225KA12_	GRM155R61C225KE11_
GRM216B31C225MA12_	GRM155R61C225ME11_
GRM216B31A225KE23_	GRM188R71A225KE15_

GRM216B31A225KE23_	GRM188R71A225KE15_
GRM216B31A225ME23_	GRM188R71A225ME15_
GRM216B31A225ME23_	GRM188R71A225ME15_
GRT216R61C105KE01_	GRT188R71C105KE13_
GRM216R61A225KE24_	GRM188R71A225KE15_
GRM216R61A225ME24_	GRM188R71A225ME15_
GRT216R61E105KE01_	GRT188R71E105KE13_
GRT216R61C105ME01_	GRT188R71C105KE13_
GRT216R61E105ME01_	GRT188R71E105KE13_
GRT216R61A105KE01_	GRT188R71C105KE13_
GRT216R61A105ME01_	GRT188R71C105KE13_
GRT216R61C225KE13_	GRT188C71C225KE13_
GRT216R61C225ME13_	GRT188C71C225KE13_
GRT216C81C105KE01_	GRT188R71C105KE13_

GRT216C81C105ME01_	GRT188R71C105KE13_
GRM219C80J475ME32_	GRM185C80J475ME11_
GRM219R61A475KE32_	GRM155R61A475ME01_
GRM219R61A475ME32_	GRM155R61A475ME01_
GRM219C80J475KE32_	GRM155C80J475ME01_
GRM219C80J475KE32_	GRM155C80J475ME01_
GRM219B31A475KE31_	GRM155R61A475ME01_
GRM219B31A475ME31_	GRM155R61A475ME01_
GRM219B30J475ME31_	GRM185C80J475ME11_
GRM219B10J475KE11_	GRM185C80J475ME11_
GRM219B30J475KE31_	GRM185C80J475ME11_
GRM219B30J475KE31_	GRM185C80J475ME11_
GRM219R60J475ME32_	GRM185C80J475ME11_
GRM219R60J475KE11_	GRM185C80J475ME11_
GRM219R60J475KE32_	GRM185C80J475ME11_

GRM219C81A475KE34_	GRM185C81A475KE11_
GRM219C81A475ME34_	GRM185C81A475ME11_
GRM219C80J475ME19_	GRM185C80J475ME11_
GRM219R61A335KE19_	GRM155R61A475ME01_
GRM219R61A335ME19_	GRM155R61A475ME01_
GRM219R61C335KA12_	GRM185R61C475KE11_
GRM219R61C335MA12_	GRM185R61C475ME11_
GRM219R61A475KE19_	GRM155R61A475ME01_
GRM219R61A475KE19_	GRM155R61A475ME01_
GRM219R61A475KE34_	GRM155R61A475ME01_
GRM219R61A475KE34_	GRM155R61A475ME01_
GRM219R61A475ME34_	GRM155R61A475ME01_
GRM219C80J475KE19_	GRM155C80J475ME01_
GRM219B31C335KA12_	GRM185R61C475KE11_
GRM219B31C335MA12_	GRM185R61C475ME11_
GRM219B31A475KE18_	GRM155R61A475ME01_

GRM219B31A475KE18_	GRM155R61A475ME01_
GRM219B31A475KE33_	GRM155R61A475ME01_
GRM219B31A475KE33_	GRM155R61A475ME01_
GRM219B31A475ME33_	GRM155R61A475ME01_
GRM219B31A475ME33_	GRM155R61A475ME01_
GRM219B10J475ME01_	GRM185C80J475ME11_
GRM219B30J475ME18_	GRM185C80J475ME11_
GRM219B30J475ME18_	GRM185C80J475ME11_
GRM219B10J475KE01_	GRM185C80J475ME11_
GRM219B30J475KE18_	GRM185C80J475ME11_
GRM219B30J475KE18_	GRM185C80J475ME11_
GRM219R60J475ME01_	GRM185C80J475ME11_
GRM219R60J475ME19_	GRM185C80J475ME11_
GRM219R60J475KE01_	GRM185C80J475ME11_

GRM219R60J475KE19_	GRM185C80J475ME11_
GRM219R60J475KE19_	GRM185C80J475ME11_
GRM219R60J475KE19_	GRM185C80J475ME11_
GRM219R71C474KA01_	GRM188R71C474KA88_
GRM219R71C474KC01_	GRM188R71C474KA88_
GRM219R71C474MA01_	GRM188R71C474MA88_
GRM219R71C474MC01_	GRM188R71C474MA88_
GRM219C80G106ME12_	GRM188C80G106ME47_
GRM219C80G106ME19_	GRM188C80G106ME47_
GRM219R60J106KE17_	GRM188R60J106KE47_
GRM219R60J106KE19_	GRM188R60J106KE47_
GRM219R60J106KE19_	GRM188R60J106KE47_
GRM219R60J106KE28_	GRM188R60J106KE47_
GRT219C80G106ME01_	GRT188C80G106ME13_
GRT219R61A226ME13_	GRT188R61A226ME13_
GRM219C81C225KA12_	GRM188C81C225KA12_
GRM219C81C225MA12_	GRM188C81C225MA12_
GRM219R61E225KA12_	GRM188R61E225KA12_
GRM219R61E225KA12_	GRM188R61E225KA12_
GRM219R61E225KA12_	GRM188R61E225KA12_
GRM219R61E225MA12_	GRM188R61E225MA12_
GRM219R61E225MA12_	GRM188R61E225MA12_

GRM219D71A475KE15_	GRM188D71A475KE11_
GRM219D71A475ME15_	GRM188D71A475ME11_
GRM219R60J106ME17_	GRM188R60J106ME47_
GRM219R60J106ME19_	GRM188R60J106ME47_
GRM219R71E224JA01_	GRM188R71E224JA88_
GRM219R71E224KA01_	GRM188R71E224KA88_
GRM219R71E224KC01_	GRM188R71E224KA88_
GRM219R71E224MA01_	GRM188R71E224MA88_
GRM219R71E224MC01_	GRM188R71E224MA88_
GRT219R60J106ME01_	GRT188R60J106ME13_
GRM219R71C474JA01_	GRM188R71C474KA88_
GRM219R71C274KA01_	GRM188R71C474KA88_
GRM219R71C274KC01_	GRM188R71C474KA88_
GRM219R71C274MA01_	GRM188R71C474MA88_
GRM219R71C274JA01_	GRM188R71C474KA88_
GRM219R71E274JA01_	GRM188R71E474KA12_
GRT219R61C335KE01_	GRT188R61C475KE13_
GRT219R61C335ME01_	GRT188R61C475KE13_

GRT219C81A475ME01_	GRT188C81C475KE13_
GRM219R61C225KA88_	GRM155R61C225KE11_
GRM219R61C225KA88_	GRM155R61C225KE11_
GRM219R61C225KA88_	GRM155R61C225KE11_
GRM219R61C225MA88_	GRM155R61C225ME11_
GRT219C81A475KE01_	GRT188C81C475KE13_
GRT219R61A335KE01_	GRT188R61C475KE13_
GRT219R61A335ME01_	GRT188R61C475KE13_
GRT219R60J106KE01_	GRT188R61A106KE13_
GRM219B30J106KE18_	GRM188R60J106KE47_
GRM219B30J106KE18_	GRM188R60J106KE47_
GRM219B31E225KA75_	GRM188R61E225KA12_
GRM219B31E225KA75_	GRM188R61E225KA12_
GRM219B31E225KA75_	GRM188R61E225KA12_
GRM219B31E225MA75_	GRM188R61E225MA12_
GRM219B31E225MA75_	GRM188R61E225MA12_

GRM219B31E225MA75_	GRM188R61E225MA12_
GRM219B30J106ME18_	GRM188R60J106ME47_
GRM219B30J106ME18_	GRM188R60J106ME47_
GRM219B31C225KA87_	GRM155R61C225KE11_
GRM219B31C225KA87_	GRM155R61C225KE11_
GRM219B31C225MA87_	GRM155R61C225ME11_
GRM219B31C225MA87_	GRM155R61C225ME11_
GRM219B11C474KA01_	GRM188R71C474KA88_
GRM219B11C474KA01_	GRM188R71C474KA88_
GRM219B11C474KC01_	GRM188R71C474KA88_
GRM219B11C474KC01_	GRM188R71C474KA88_
GRM219B11C474MA01_	GRM188R71C474MA88_
GRM219B11A225KA01_	GRM188R71A225KE15_
GRM219B11A225MA01_	GRM188R71A225ME15_
GRM219B11A225MA01_	GRM188R71A225ME15_
GRM219B11E224JA01_	GRM188R71E224JA88_

GRM219B11E224KA01_	GRM188R71E224KA88_
GRM219B11E224KA01_	GRM188R71E224KA88_
GRM219B11E224KA22_	GRM188R71E224KA88_
GRM219B11E224KC01_	GRM188R71E224KA88_
GRM219B11E224KC01_	GRM188R71E224KA88_
GRM219B11E224KC01_	GRM188R71E224KA88_
GRM219B11E224MA01_	GRM188R71E224MA88_
GRM219B11C474JA01_	GRM188R71C474KA88_
GRM219B11C274KA01_	GRM188R71C474KA88_
GRM219B11C274KC01_	GRM188R71C474KA88_
GRM219B11C274KC01_	GRM188R71C474KA88_
GRM219B11C274MA01_	GRM188R71C474MA88_
GRM219B11E274KA01_	GRM188R71E474KA12_
GRM219B11E274KC01_	GRM188R71E474KA12_

GRM219B11E274MA01_	GRM188R71E474MA12_
GRM219B11C274JA01_	GRM188R71C474KA88_
GRM219B11E274JA01_	GRM188R71E474KA12_
GRM219R11C474KA01_	GRM188R71C474KA88_
GRM219R11C474KA01_	GRM188R71C474KA88_
GRM219R11C474KC01_	GRM188R71C474KA88_
GRM219R11C474MA01_	GRM188R71C474MA88_
GRM219R11E224JA01_	GRM188R71E224JA88_
GRM219R11E224KA01_	GRM188R71E224KA88_
GRM219R11E224KC01_	GRM188R71E224KA88_
GRM219R11E224KC18_	GRM188R71E224KA88_
GRM219R11E224MA01_	GRM188R71E224MA88_
GRM219R11C474JA01_	GRM188R71C474KA88_
GRM219R11C274KA01_	GRM188R71C474KA88_

GRM219R11C274MA01_	GRM188R71C474MA88_
GRM219R11E274KA01_	GRM188R71E474KA12_
GRM219R11E274KC01_	GRM188R71E474KA12_
GRM219R11E274MA01_	GRM188R71E474MA12_
GRM219R71E274KA01_	GRM188R71E474KA12_
GRM219R71E274MA01_	GRM188R71E474MA12_
GRM219R11C274JA01_	GRM188R71C474KA88_
GRM219R11C274JC01_	GRM188R71C474KA88_
GRM219R11E274JA01_	GRM188R71E474KA12_
GRM219R61E474KC36_	GRM188R71E474KA12_
GRM219R61A225KA01_	GRM188R71A225KE15_
GRM219R61A225MA01_	GRM188R71A225ME15_
GRM219R60J226ME47_	GRM188R60J226MEA0_

GRM219R60J226ME58_	GRM188R60J226MEA0_
GRM219R60J226MEA0_	GRM188R60J226MEA0_
GRM219R61A226MEA0_	GRM188R61A226ME15_
GRM219R60G226ME66_	GRM188R60G226MEA0_
GRT219C80G106KE01_	GRT188C80J106ME13_
GRM219C80E226ME47_	GRM188C80G226ME15_
GRT219R61E225KE01_	GRT188R61H225KE13_
GRT219R61E225ME01_	GRT188R61H225KE13_
GRM219B30J226ME47_	GRM188R60J226MEA0_
GRM219B30J226MEA0_	GRM188R60J226MEA0_
GRM219B31A226MEA0_	GRM188R61A226ME15_
GRM219B31A226MEA0_	GRM188R61A226ME15_
GRM219B30G226ME66_	GRM188R60G226MEA0_
GRT219R61C225KE01_	GRT188C71C225KE13_
GRT219R61C225ME01_	GRT188C71C225KE13_
GRT219C81C225KE01_	GRT188C71C225KE13_

GRT219C81C225ME01_	GRT188C71C225KE13_
GRM219D71C225KA12_	GRM188C71C225KE11_
GRM219D71C225MA12_	GRM188C71C225ME11_
GRM21BR71H124KA36_	GRM188R71H224KAC4_
GRM21BR71H154KA01_	GRM188R71H224KAC4_
GRM21BR71H154KA01_	GRM188R71H224KAC4_
GRM21BR71H154KA36_	GRM188R71H224KAC4_
GRM21BR71H154MA01_	GRM188R71H224MAC4_
GRM21BR71H164KA36_	GRM188R71H224KAC4_
GRM21BR71H184KA01_	GRM188R71H224KAC4_
GRM21BR71H184KA36_	GRM188R71H224KAC4_
GRM21BR71H184MA01_	GRM188R71H224MAC4_
GRM21BR71C334KA01_	GRM188R71C474KA88_
GRM21BR71C334KA30_	GRM188R71C474KA88_
GRM21BR71C334KA36_	GRM188R71C474KA88_
GRM21BR71C334MA01_	GRM188R71C474MA88_

GRM21BR71E334KA01_	GRM188R71E474KA12_
GRM21BR71E334KA30_	GRM188R71E474KA12_
GRM21BR71E334KC01_	GRM188R71E474KA12_
GRM21BR71E334MA01_	GRM188R71E474MA12_
GRM21BR71C334JA01_	GRM188R71C474KA88_
GRM21BR71E334JA01_	GRM188R71E474KA12_
GRM21BR71C394KA01_	GRM188R71C474KA88_
GRM21BR71C394KA36_	GRM188R71C474KA88_
GRM21BR71C394MA01_	GRM188R71C474MA88_
GRM21BR71E394KA01_	GRM188R71E474KA12_
GRM21BR71E394MA01_	GRM188R71E474MA12_
GRM21BR71C394JA01_	GRM188R71C474KA88_
GRM21BR71E394JA01_	GRM188R71E474KA12_
GRM21BB11C334KA01_	GRM188R71C474KA88_

GRM21BB11C334KA01_	GRM188R71C474KA88_
GRM21BB11C334KA01_	GRM188R71C474KA88_
GRM21BB11C334KA01_	GRM188R71C474KA88_
GRM21BB11C334KA01_	GRM188R71C474KA88_
GRM21BB11C334KC01_	GRM188R71C474KA88_
GRM21BB11C334MA01_	GRM188R71C474MA88_
GRM21BB11C334JA01_	GRM188R71C474KA88_
GRM21BB11E334JA01_	GRM188R71E474KA12_
GRM21BB11E334JC01_	GRM188R71E474KA12_
GRM21BB11C394KA01_	GRM188R71C474KA88_
GRM21BB11C394KA01_	GRM188R71C474KA88_

GRM21BB11C394KA01_	GRM188R71C474KA88_
GRM21BB11C394MA01_	GRM188R71C474MA88_
GRM21BB11E394KA01_	GRM188R71E474KA12_
GRM21BB11E394KA01_	GRM188R71E474KA12_
GRM21BB11E394KC01_	GRM188R71E474KA12_
GRM21BB11E394MA01_	GRM188R71E474MA12_
GRM21BB11C394JA01_	GRM188R71C474KA88_
GRM21BB11E394JA01_	GRM188R71E474KA12_
GRM21BR11C334KA01_	GRM188R71C474KA88_
GRM21BR11C334KA01_	GRM188R71C474KA88_
GRM21BR11C334KC01_	GRM188R71C474KA88_
GRM21BR11C334MA01_	GRM188R71C474MA88_

GRM21BR11E334KA01_	GRM188R71E474KA12_
GRM21BR11E334KA01_	GRM188R71E474KA12_
GRM21BR11E334KC01_	GRM188R71E474KA12_
GRM21BR11E334MA01_	GRM188R71E474MA12_
GRM21BR11E334MC01_	GRM188R71E474MA12_
GRM21BR71E334KA01_	GRM188R71E474KA12_
GRM21BR11C334JA01_	GRM188R71C474KA88_
GRM21BR11E334JA01_	GRM188R71E474KA12_
GRM21BR11C394KA01_	GRM188R71C474KA88_
GRM21BR11C394MA01_	GRM188R71C474MA88_
GRM21BR11E394KA01_	GRM188R71E474KA12_
GRM21BR11E394KC01_	GRM188R71E474KA12_

GRM21BR11E394MA01_	GRM188R71E474MA12_
GRM21BR11C394JA01_	GRM188R71C474KA88_
GRM21BR11E394JA01_	GRM188R71E474KA12_
GRM21BR61C334KA01_	GRM188R71C474KA88_
GRM21BR61C334MA01_	GRM188R71C474MA88_
GRM21BR61C334JA01_	GRM188R71C474KA88_
GRM21BR61C394KA01_	GRM188R71C474KA88_
GRM21BR61C394MA01_	GRM188R71C474MA88_
GRM21BR61C394JA01_	GRM188R71C474KA88_
GCM21BR71C334KA14_	GCM188R71C334KA37_
GCM21BR71C334KA51_	GCM188R71C334KA37_
GCM21BR71E154KA01_	GCM188R71E154KA37_
GCM21BR71E154KA02_	GCM188R71E154KA37_
GCM21BR71E154KA14_	GCM188R71E154KA37_

GCM21BR71E154KA15_	GCM188R71E154KA37_
GCM21BR71E154KA37_	GCM188R71E154KA37_
GCM21BR71E154KA66_	GCM188R71E154KA37_
GCM21BR71E154MA01_	GCM188R71E154MA37_
GCM21BR71E154MA37_	GCM188R71E154MA37_
GCM21BR71E154MA66_	GCM188R71E154MA37_
GCM21BR71E184KA01_	GCM188R71E184KA55_
GCM21BR71E184KA02_	GCM188R71E184KA55_
GCM21BR71E184KA37_	GCM188R71E184KA55_
GCM21BR71E184MA01_	GCM188R71E184MA55_
GCM21BR71E184MA37_	GCM188R71E184MA55_
GCM21BR71E154JA14_	GCM188R71E154KA37_
GCM21BR71E154JA37_	GCM188R71E154KA37_
GCM21BR71E154JA66_	GCM188R71E154KA37_
GCM21BR71E184JA37_	GCM188R71E184KA55_
GCM21BR11E154KA01_	GCM188R71E154KA37_
GCM21BR11E154MA01_	GCM188R71E154MA37_
GCM21BR11E184KA01_	GCM188R71E184KA55_
GCM21BR11E184MA01_	GCM188R71E184MA55_
GRM21BB31H154KA88_	GRM155R61H224KE01_

GRM21BB31H154KA88_	GRM155R61H224KE01_
GRM21BB31H154MA88_	GRM155R61H224ME01_
GRM319R71H221KA01_	GRM033R71H221KA12_
GRM319R71H221MA01_	GRM033R71H221MA12_
GRM319R71H331KA01_	GRM033R71H331KA12_
GRM319R71H331MA01_	GRM033R71H331MA12_
GRM319R71H391KA01_	GRM033R71H391KA12_
GRM319R71H391MA01_	GRM033R71H391MA12_
GRM319R71H471KA01_	GRM033R71H471KA12_
GRM319R71H471MA01_	GRM033R71H471MA12_
GRM319R71H561KA01_	GRM033R71H561KA12_
GRM319R71H561MA01_	GRM033R71H561MA12_
GRM319R71H681KA01_	GRM033R71H681KA12_
GRM319R71H681MA01_	GRM033R71H681MA12_
GRM319R71H821KA01_	GRM033R71H821KA12_
GRM319R71H821MA01_	GRM033R71H821MA12_
GRM319R71H102KA01_	GRM033R71H102KA12_
GRM319R71H102MA01_	GRM033R71H102MA12_
GRM319R71H152KA01_	GRM033R71H152KA12_
GRM319R71H152MA01_	GRM033R71H152MA12_
GRM319R71H122KA01_	GRM033R71H122KA12_
GRM319R71H122MA01_	GRM033R71H122MA12_
GRM319R71H271KA01_	GRM033R71H271KA12_

GRM319R71H271MA01_	GRM033R71H271MA12_
GRM319R71H221JA01_	GRM033R71H221KA12_
GRM319R71H331JA01_	GRM033R71H331KA12_
GRM319R71H391JA01_	GRM033R71H391KA12_
GRM319R71H471JA01_	GRM033R71H471KA12_
GRM319R71H561JA01_	GRM033R71H561KA12_
GRM319R71H681JA01_	GRM033R71H681KA12_
GRM319R71H821JA01_	GRM033R71H821KA12_
GRM319R71H102JA01_	GRM033R71H102KA12_
GRM319R71H102JA01_	GRM033R71H102KA12_
GRM319R71H152JA01_	GRM033R71H152KA12_
GRM319R71H122JA01_	GRM033R71H122KA12_
GRM319R71H271JA01_	GRM033R71H271KA12_
GRM319B11C104KA01_	GRM033R61C104KE14_
GRM319B11C104KA01_	GRM033R61C104KE14_
GRM319B11C104MA01_	GRM033R61C104ME14_
GRM319B11C104MA01_	GRM033R61C104ME14_

GRM319B11C683KA01_	GRM033R61C683KE84_
GRM319B11C683MA01_	GRM033R61C683ME84_
GRM319B11C823KA01_	GRM033R61C823KE84_
GRM319B11C823MA01_	GRM033R61C823ME84_
GRM319B11H221KA01_	GRM033R61H221KA12_
GRM319B11H331KA01_	GRM033R61H331KA12_
GRM319B11H471KA01_	GRM033R61H471KA12_
GRM319B11H471KA59_	GRM033R61H471KA12_
GRM319B11H681KA01_	GRM033R61H681KA12_
GRM319B11H102KA01_	GRM033R61H102KA12_
GRM319B11H102KA01_	GRM033R61H102KA12_
GRM319B11H152KA01_	GRM033R61H152KA12_
GRM319B11E104KA01_	GRM033R61E104KE14_
GRM319B11E104KA01_	GRM033R61E104KE14_
GRM319B11E104KA01_	GRM033R61E104KE14_
GRM319B11E104KA01_	GRM033R61E104KE14_

GRM319B11E104KA22_	GRM033R61E104KE14_
GRM319B11E104MA01_	GRM033R61E104ME14_
GRM319B11E104MA01_	GRM033R61E104ME14_
GRM319B11C224KA01_	GRM033R61C224KE14_
GRM319B11C224KA01_	GRM033R61C224KE14_
GRM319B11C224MA01_	GRM033R61C224ME14_
GRM319B11H221MA01_	GRM033R61H221KA12_
GRM319B11H331MA01_	GRM033R61H331KA12_
GRM319B11H471MA01_	GRM033R61H471KA12_
GRM319B11H681MA01_	GRM033R61H681KA12_
GRM319B11H102MA01_	GRM033R61H102KA12_
GRM319B11H152MA01_	GRM033R61H152KA12_
GRM319B11C104JA01_	GRM033R61C104KE18_
GRM319B11C224JA01_	GRM033R61C224KE14_

GRM319B11C683JA01_	GRM033R61C683KE84_
GRM319B11C823JA01_	GRM033R61C823KE84_
GRM319B11E563KA01_	GRM033R61E104KE14_
GRM319B11E563KA01_	GRM033R61E104KE14_
GRM319B11E563KA01_	GRM033R61E104KE14_
GRM319B11E563MA01_	GRM033R61E104ME14_
GRM319B11E563JA01_	GRM033R61E104KE14_
GRM319B11E683JA01_	GRM033R61E104KE14_
GRM319B11E683KA01_	GRM033R61E104KE14_
GRM319B11E683KA01_	GRM033R61E104KE14_
GRM319B11E683KA01_	GRM033R61E104KE14_
GRM319B11E683MA01_	GRM033R61E104ME14_

GRM319B11E823JA01_	GRM033R61E104KE14_
GRM319B11E823KA01_	GRM033R61E104KE14_
GRM319B11E823KA01_	GRM033R61E104KE14_
GRM319B11E823MA01_	GRM033R61E104ME14_
GRM319B11H391KA01_	GRM033R71H391KA12_
GRM319B11H391MA01_	GRM033R71H391MA12_
GRM319B11H561KA01_	GRM033R71H561KA12_
GRM319B11H561MA01_	GRM033R71H561MA12_
GRM319B11H821KA01_	GRM033R71H821KA12_
GRM319B11H821MA01_	GRM033R71H821MA12_
GRM319B11H122KA01_	GRM033R71H122KA12_
GRM319B11H122MA01_	GRM033R71H122MA12_
GRM319B11H271KA01_	GRM033R71H271KA12_
GRM319B11H271MA01_	GRM033R71H271MA12_
GRM319B11H221JA01_	GRM033R71H221KA12_

GRM319B11H331JA01_	GRM033R71H331KA12_
GRM319B11H391JA01_	GRM033R71H391KA12_
GRM319B11H471JA01_	GRM033R71H471KA12_
GRM319B11H561JA01_	GRM033R71H561KA12_
GRM319B11H681JA01_	GRM033R71H681KA12_
GRM319B11H821JA01_	GRM033R71H821KA12_
GRM319B11H102JA01_	GRM033R71H102KA12_
GRM319B11H152JA01_	GRM033R71H152KA12_
GRM319B11H122JA01_	GRM033R71H122KA12_
GRM319B11H271JA01_	GRM033R71H271KA12_
GRM319R11C104KA01_	GRM033R61C104KE14_
GRM319R11C104KA01_	GRM033R61C104KE14_
GRM319R11C104KA01_	GRM033R61C104KE14_

GRM319R11C104MA01_	GRM033R61C104ME14_
GRM319R11C224JA01_	GRM033R61C224KE14_
GRM319R11C224JA01_	GRM033R61C224KE14_
GRM319R11C683KA01_	GRM033R61C104KE14_
GRM319R11C683MA01_	GRM033R61C104ME14_
GRM319R11C823KA01_	GRM033R61C104KE14_
GRM319R11C823MA01_	GRM033R61C104ME14_
GRM319R11H221KA01_	GRM033R71H221KA12_
GRM319R11H221MA01_	GRM033R71H221MA12_
GRM319R11H331KA01_	GRM033R71H331KA12_
GRM319R11H331MA01_	GRM033R71H331MA12_
GRM319R11H391KA01_	GRM033R71H391KA12_
GRM319R11H391MA01_	GRM033R71H391MA12_
GRM319R11H471KA01_	GRM033R71H471KA12_

GRM319R11H471MA01_	GRM033R71H471MA12_
GRM319R11H561KA01_	GRM033R71H561KA12_
GRM319R11H561MA01_	GRM033R71H561MA12_
GRM319R11H681KA01_	GRM033R71H681KA12_
GRM319R11H681MA01_	GRM033R71H681MA12_
GRM319R11H821KA01_	GRM033R71H821KA12_
GRM319R11H821MA01_	GRM033R71H821MA12_
GRM319R11H102KA01_	GRM033R71H102KA12_
GRM319R11H102KA01_	GRM033R71H102KA12_
GRM319R11H102MA01_	GRM033R71H102MA12_
GRM319R11H152KA01_	GRM033R71H152KA12_
GRM319R11H152MA01_	GRM033R71H152MA12_
GRM319R11H122KA01_	GRM033R71H122KA12_
GRM319R11H122MA01_	GRM033R71H122MA12_
GRM319R11H271KA01_	GRM033R71H271KA12_
GRM319R11H271MA01_	GRM033R71H271MA12_

GRM319R11H221JA01_	GRM033R71H221KA12_
GRM319R11H331JA01_	GRM033R71H331KA12_
GRM319R11H391JA01_	GRM033R71H391KA12_
GRM319R11H471JA01_	GRM033R71H471KA12_
GRM319R11H561JA01_	GRM033R71H561KA12_
GRM319R11H681JA01_	GRM033R71H681KA12_
GRM319R11H821JA01_	GRM033R71H821KA12_
GRM319R11H102JA01_	GRM033R71H102KA12_
GRM319R11H152JA01_	GRM033R71H152KA12_
GRM319R11H122JA01_	GRM033R71H122KA12_
GRM319R11H271JA01_	GRM033R71H271KA12_
GRM319R11C104JA01_	GRM033C71C104KE14_

GRM319R11C683JA01_	GRM033C71C104KE14_
GRM319R11C823JA01_	GRM033C71C104KE14_
GRM319R71C104KA01_	GRM033C71C104KE14_
GRM319R71C104MA01_	GRM033C71C104ME14_
GRM319R71C104JA01_	GRM033C71C104KE14_
GRM319R71C683KA01_	GRM033C71C104KE14_
GRM319R71C683MA01_	GRM033C71C104ME14_
GRM319R71C683JA01_	GRM033C71C104KE14_
GRM319R71C823KA01_	GRM033C71C104KE14_
GRM319R71C823MA01_	GRM033C71C104ME14_
GRM319R71C823JA01_	GRM033C71C104KE14_
GRM319R61A105KA01_	GRM033R61A105ME01_

GRM319B11A105KA01_	GRM033R61A105ME01_
GRM319B11A105KA01_	GRM033R61A105ME01_
GRM319B11A105KC01_	GRM033R61A105ME01_
GRM31MB11E104KA01_	GRM033R61E104KE14_
GRM31MB11E104MA01_	GRM033R61E104ME14_
GRM31MB11C224KA01_	GRM033R61C224KE14_
GRM31MB11C224KA01_	GRM033R61C224KE14_
GRM31MB11C224MA01_	GRM033R61C224ME14_
GRM316R61A225KA01_	GRM155R61A225KE01_
GRM316R61A225MA01_	GRM155R61A225ME01_
GRM316B11A225KA01_	GRM155R61A225KE01_
GRM316B11A225MA01_	GRM155R61A225ME01_
GRM316R61A335ME19_	GRM155R61A475MEAA_
GRM316B31A335ME18_	GRM155R61A475MEAA_
GRM316B31A335ME18_	GRM155R61A475MEAA_
GRM319R72A221KA01_	GRM155R72A221KA01_

GRM319R72A221MA01_	GRM155R72A221MA01_
GRM319R72A471KA01_	GRM155R72A471KA01_
GRM319R72A471MA01_	GRM155R72A471MA01_
GRM319R72A102KA01_	GRM155R72A102KA01_
GRM319R72A102KA26_	GRM155R72A102KA01_
GRM319R72A102MA01_	GRM155R72A102MA01_
GRM319R71H222JA01_	GRM155R71H222JA01_
GRM319R71H222KA01_	GRM155R71H222KA01_
GRM319R71H222MA01_	GRM155R71H222MA01_
GRM319R71H472JA01_	GRM155R71H472JA01_
GRM319R71H472JA01_	GRM155R71H472JA01_
GRM319R71H472KA01_	GRM155R71H472KA01_
GRM319R71H472MA01_	GRM155R71H472MA01_
GRM319R72A222KA01_	GRM155R72A222KA01_
GRM319R72A222KA01_	GRM155R72A222KA01_
GRM319R72A222KA26_	GRM155R72A222KA01_
GRM319R72A222MA01_	GRM155R72A222MA01_
GRM319R72A472KA01_	GRM155R72A472KA01_
GRM319R72A472MA01_	GRM155R72A472MA01_
GCM319R71H104KA01_	GCM155R71H104KE37_
GCM319R71H104KA02_	GCM155R71H104KE37_
GCM319R71H104KA17_	GCM155R71H104KE37_
GCM319R71H104KA37_	GCM155R71H104ME37_
GCM319R71H104KA37_	GCM155R71H104KE37_
GCM319R71H104MA01_	GCM155R71H104ME37_

GCM319R71H104MA02_	GCM155R71H104ME37_
GCM319R71H104MA37_	GCM155R71H104ME37_
GCM319R71H153KA01_	GCM155R71H153KA55_
GCM319R71H153MA01_	GCM155R71H153MA55_
GCM319R71H223KA01_	GCM155R71H223KA55_
GCM319R71H223KA02_	GCM155R71H223KA55_
GCM319R71H223MA01_	GCM155R71H223MA55_
GRM319R71E104KA01_	GRM155R71E104KE14_
GRM319R71E104MA01_	GRM155R71E104ME14_
GRM319R71H104KA01_	GRM155R71H104KE14_
GRM319R71H104KA01_	GRM155R71H104KE14_
GRM319R71H104KA01_	GRM155R71H104KE14_
GRM319R71H104KA26_	GRM155R71H104KE14_
GRM319R71H104MA01_	GRM155R71H104ME14_
GRM319R71H104MA01_	GRM155R71H104ME14_
GRM319R71H224KA01_	GRM155R71C224KA12_
GRM319R71H224KA01_	GRM155R71C224KA12_
GRM319R71H224KA26_	GRM155R71C224KA12_
GRM319R71H224MA01_	GRM155R71C224MA12_
GRM319R61A225KA01_	GRM155R61A225KE01_
GRM319R61E105KC36_	GRM155R61E105KA12_
GRM319R61E105MC36_	GRM155R61E105MA12_
GCM319R71H221KA01_	GCM155R71H221KA37_
GCM319R71H221MA01_	GCM155R71H221MA37_
GCM319R72A221KA01_	GCM155R72A221KA37_

GCM319R72A221MA01_	GCM155R72A221MA37_
GCM319R71H331KA01_	GCM155R71H331KA37_
GCM319R71H331MA01_	GCM155R71H331MA37_
GCM319R72A331KA01_	GCM155R72A331KA37_
GCM319R72A331MA01_	GCM155R72A331MA37_
GCM319R71H391KA01_	GCM155R71H391KA37_
GCM319R71H391MA01_	GCM155R71H391MA37_
GCM319R72A391KA01_	GCM155R72A391KA37_
GCM319R72A391MA01_	GCM155R72A391MA37_
GCM319R71H471KA01_	GCM155R71H471KA37_
GCM319R71H471MA01_	GCM155R71H471MA37_
GCM319R72A471KA01_	GCM155R72A471KA37_
GCM319R72A471MA01_	GCM155R72A471MA37_
GCM319R71H561KA01_	GCM155R71H561KA37_
GCM319R71H561MA01_	GCM155R71H561MA37_
GCM319R72A561KA01_	GCM155R72A561KA37_
GCM319R72A561MA01_	GCM155R72A561MA37_
GCM319R71H681KA01_	GCM155R71H681KA37_
GCM319R71H681MA01_	GCM155R71H681MA37_
GCM319R72A681KA01_	GCM155R72A681KA37_
GCM319R72A681MA01_	GCM155R72A681MA37_
GCM319R71H821KA01_	GCM155R71H821KA37_
GCM319R71H821MA01_	GCM155R71H821MA37_
GCM319R72A821KA01_	GCM155R72A821KA37_
GCM319R72A821MA01_	GCM155R72A821MA37_

GCM319R71H102KA01_	GCM155R71H102KA37_
GCM319R71H102KA02_	GCM155R71H102KA37_
GCM319R71H102MA01_	GCM155R71H102MA37_
GCM319R72A102KA01_	GCM155R72A102KA37_
GCM319R72A102KA02_	GCM155R72A102KA37_
GCM319R72A102MA01_	GCM155R72A102MA37_
GCM319R71H152KA01_	GCM155R71H152KA37_
GCM319R71H152MA01_	GCM155R71H152MA37_
GCM319R72A152KA01_	GCM155R72A152KA37_
GCM319R72A152MA01_	GCM155R72A152MA37_
GCM319R71H182KA01_	GCM155R71H182KA37_
GCM319R71H182MA01_	GCM155R71H182MA37_
GCM319R71H222KA01_	GCM155R71H222KA37_
GCM319R71H222KA02_	GCM155R71H222KA37_
GCM319R71H222MA01_	GCM155R71H222MA37_
GCM319R71H272KA01_	GCM155R71H272KA37_
GCM319R71H272MA01_	GCM155R71H272MA37_
GCM319R71H332KA01_	GCM155R71H332KA37_
GCM319R71H332MA01_	GCM155R71H332MA37_
GCM319R71H392KA01_	GCM155R71H392KA37_
GCM319R71H392MA01_	GCM155R71H392MA37_
GCM319R71H472KA01_	GCM155R71H472KA37_
GCM319R71H472KA02_	GCM155R71H472KA37_
GCM319R71H472MA01_	GCM155R71H472MA37_
GCM319R71H562KA01_	GCM155R71H562KA55_

GCM319R71H562MA01_	GCM155R71H562MA55_
GCM319R71H682KA01_	GCM155R71H682KA55_
GCM319R71H682MA01_	GCM155R71H682MA55_
GCM319R71H822KA01_	GCM155R71H822KA55_
GCM319R71H822MA01_	GCM155R71H822MA55_
GCM319R72A182KA01_	GCM155R72A182KA37_
GCM319R72A182KA02_	GCM155R72A182KA37_
GCM319R72A182KA17_	GCM155R72A182KA37_
GCM319R72A182MA01_	GCM155R72A182MA37_
GCM319R72A222KA01_	GCM155R72A222KA37_
GCM319R72A222MA01_	GCM155R72A222MA37_
GCM319R72A272KA01_	GCM155R72A272KA37_
GCM319R72A272MA01_	GCM155R72A272MA37_
GCM319R72A332KA01_	GCM155R72A332KA37_
GCM319R72A332KA02_	GCM155R72A332KA37_
GCM319R72A332MA01_	GCM155R72A332MA37_
GCM319R72A392KA01_	GCM155R72A392KA37_
GCM319R72A392MA01_	GCM155R72A392MA37_
GCM319R72A472KA01_	GCM155R72A472KA37_
GCM319R72A472KA02_	GCM155R72A472KA37_
GCM319R72A472MA01_	GCM155R72A472MA37_
GRM319R71H103JA01_	GRM155R71H103JA88_
GRM319R71H103KA01_	GRM155R71H103KA88_
GRM319R71H103KA01_	GRM155R71H103KA88_
GRM319R71H103MA01_	GRM155R71H103MA88_

GCM319R71H123KA01_	GCM155R71H123KA55_
GCM319R71H123MA01_	GCM155R71H123MA55_
GCM319R71H183KA01_	GCM155R71H183KA55_
GCM319R71H183MA01_	GCM155R71H183MA55_
GRM319R71E473JA01_	GRM155R71E473JA88_
GRM319R71E473KA01_	GRM155R71E473KA88_
GRM319R71E473MA01_	GRM155R71E473MA88_
GRM319R71H223JA01_	GRM155R71H223JA12_
GRM319R71H223JA26_	GRM155R71H223JA12_
GRM319R71H223KA01_	GRM155R71H223KA12_
GRM319R71H223KA26_	GRM155R71H223KA12_
GRM319R71H223MA01_	GRM155R71H223MA12_
GRM319R71C224KA01_	GRM155R71C224KA12_
GRM319R71C224MA01_	GRM155R71C224MA12_
GRM319R61C105KAA3_	GRM155R61C105KA12_
GRM319R61C105MAA3_	GRM155R61C105MA12_
GCM319R71H122KA01_	GCM155R71H122KA37_
GCM319R71H122MA01_	GCM155R71H122MA37_
GCM319R71H271KA01_	GCM155R71H271KA37_
GCM319R71H271MA01_	GCM155R71H271MA37_
GCM319R72A122KA01_	GCM155R72A122KA37_
GCM319R72A122MA01_	GCM155R72A122MA37_
GCM319R72A271KA01_	GCM155R72A271KA37_
GCM319R72A271MA01_	GCM155R72A271MA37_

GRM319R72A221JA01_	GRM155R72A221KA01_
GRM319R72A471JA01_	GRM155R72A471KA01_
GRM319R72A102JA01_	GRM155R72A102KA01_
GRM319R72A222JA01_	GRM155R72A222KA01_
GRM319R72A472JA01_	GRM155R72A472KA01_
GRM319R71E104JA01_	GRM155R71E104KE14_
GRM319R71H104JA01_	GRM155R71H104KE14_
GRM319R71H104JA01_	GRM155R71H104KE14_
GRM319R71H104JA26_	GRM155R71H104KE14_
GRM319R71C224JA01_	GRM155R71C224KA12_
GCM319R71H103JA01_	GCM155R71H103KA55_
GCM319R72A272JA17_	GCM155R72A272KA37_
GCM319R71H104JA17_	GCM155R71H104KE02_
GCM319R71H104JA37_	GCM155R71H104KE02_
GCM319R71H123JA01_	GCM155R71H123KA55_
GCM319R71H153JA01_	GCM155R71H153KA55_

GCM319R71H183JA01_	GCM155R71H183KA55_
GCM319R71H223JA01_	GCM155R71H223KA55_
GRM319R71H123JA01_	GRM155R71H223JA12_
GRM319R71H123KA01_	GRM155R71H223KA12_
GRM319R71H123MA01_	GRM155R71H223MA12_
GRM319R71H153JA01_	GRM155R71H223JA12_
GRM319R71H153KA01_	GRM155R71H223KA12_
GRM319R71H153MA01_	GRM155R71H223MA12_
GRM319R71H182JA01_	GRM155R71H222JA01_
GRM319R71H182KA01_	GRM155R71H222KA01_
GRM319R71H182MA01_	GRM155R71H222MA01_
GRM319R72A182KA01_	GRM155R72A222KA01_
GRM319R72A182MA01_	GRM155R72A222MA01_
GRM319R72A182JA01_	GRM155R72A222KA01_
GRM319R71H272JA01_	GRM155R71H472JA01_
GRM319R71H272KA01_	GRM155R71H472KA01_

GRM319R71H272MA01_	GRM155R71H472MA01_
GRM319R72A272KA01_	GRM155R72A472KA01_
GRM319R72A272MA01_	GRM155R72A472MA01_
GRM319R72A272JA01_	GRM155R72A472KA01_
GRM319R71H273KA01_	GRM155R71H473KE14_
GRM319R71H273MA01_	GRM155R71H473ME14_
GCM319R71H273JA01_	GCM155R71H473KE02_
GRM319R71H303KA01_	GRM155R71H473KE14_
GRM319R71H303MA01_	GRM155R71H473ME14_
GRM319R71H332JA01_	GRM155R71H472JA01_
GRM319R71H332KA01_	GRM155R71H472KA01_
GRM319R71H332KA01_	GRM155R71H472KA01_
GRM319R71H332MA01_	GRM155R71H472MA01_
GRM319R72A332KA01_	GRM155R72A472KA01_
GRM319R72A332MA01_	GRM155R72A472MA01_

GRM319R72A332JA01_	GRM155R72A472KA01_
GRM319R71H333KA01_	GRM155R71H473KE14_
GRM319R71H333MA01_	GRM155R71H473ME14_
GRM319R71H363KA01_	GRM155R71H473KE14_
GRM319R71H363MA01_	GRM155R71H473ME14_
GRM319R71H392JA01_	GRM155R71H472JA01_
GRM319R71H392KA01_	GRM155R71H472KA01_
GRM319R71H392MA01_	GRM155R71H472MA01_
GRM319R72A392KA01_	GRM155R72A472KA01_
GRM319R72A392MA01_	GRM155R72A472MA01_
GRM319R72A392JA01_	GRM155R72A472KA01_
GRM319R71H393KA01_	GRM155R71H473KE14_
GRM319R71H393MA01_	GRM155R71H473ME14_
GRM319R71H433KA01_	GRM155R71H473KE14_
GRM319R71H433MA01_	GRM155R71H473ME14_
GRM319R71H513KA01_	GRM155R71H104KE14_

GRM319R71H513MA01_	GRM155R71H104ME14_
GRM319R71H513JA01_	GRM155R71H104KE14_
GRM319R71H562JA01_	GRM155R71H103JA88_
GRM319R71H562KA01_	GRM155R71H103KA88_
GRM319R71H562MA01_	GRM155R71H103MA88_
GRM319R71E563KA01_	GRM155R71E104KE14_
GRM319R71E563MA01_	GRM155R71E104ME14_
GRM319R71H563KA01_	GRM155R71H104KE14_
GRM319R71H563MA01_	GRM155R71H104ME14_
GRM319R71E563JA01_	GRM155R71E104KE14_
GRM319R71H563JA01_	GRM155R71H104KE14_
GRM319R71H623KA01_	GRM155R71H104KE14_
GRM319R71H623MA01_	GRM155R71H104ME14_
GRM319R71H623JA01_	GRM155R71H104KE14_
GRM319R71H682JA01_	GRM155R71H103JA88_

GRM319R71H682KA01_	GRM155R71H103KA88_
GRM319R71H682MA01_	GRM155R71H103MA88_
GRM319R71E683KA01_	GRM155R71E104KE14_
GRM319R71E683MA01_	GRM155R71E104ME14_
GRM319R71H683KA01_	GRM155R71H104KE14_
GRM319R71H683KA01_	GRM155R71H104KE14_
GRM319R71H683MA01_	GRM155R71H104ME14_
GRM319R71E683JA01_	GRM155R71E104KE14_
GRM319R71H683JA01_	GRM155R71H104KE14_
GRM319R71H753KA01_	GRM155R71H104KE14_
GRM319R71H753MA01_	GRM155R71H104ME14_
GRM319R71H753JA01_	GRM155R71H104KE14_
GRM319R71H822JA01_	GRM155R71H103JA88_
GRM319R71H822KA01_	GRM155R71H103KA88_
GRM319R71H822MA01_	GRM155R71H103MA88_

GRM319R71E823KA01_	GRM155R71E104KE14_
GRM319R71E823MA01_	GRM155R71E104ME14_
GRM319R71H823KA01_	GRM155R71H104KE14_
GRM319R71H823MA01_	GRM155R71H104ME14_
GRM319R71E823JA01_	GRM155R71E104KE14_
GRM319R71H823JA01_	GRM155R71H104KE14_
GRM319B11H182KA01_	GRM1555C1H182JA01_
GRM319B11H182MA01_	GRM1555C1H182JA01_
GRM319B11A225KA01_	GRM155R61A225KE01_
GRM319B11A225KA01_	GRM155R61A225KE01_
GRM319B31E105KC45_	GRM155R61E105KA12_
GRM319B11C105KAA3_	GRM155R61C105KA12_
GRM319B11C105KC11_	GRM155R61C105KA12_
GRM319B11C105MAA3_	GRM155R61C105MA12_
GRM319B11C105MC11_	GRM155R61C105MA12_

GRM319B11E564KA01_	GRM155R61E105KA12_
GRM319B11E564KA01_	GRM155R61E105KA12_
GRM319B11E564KC01_	GRM155R61E105KA12_
GRM319B11E564MA01_	GRM155R61E105MA12_
GRM319B11C564KA01_	GRM155R61C105KA12_
GRM319B11C564MA01_	GRM155R61C105MA12_
GRM319B11E564JA01_	GRM155R61E105KA12_
GRM319B11E684KA01_	GRM155R61E105KA12_
GRM319B11E684KA01_	GRM155R61E105KA12_
GRM319B11E684KA01_	GRM155R61E105KA12_
GRM319B11E684KA01_	GRM155R61E105KA12_
GRM319B11E684KC01_	GRM155R61E105KA12_

GRM319B11E684MA01_	GRM155R61E105MA12_
GRM319B11E684JA01_	GRM155R61E105KA12_
GRM319B11H513KA01_	GRM155R61H104KE14_
GRM319B11H513MA01_	GRM155R61H104ME14_
GRM319B11H563KA01_	GRM155R61H104KE14_
GRM319B11H563KA01_	GRM155R61H104KE14_
GRM319B11H563MA01_	GRM155R61H104ME14_
GRM319B11H623KA01_	GRM155R61H104KE14_
GRM319B11H623MA01_	GRM155R61H104ME14_
GRM319B11H683KA01_	GRM155R61H104KE14_
GRM319B11H683KA01_	GRM155R61H104KE14_
GRM319B11H683KA01_	GRM155R61H104KE14_

GRM319B11H683KA01_	GRM155R61H104KE14_
GRM319B11H683MA01_	GRM155R61H104ME14_
GRM319B11H753KA01_	GRM155R61H104KE14_
GRM319B11H753MA01_	GRM155R61H104ME14_
GRM319B11H823MA01_	GRM155R61H104ME14_
GRM319B11H823KA01_	GRM155R61H104KE14_
GRM319B11H222JA01_	GRM155R71H222JA01_
GRM319B11H222KA01_	GRM155R71H222KA01_
GRM319B11H222KA59_	GRM155R71H222KA01_
GRM319B11H222MA01_	GRM155R71H222MA01_
GRM319B11H472JA01_	GRM155R71H472JA01_
GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA01_	GRM155R71H104KE14_

GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA01_	GRM155R71H104KE14_
GRM319B11H104KA22_	GRM155R71H104KE14_
GRM319B11H104KA22_	GRM155R71H104KE14_
GRM319B11H104MA01_	GRM155R71H104ME14_
GRM319B11H104MA01_	GRM155R71H104ME14_
GRM319B11H103JA01_	GRM155R71H103JA88_
GRM319B11E473JA01_	GRM155R71E473JA88_
GRM319B11E473KA01_	GRM155R71E473KA88_
GRM319B11E473KA01_	GRM155R71E473KA88_
GRM319B11E473MA01_	GRM155R71E473MA88_
GRM319B11H223JA01_	GRM155R71H223JA12_

GRM319B11E104JA01_	GRM155R71E104KE14_
GRM319B11H104JA01_	GRM155R71H104KE14_
GRM319B11H123JA01_	GRM155R71H223JA12_
GRM319B11H153JA01_	GRM155R71H223JA12_
GRM319B11H182JA01_	GRM155R71H222JA01_
GRM319B11H272JA01_	GRM155R71H472JA01_
GRM319B11H303KA01_	GRM155R71H473KE14_
GRM319B11H303MA01_	GRM155R71H473ME14_
GRM319B11H332JA01_	GRM155R71H472JA01_
GRM319B11H363KA01_	GRM155R71H473KE14_
GRM319B11H363MA01_	GRM155R71H473ME14_
GRM319B11H392JA01_	GRM155R71H472JA01_

GRM319B11H513JA01_	GRM155R71H104KE14_
GRM319B11H562JA01_	GRM155R71H103JA88_
GRM319B11H563JA01_	GRM155R71H104KE14_
GRM319B11H623JA01_	GRM155R71H104KE14_
GRM319B11H682JA01_	GRM155R71H103JA88_
GRM319B11H683JA01_	GRM155R71H104KE14_
GRM319B11H753JA01_	GRM155R71H104KE14_
GRM319B11H822JA01_	GRM155R71H103JA88_
GRM319B11H823JA01_	GRM155R71H104KE14_
GRM319R11C564MA01_	GRM155R61C105MA12_
GRM319R11E564MA01_	GRM155R61E105MA12_

GRM319R11E684MA01_	GRM155R61E105MA12_
GRM319R11H222JA01_	GRM155R71H222JA01_
GRM319R11H222KA01_	GRM155R71H222KA01_
GRM319R11H222KA59_	GRM155R71H222KA01_
GRM319R11H222MA01_	GRM155R71H222MA01_
GRM319R11H472JA01_	GRM155R71H472JA01_
GRM319R11H472KA01_	GRM155R71H472KA01_
GRM319R11H472MA01_	GRM155R71H472MA01_
GCM319R11H153KA01_	GCM155R71H153KA55_
GCM319R11H153MA01_	GCM155R71H153MA55_
GCM319R11H223KA01_	GCM155R71H223KA55_
GCM319R11H223MA01_	GCM155R71H223MA55_
GRM319R11E104KA01_	GRM155R71E104KE14_
GRM319R11E104KA01_	GRM155R71E104KE14_
GRM319R11E104MA01_	GRM155R71E104ME14_
GRM319R11H104KA01_	GRM155R71H104KE14_

GRM319R11H104KA01_	GRM155R71H104KE14_
GRM319R11H104KA01_	GRM155R71H104KE14_
GRM319R11H104KA01_	GRM155R71H104KE14_
GRM319R11H104KA01_	GRM155R71H104KE14_
GRM319R11H104KA01_	GRM155R71H104KE14_
GRM319R11H104KA22_	GRM155R71H104KE14_
GRM319R11H104MA01_	GRM155R71H104ME14_
GCM319R11H221KA01_	GCM155R71H221KA37_
GCM319R11H221MA01_	GCM155R71H221MA37_
GCM319R11H331KA01_	GCM155R71H331KA37_
GCM319R11H331MA01_	GCM155R71H331MA37_
GCM319R11H391KA01_	GCM155R71H391KA37_
GCM319R11H391MA01_	GCM155R71H391MA37_
GCM319R11H471KA01_	GCM155R71H471KA37_
GCM319R11H471MA01_	GCM155R71H471MA37_
GCM319R11H561KA01_	GCM155R71H561KA37_

GCM319R11H561MA01_	GCM155R71H561MA37_
GCM319R11H681KA01_	GCM155R71H681KA37_
GCM319R11H681MA01_	GCM155R71H681MA37_
GCM319R11H821KA01_	GCM155R71H821KA37_
GCM319R11H821MA01_	GCM155R71H821MA37_
GCM319R11H102KA01_	GCM155R71H102KA37_
GCM319R11H102KA01_	GCM155R71H102KA37_
GCM319R11H102MA01_	GCM155R71H102MA37_
GCM319R11H152KA01_	GCM155R71H152KA37_
GCM319R11H152MA01_	GCM155R71H152MA37_
GCM319R11H103KA01_	GCM155R71H103KA40_
GCM319R11H103MA01_	GCM155R71H103MA40_
GCM319R11H182KA01_	GCM155R71H182KA37_
GCM319R11H182MA01_	GCM155R71H182MA37_
GCM319R11H222KA01_	GCM155R71H222KA37_
GCM319R11H222MA01_	GCM155R71H222MA37_

GCM319R11H272KA01_	GCM155R71H272KA37_
GCM319R11H272MA01_	GCM155R71H272MA37_
GCM319R11H332KA01_	GCM155R71H332KA37_
GCM319R11H332MA01_	GCM155R71H332MA37_
GCM319R11H392KA01_	GCM155R71H392KA37_
GCM319R11H392MA01_	GCM155R71H392MA37_
GCM319R11H472KA01_	GCM155R71H472KA37_
GCM319R11H472MA01_	GCM155R71H472MA37_
GCM319R11H562KA01_	GCM155R71H562KA55_
GCM319R11H562MA01_	GCM155R71H562MA55_
GCM319R11H682KA01_	GCM155R71H682KA55_
GCM319R11H682MA01_	GCM155R71H682MA55_
GCM319R11H822KA01_	GCM155R71H822KA55_
GCM319R11H822MA01_	GCM155R71H822MA55_
GCM319R71H103KA01_	GCM155R71H103KA40_
GCM319R71H103KA02_	GCM155R71H103KA55_

GCM319R71H103MA01_	GCM155R71H103MA40_
GRM319R11H103JA01_	GRM155R71H103JA88_
GRM319R11H103KA01_	GRM155R71H103KA88_
GRM319R11H103MA01_	GRM155R71H103MA88_
GCM319R11H104KA01_	GCM155R71H104KE37_
GCM319R11H104KA01_	GCM155R71H104KE37_
GCM319R11H104MA01_	GCM155R71H104ME37_
GCM319R11H104MA01_	GCM155R71H104ME37_
GCM319R11H123KA01_	GCM155R71H123KA55_
GCM319R11H123MA01_	GCM155R71H123MA55_
GCM319R11H183KA01_	GCM155R71H183KA55_
GCM319R11H183MA01_	GCM155R71H183MA55_
GRM319R11E473KA01_	GRM155R71E473KA88_
GRM319R11E473JA01_	GRM155R71E473JA88_
GRM319R11E473MA01_	GRM155R71E473MA88_
GRM319R11H223JA01_	GRM155R71H223JA12_

GRM319R11H223KA01_	GRM155R71H223KA12_
GRM319R11H223MA01_	GRM155R71H223MA12_
GRM319R11C224KA01_	GRM155R71C224KA12_
GRM319R11C224KA01_	GRM155R71C224KA12_
GRM319R11C224KA01_	GRM155R71C224KA12_
GRM319R11C224MA01_	GRM155R71C224MA12_
GCM319R11H122KA01_	GCM155R71H122KA37_
GCM319R11H122MA01_	GCM155R71H122MA37_
GCM319R11H271KA01_	GCM155R71H271KA37_
GCM319R11H271MA01_	GCM155R71H271MA37_
GRM319R11E104JA01_	GRM155R71E104KE14_
GRM319R11H104JA01_	GRM155R71H104KE14_
GCM319R11H103JA01_	GCM155R71H103KA55_
GCM319R11H123JA01_	GCM155R71H123KA55_
GCM319R11H153JA01_	GCM155R71H153KA55_

GCM319R11H183JA01_	GCM155R71H183KA55_
GCM319R11H223JA01_	GCM155R71H223KA55_
GRM319R11H123JA01_	GRM155R71H223JA12_
GRM319R11H123KA01_	GRM155R71H223KA12_
GRM319R11H123MA01_	GRM155R71H223MA12_
GRM319R11H153JA01_	GRM155R71H223JA12_
GRM319R11H153KA01_	GRM155R71H223KA12_
GRM319R11H153MA01_	GRM155R71H223MA12_
GRM319R11H182JA01_	GRM155R71H222JA01_
GRM319R11H182KA01_	GRM155R71H222KA01_
GRM319R11H182MA01_	GRM155R71H222MA01_
GRM319R11H272JA01_	GRM155R71H472JA01_

GRM319R11H272KA01_	GRM155R71H472KA01_
GRM319R11H272MA01_	GRM155R71H472MA01_
GRM319R11H273KA01_	GRM155R71H473KE14_
GRM319R11H273MA01_	GRM155R71H473ME14_
GCM319R11H273JA01_	GCM155R71H473KE02_
GRM319R11H303KA01_	GRM155R71H473KE14_
GRM319R11H303MA01_	GRM155R71H473ME14_
GRM319R11H332JA01_	GRM155R71H472JA01_
GRM319R11H332KA01_	GRM155R71H472KA01_
GRM319R11H332MA01_	GRM155R71H472MA01_
GRM319R11H333KA01_	GRM155R71H473KE14_
GRM319R11H333MA01_	GRM155R71H473ME14_

GRM319R11H363KA01_	GRM155R71H473KE14_
GRM319R11H363MA01_	GRM155R71H473ME14_
GRM319R11H392JA01_	GRM155R71H472JA01_
GRM319R11H392KA01_	GRM155R71H472KA01_
GRM319R11H392MA01_	GRM155R71H472MA01_
GRM319R11H393KA01_	GRM155R71H473KE14_
GRM319R11H393MA01_	GRM155R71H473ME14_
GRM319R11H433KA01_	GRM155R71H473KE14_
GRM319R11H433MA01_	GRM155R71H473ME14_
GRM319R11H513KA01_	GRM155R71H104KE14_
GRM319R11H513MA01_	GRM155R71H104ME14_
GRM319R11H513JA01_	GRM155R71H104KE14_

GRM319R11H562JA01_	GRM155R71H103JA88_
GRM319R11H562KA01_	GRM155R71H103KA88_
GRM319R11H562MA01_	GRM155R71H103MA88_
GRM319R11E563KA01_	GRM155R71E104KE14_
GRM319R11E563MA01_	GRM155R71E104ME14_
GRM319R11H563KA01_	GRM155R71H104KE14_
GRM319R11H563MA01_	GRM155R71H104ME14_
GRM319R11E563JA01_	GRM155R71E104KE14_
GRM319R11H563JA01_	GRM155R71H104KE14_
GRM319R11H623KA01_	GRM155R71H104KE14_
GRM319R11H623MA01_	GRM155R71H104ME14_

GRM319R11H623JA01_	GRM155R71H104KE14_
GRM319R11H682JA01_	GRM155R71H103JA88_
GRM319R11H682KA01_	GRM155R71H103KA88_
GRM319R11H682MA01_	GRM155R71H103MA88_
GRM319R11E683KA01_	GRM155R71E104KE14_
GRM319R11E683MA01_	GRM155R71E104ME14_
GRM319R11H683KA01_	GRM155R71H104KE14_
GRM319R11H683MA01_	GRM155R71H104ME14_
GRM319R11E683JA01_	GRM155R71E104KE14_
GRM319R11H683JA01_	GRM155R71H104KE14_
GRM319R11H753KA01_	GRM155R71H104KE14_

GRM319R11H753MA01_	GRM155R71H104ME14_
GRM319R11H753JA01_	GRM155R71H104KE14_
GRM319R11H822JA01_	GRM155R71H103JA88_
GRM319R11H822KA01_	GRM155R71H103KA88_
GRM319R11H822MA01_	GRM155R71H103MA88_
GRM319R11E823KA01_	GRM155R71E104KE14_
GRM319R11E823MA01_	GRM155R71E104ME14_
GRM319R11H823KA01_	GRM155R71H104KE14_
GRM319R11H823MA01_	GRM155R71H104ME14_
GRM319R11E823JA01_	GRM155R71E104KE14_
GRM319R11H823JA01_	GRM155R71H104KE14_
GRM319R11C105MAA3_	GRM155C71C105ME11_

GRM319R11A105KA01_	GRM155C71A105KE11_
GRM319R11A105KA01_	GRM155C71A105KE11_
GRM319R11C105KAA3_	GRM155C71C105KE11_
GRM319R11C105KC11_	GRM155C71C105KE11_
GRM319R11C564KA01_	GRM155C71C105KE11_
GRM319R11E564KA01_	GRM155D71E105KE11_
GRM319R11E564JA01_	GRM155D71E105KE11_
GRM319R11E684KA01_	GRM155D71E105KE11_
GRM319R11E684KA01_	GRM155D71E105KE11_
GRM319R11E684KC01_	GRM155D71E105KE11_
GRM319R11E684JA01_	GRM155D71E105KE11_
GRM319R72A331JA01_	GRM1555C2A331JE01_
GRM319R72A391JA01_	GRM1555C2A391JE01_

GRM319R72A561JA01_	GRM1555C2A561JE01_
GRM319R72A681JA01_	GRM1555C2A681JE01_
GRM319R72A821JA01_	GRM1555C2A821JE01_
GRM319R72A122JA01_	GRM1555C2A122JE01_
GRM319R72A271JA01_	GRM1555C2A271JE01_
GRM319R72A331KA01_	GRM1555C2A331JE01_
GRM319R72A391KA01_	GRM1555C2A391JE01_
GRM319R72A561KA01_	GRM1555C2A561JE01_
GRM319R72A681KA01_	GRM1555C2A681JE01_
GRM319R72A821KA01_	GRM1555C2A821JE01_
GRM319R72A122KA01_	GRM1555C2A122JE01_
GRM319R72A271KA01_	GRM1555C2A271JE01_
GRM319R72A331MA01_	GRM1555C2A331JE01_

GRM319R72A391MA01_	GRM1555C2A391JE01_
GRM319R72A561MA01_	GRM1555C2A561JE01_
GRM319R72A681MA01_	GRM1555C2A681JE01_
GRM319R72A821MA01_	GRM1555C2A821JE01_
GRM319R72A122MA01_	GRM1555C2A122JE01_
GRM319R72A271MA01_	GRM1555C2A271JE01_
GRM319R71A105MC01_	GRM155C71A105ME11_
GRM319R71C105MAA3_	GRM155C71C105ME11_
GRM319R71C105MC11_	GRM155C71C105ME11_
GRM319R71A105KA01_	GRM155C71A105KE11_
GRM319R71A105KC01_	GRM155C71A105KE11_
GRM319R71C105KAA3_	GRM155C71C105KE11_
GRM319R71C105KC11_	GRM155C71C105KE11_
GRM319R71C564MA01_	GRM155C71C105ME11_

GRM319R71C564KA01_	GRM155C71C105KE11_
GRM319R71C564KA26_	GRM155C71C105KE11_
GRM319R71H224JA01_	GRM155D71H224KE01_
GCM319R71H124JA37_	GCM155D71H224KE02_
GRM319R71E564KA01_	GRM155D71E105KE11_
GRM319R71E564MA01_	GRM155D71E105KE11_
GRM319R71E564JA01_	GRM155D71E105KE11_
GRM319R71E684KA01_	GRM155D71E105KE11_
GRM319R71E684MA01_	GRM155D71E105KE11_
GRM319R71E684JA01_	GRM155D71E105KE11_
GRM31MR71E104KA01_	GRM155R71E104KE14_
GRM31MR71E104MA01_	GRM155R71E104ME14_

GRM31MR71H104KA01_	GRM155R71H104KE14_
GRM31MR71H104MA01_	GRM155R71H104ME14_
GCM31MR71H333KA01_	GCM155R71H333KE02_
GCM31MR71H333KA02_	GCM155R71H333KE02_
GCM31MR71H333MA01_	GCM155R71H333ME02_
GCM31MR71H333MA02_	GCM155R71H333ME02_
GCM31MR71H683KA01_	GCM155R71H683KE02_
GCM31MR71H683KA02_	GCM155R71H683KE02_
GCM31MR71H683MA01_	GCM155R71H683ME02_
GCM31MR71H683MA02_	GCM155R71H683ME02_
GRM31MR71C224KA01_	GRM155R71C224KA12_
GRM31MR71C224MA01_	GRM155R71C224MA12_
GRM31MR71E104JA01_	GRM155R71E104KE14_
GRM31MR71H104JA01_	GRM155R71H104KE14_
GCM31MR71H333JA01_	GCM155R71H333KE02_
GCM31MR71H683JA01_	GCM155R71H683KE02_
GRM31MR61C564KA01_	GRM155R61C105KA12_
GRM31MR61C564MA01_	GRM155R61C105MA12_
GRM31MR61C564JA01_	GRM155R61C105KA12_
GRM31MR61C684KA01_	GRM155R61C105KA12_

GRM31MR61C684MA01_	GRM155R61C105MA12_
GRM31MR61C684JA01_	GRM155R61C105KA12_
GRM31MR61C824KA01_	GRM155R61C105KA12_
GRM31MR61C824MA01_	GRM155R61C105MA12_
GRM31MR61C824JA01_	GRM155R61C105KA12_
GRM31MR71H333KA01_	GRM155R71H473KE14_
GRM31MR71H333KA26_	GRM155R71H473KE14_
GRM31MR71H333MA01_	GRM155R71H473ME14_
GRM31MR71H393KA01_	GRM155R71H473KE14_
GRM31MR71H393MA01_	GRM155R71H473ME14_
GCM31MR71H393JA01_	GCM155R71H473KE02_
GRM31MR71H513JA26_	GRM155R71H104KE14_
GRM31MR71H563KA01_	GRM155R71H104KE14_
GRM31MR71H563MA01_	GRM155R71H104ME14_
GRM31MR71H563JA01_	GRM155R71H104KE14_

GRM31MR71H563JA26_	GRM155R71H104KE14_
GCM31MR71H563JA01_	GCM155R71H104KE02_
GRM31MR71H623JA26_	GRM155R71H104KE14_
GRM31MR71H683KA01_	GRM155R71H104KE14_
GRM31MR71H683KA26_	GRM155R71H104KE14_
GRM31MR71H683MA01_	GRM155R71H104ME14_
GRM31MR71H683JA01_	GRM155R71H104KE14_
GRM31MR71H683JA26_	GRM155R71H104KE14_
GRM31MR71H753JA26_	GRM155R71H104KE14_
GRM31MR71H823KA01_	GRM155R71H104KE14_
GRM31MR71H823MA01_	GRM155R71H104ME14_
GRM31MR71H823JA01_	GRM155R71H104KE14_
GRM31MR71H823JA26_	GRM155R71H104KE14_

GCM31MR71H823JA01_	GCM155R71H104KE02_
GRM31MR71H913KA01_	GRM155R71H104KE14_
GRM31MR71H913MA01_	GRM155R71H104ME14_
GCM31MR71H913KA01_	GCM155R71H104KE02_
GCM31MR71H913MA01_	GCM155R71H104ME02_
GRM31MR71H913JA01_	GRM155R71H104KE14_
GRM31MR71H913JA26_	GRM155R71H104KE14_
GCM31MR71H913JA01_	GCM155R71H104KE02_
GRM31MB11H224KA01_	GRM155R61H224KE01_
GRM31MB11H224KA01_	GRM155R61H224KE01_
GRM31MB11H224KA01_	GRM155R61H224KE01_
GRM31MB11H224MA01_	GRM155R61H224ME01_
GRM31MB11H224JA01_	GRM155R61H224KE01_
GRM31MB11H124JA01_	GRM155R61H224KE01_

GRM31MB11H154JA01_	GRM155R61H224KE01_
GRM31MB11H184KA01_	GRM155R61H224KE01_
GRM31MB11H184MA01_	GRM155R61H224ME01_
GRM31MB11H184JA01_	GRM155R61H224KE01_
GRM31MB11C564KA01_	GRM155R61C105KA12_
GRM31MB11C564MA01_	GRM155R61C105MA12_
GRM31MB11C564JA01_	GRM155R61C105KA12_
GRM31MB11C684KA01_	GRM155R61C105KA12_
GRM31MB11C684KA01_	GRM155R61C105KA12_
GRM31MB11C684KA01_	GRM155R61C105KA12_
GRM31MB11C684MA01_	GRM155R61C105MA12_

GRM31MB11C684JA01_	GRM155R61C105KA12_
GRM31MB11E824KA01_	GRM155R61E105KA12_
GRM31MB11E824MA01_	GRM155R61E105MA12_
GRM31MB11C824KA01_	GRM155R61C105KA12_
GRM31MB11C824KA01_	GRM155R61C105KA12_
GRM31MB11C824MA01_	GRM155R61C105MA12_
GRM31MB11C824JA01_	GRM155R61C105KA12_
GRM31MB11H563KA01_	GRM155R61H104KE14_
GRM31MB11H563MA01_	GRM155R61H104ME14_
GRM31MB11H683KA01_	GRM155R61H104KE14_
GRM31MB11H683MA01_	GRM155R61H104ME14_
GRM31MB11H823KA01_	GRM155R61H104KE14_

GRM31MB11H823MA01_	GRM155R61H104ME14_
GRM31MB11H913KA01_	GRM155R61H104KE14_
GRM31MB11H913MA01_	GRM155R61H104ME14_
GRM31MB11H104KA01_	GRM155R71H104KE14_
GRM31MB11H104KA01_	GRM155R71H104KE14_
GRM31MB11H104MA01_	GRM155R71H104ME14_
GRM31MB11E104JA01_	GRM155R71E104KE14_
GRM31MB11H104JA01_	GRM155R71H104KE14_
GRM31MB11H563JA01_	GRM155R71H104KE14_
GRM31MB11H683JA01_	GRM155R71H104KE14_
GRM31MB11H823JA01_	GRM155R71H104KE14_
GRM31MB11H913JA01_	GRM155R71H104KE14_

GRM31MR11H224KA01_	GRM155R61H224KE01_
GRM31MR11H224KA01_	GRM155R61H224KE01_
GRM31MR11H224MA01_	GRM155R61H224ME01_
GRM31MR11C684MA01_	GRM155R61C105MA12_
GRM31MR11C824MA01_	GRM155R61C105MA12_
GRM31MR11E824MA01_	GRM155R61E105MA12_
GRM31MR11E104KA01_	GRM155R71E104KE14_
GRM31MR11E104MA01_	GRM155R71E104ME14_
GRM31MR11H104KA01_	GRM155R71H104KE14_
GRM31MR11H104MA01_	GRM155R71H104ME14_
GCM31MR11H333KA01_	GCM155R71H333KE02_
GCM31MR11H333MA01_	GCM155R71H333ME02_
GCM31MR11H683KA01_	GCM155R71H683KE02_
GCM31MR11H683MA01_	GCM155R71H683ME02_
GRM31MR11C224KA01_	GRM155R71C224KA12_

GRM31MR11C224MA01_	GRM155R71C224MA12_
GRM31MR11E104JA01_	GRM155R71E104KE14_
GRM31MR11H104JA01_	GRM155R71H104KE14_
GCM31MR11H333JA01_	GCM155R71H333KE02_
GCM31MR11H683JA01_	GCM155R71H683KE02_
GRM31MR11H333KA01_	GRM155R71H473KE14_
GRM31MR11H333MA01_	GRM155R71H473ME14_
GRM31MR11H393KA01_	GRM155R71H473KE14_
GRM31MR11H393MA01_	GRM155R71H473ME14_
GCM31MR11H393JA01_	GCM155R71H473KE02_
GRM31MR11H563KA01_	GRM155R71H104KE14_
GRM31MR11H563MA01_	GRM155R71H104ME14_

GRM31MR11H563JA01_	GRM155R71H104KE14_
GCM31MR11H563JA01_	GCM155R71H104KE02_
GRM31MR11H683KA01_	GRM155R71H104KE14_
GRM31MR11H683MA01_	GRM155R71H104ME14_
GRM31MR11H683JA01_	GRM155R71H104KE14_
GRM31MR11H823KA01_	GRM155R71H104KE14_
GRM31MR11H823MA01_	GRM155R71H104ME14_
GRM31MR11H823JA01_	GRM155R71H104KE14_
GCM31MR11H823JA01_	GCM155R71H104KE02_
GRM31MR11H913KA01_	GRM155R71H104KE14_
GRM31MR11H913MA01_	GRM155R71H104ME14_

GCM31MR11H913KA01_	GCM155R71H104KE02_
GCM31MR11H913MA01_	GCM155R71H104ME02_
GRM31MR11H913JA01_	GRM155R71H104KE14_
GCM31MR11H913JA01_	GCM155R71H104KE02_
GRM31MR11C564MA01_	GRM155C71C105ME11_
GRM31MR11C564KA01_	GRM155C71C105KE11_
GRM31MR11C564JA01_	GRM155C71C105KE11_
GRM31MR11C684KA01_	GRM155C71C105KE11_
GRM31MR11C684KA01_	GRM155C71C105KE11_
GRM31MR11C684JA01_	GRM155C71C105KE11_
GRM31MR11C824KA01_	GRM155C71C105KE11_

GRM31MR11C824JA01_	GRM155C71C105KE11_
GRM31MR11H224JA01_	GRM155D71H224KE01_
GRM31MR11H124JA01_	GRM155D71H224KE01_
GRM31MR11H154JA01_	GRM155D71H224KE01_
GRM31MR11H184JA01_	GRM155D71H224KE01_
GRM31MR11E824KA01_	GRM155D71E105KE11_
GRM31MR71C564MA01_	GRM155C71C105ME11_
GRM31MR71C564KA01_	GRM155C71C105KE11_
GRM31MR71C564KA36_	GRM155C71C105KE11_
GRM31MR71C564JA01_	GRM155C71C105KE11_
GRM31MR71C684MA01_	GRM155C71C105ME11_

GRM31MR71C684KA01_	GRM155C71C105KE11_
GRM31MR71C684KA36_	GRM155C71C105KE11_
GRM31MR71C684JA01_	GRM155C71C105KE11_
GRM31MR71C824MA01_	GRM155C71C105ME11_
GRM31MR71C824KA01_	GRM155C71C105KE11_
GRM31MR71C824KA36_	GRM155C71C105KE11_
GRM31MR71C824JA01_	GRM155C71C105KE11_
GRM31MR71H224JA01_	GRM155D71H224KE01_
GRM31MR71H124JA01_	GRM155D71H224KE01_
GCM31MR71H124JA37_	GCM155D71H224KE02_
GRM31MR71H154JA01_	GRM155D71H224KE01_

GRM31MR71H184JA01_	GRM155D71H224KE01_
GCM31MR71H184JA02_	GCM155D71H224KE02_
GRM31MR71E824KA01_	GRM155D71E105KE11_
GRM31MR71E824MA01_	GRM155D71E105KE11_
GRM31XR61A335MAA7_	GRM155R61A475MEAA_
GRM31XB11A335MAA7_	GRM155R61A475MEAA_
GRM31CB11H224KA01_	GRM155R61H224KE01_
GCM319R72A103KA01_	GCM188R72A103KA37_
GCM319R72A103KA02_	GCM188R72A103KA37_
GCM319R72A103KA17_	GCM188R72A103KA37_
GCM319R72A103MA01_	GCM188R72A103MA37_
GCM319R72A562KA01_	GCM188R72A562KA37_
GCM319R72A562MA01_	GCM188R72A562MA37_
GCM319R72A682KA01_	GCM188R72A682KA37_
GCM319R72A682MA01_	GCM188R72A682MA37_
GCM319R72A822KA01_	GCM188R72A822KA37_
GCM319R72A822MA01_	GCM188R72A822MA37_

GRM319R72A103KA01_	GRM188R72A103KA01_
GRM319R72A103KA26_	GRM188R72A103KA01_
GRM319R72A103MA01_	GRM188R72A103MA01_
GCM319R72A123KA01_	GCM188R72A123KA37_
GCM319R72A123MA01_	GCM188R72A123MA37_
GCM319R72A153KA01_	GCM188R72A153KA37_
GCM319R72A153KA02_	GCM188R72A153KA37_
GCM319R72A153MA01_	GCM188R72A153MA37_
GRM319R72A104KA01_	GRM188R72A104KA35_
GRM319R72A104KA01_	GRM188R72A104KA35_
GRM319R72A104KA01_	GRM188R72A104KA35_
GRM319R72A104KA26_	GRM188R72A104KA35_
GRM319R72A104MA01_	GRM188R72A104MA35_
GRM319R71C474KA01_	GRM188R71C474KA88_
GRM319R71C474KA26_	GRM188R71C474KA88_
GRM319R71C474KC01_	GRM188R71C474KA88_
GRM319R71C474MA01_	GRM188R71C474MA88_
GRM319R71E474KA01_	GRM188R71E474KA12_
GRM319R71E474KAAK_	GRM188R71E474KA12_
GRM319R71E474KC01_	GRM188R71E474KA12_
GRM319R71E474MA01_	GRM188R71E474MA12_
GRM319R72A103JA01_	GRM188R72A103KA01_
GRM319R72A104JA01_	GRM188R72A104KA35_

GRM319R71E474JA01_	GRM188R71E474KA12_
GRM319R71H124KA01_	GRM188R71H224KAC4_
GRM319R71H124MA01_	GRM188R71H224MAC4_
GRM319R71E274KA01_	GRM188R71E474KA12_
GRM319R71E274MA01_	GRM188R71E474MA12_
GRM319R71E274JA01_	GRM188R71E474KA12_
GRM319R71C334KA01_	GRM188R71C474KA88_
GRM319R71C334MA01_	GRM188R71C474MA88_
GRM319R71E334KA01_	GRM188R71E474KA12_
GRM319R71E334KA30_	GRM188R71E474KA12_
GRM319R71E334MA01_	GRM188R71E474MA12_
GRM319R71C334JA01_	GRM188R71C474KA88_
GRM319R71E334JA01_	GRM188R71E474KA12_
GRM319R71E394KA01_	GRM188R71E474KA12_
GRM319R71E394KC01_	GRM188R71E474KA12_

GRM319R71E394MA01_	GRM188R71E474MA12_
GRM319R71E394JA01_	GRM188R71E474KA12_
GRM319R72A123JA01_	GRM188R72A223JAC4_
GRM319R72A123KA01_	GRM188R72A223KAC4_
GRM319R72A123MA01_	GRM188R72A223MAC4_
GRM319R72A153JA01_	GRM188R72A223JAC4_
GRM319R72A153KA01_	GRM188R72A223KAC4_
GRM319R72A153KA26_	GRM188R72A223KAC4_
GRM319R72A153MA01_	GRM188R72A223MAC4_
GRM319R72A562KA01_	GRM188R72A103KA01_
GRM319R72A562MA01_	GRM188R72A103MA01_
GRM319R72A562JA01_	GRM188R72A103KA01_
GRM319R72A682KA01_	GRM188R72A103KA01_
GRM319R72A682MA01_	GRM188R72A103MA01_
GRM319R72A682JA01_	GRM188R72A103KA01_

GRM319R72A822KA01_	GRM188R72A103KA01_
GRM319R72A822MA01_	GRM188R72A103MA01_
GRM319R72A822JA01_	GRM188R72A103KA01_
GRM319B11C474KA01_	GRM188R71C474KA88_
GRM319B11C474KA01_	GRM188R71C474KA88_
GRM319B11C474KC01_	GRM188R71C474KA88_
GRM319B11C474MA01_	GRM188R71C474MA88_
GRM319B11E474KA01_	GRM188R71E474KA12_
GRM319B11E474KA01_	GRM188R71E474KA12_
GRM319B11E474KC01_	GRM188R71E474KA12_
GRM319B11E474MA01_	GRM188R71E474MA12_
GRM319B11E474JA01_	GRM188R71E474KA12_
GRM319B11H124KA01_	GRM188R71H224KAC4_
GRM319B11H124MA01_	GRM188R71H224MAC4_
GRM319B11E274KA01_	GRM188R71E474KA12_

GRM319B11E274KA01_	GRM188R71E474KA12_
GRM319B11E274MA01_	GRM188R71E474MA12_
GRM319B11E274JA01_	GRM188R71E474KA12_
GRM319B11C334KA01_	GRM188R71C474KA88_
GRM319B11C334KA01_	GRM188R71C474KA88_
GRM319B11C334MA01_	GRM188R71C474MA88_
GRM319B11E334KA01_	GRM188R71E474KA12_
GRM319B11E334KA01_	GRM188R71E474KA12_
GRM319B11E334KA01_	GRM188R71E474KA12_
GRM319B11E334MA01_	GRM188R71E474MA12_
GRM319B11C334JA01_	GRM188R71C474KA88_

GRM319B11E334JA01_	GRM188R71E474KA12_
GRM319B11E394KA01_	GRM188R71E474MA12_
GRM319B11E394KA01_	GRM188R71E474MA12_
GRM319B11E394MA01_	GRM188R71E474MA12_
GRM319B11E394JA01_	GRM188R71E474KA12_
GRM319R11C474KA01_	GRM188R71C474KA88_
GRM319R11C474MA01_	GRM188R71C474MA88_
GRM319R11E474KA01_	GRM188R71E474KA12_
GRM319R11E474KA01_	GRM188R71E474KA12_
GRM319R11E474KC01_	GRM188R71E474KA12_
GRM319R11E474MA01_	GRM188R71E474MA12_
GRM319R11E224KA01_	GRM188R71E224KA88_
GRM319R11E474JA01_	GRM188R71E474KA12_

GRM319R11H124KA01_	GRM188R71H224KAC4_
GRM319R11H124MA01_	GRM188R71H224MAC4_
GRM319R11E274KA01_	GRM188R71E474KA12_
GRM319R11E274MA01_	GRM188R71E474MA12_
GRM319R11E274JA01_	GRM188R71E474KA12_
GRM319R11C334KA01_	GRM188R71C474KA88_
GRM319R11C334MA01_	GRM188R71C474MA88_
GRM319R11E334KA01_	GRM188R71E474KA12_
GRM319R11E334KA01_	GRM188R71E474KA12_
GRM319R11E334MA01_	GRM188R71E474MA12_
GRM319R11C334JA01_	GRM188R71C474KA88_

GRM319R11E334JA01_	GRM188R71E474KA12_
GRM319R11E394KA01_	GRM188R71E474KA12_
GRM319R11E394MA01_	GRM188R71E474MA12_
GRM319R11E394JA01_	GRM188R71E474KA12_
G CJ319R11H124KA01_	G CJ188R91H124KA01_
G CJ319R11H124MA01_	G CJ188R91H124MA01_
GRM319R72A152JA01_	GRM1885C2A152JA01_
GRM319R72A152KA01_	GRM1885C2A152JA01_
GRM319R72A152MA01_	GRM1885C2A152JA01_
G CJ319R71H124KA01_	G CJ188R91H124KA01_
G CJ319R71H124MA01_	G CJ188R91H124MA01_
GRM31MR72A223JA01_	GRM188R72A223JAC4_
GRM31MR72A223KA01_	GRM188R72A223KAC4_
GRM31MR72A223KA01_	GRM188R72A223KAC4_
GRM31MR72A223KA26_	GRM188R72A223KAC4_

GRM31MR72A223MA01_	GRM188R72A223MAC4_
GRM31MR71H224KA01_	GRM188R71H224KAC4_
GRM31MR71H224KA01_	GRM188R71H224KAC4_
GRM31MR71H224MA01_	GRM188R71H224MAC4_
GCM31MR71E154KA01_	GCM188R71E154KA37_
GCM31MR71E154MA01_	GCM188R71E154MA37_
GCM31MR71H154KA01_	GCM188R71H154KA64_
GCM31MR71H154KA02_	GCM188R71H154KA64_
GCM31MR71H154KA37_	GCM188R71H154KA64_
GCM31MR71H154MA01_	GCM188R71H154MA64_
GCM31MR71H154MA37_	GCM188R71H154MA64_
GCM31MR72A183KA01_	GCM188R72A183KA37_
GCM31MR72A183MA01_	GCM188R72A183MA37_
GRM31MR71E474KA01_	GRM188R71E474KA12_
GRM31MR71E474KA36_	GRM188R71E474KA12_
GRM31MR71E474MA01_	GRM188R71E474MA12_
GRM31MR71E224JA01_	GRM188R71E224JA88_
GRM31MR71E224KA01_	GRM188R71E224KA88_
GRM31MR71E224KA01_	GRM188R71E224KA88_
GRM31MR71E224KA36_	GRM188R71E224KA88_
GRM31MR71E224MA01_	GRM188R71E224MA88_
GCM31MR71E124KA01_	GCM188R71E124KA37_
GCM31MR71E124MA01_	GCM188R71E124MA37_
GCM31MR71E184KA01_	GCM188R71E184KA55_
GCM31MR71E184MA01_	GCM188R71E184MA55_

GCM31MR71H154JA37_	GCM188R71H154KA64_
GRM31MR71H124KA01_	GRM188R71H224KAC4_
GRM31MR71H124KA36_	GRM188R71H224KAC4_
GRM31MR71H124MA01_	GRM188R71H224MAC4_
GRM31MR71H134KA36_	GRM188R71H224KAC4_
GRM31MR71H154KA01_	GRM188R71H224KAC4_
GRM31MR71H154KA01_	GRM188R71H224KAC4_
GRM31MR71H154KA36_	GRM188R71H224KAC4_
GRM31MR71H154MA01_	GRM188R71H224MAC4_
GRM31MR71H164KA36_	GRM188R71H224KAC4_
GRM31MR71H184KA01_	GRM188R71H224KAC4_
GRM31MR71H184KA36_	GRM188R71H224KAC4_
GRM31MR71H184MA01_	GRM188R71H224MAC4_
GRM31MR71C334KA01_	GRM188R71C474KA88_
GRM31MR71C334KA26_	GRM188R71C474KA88_
GRM31MR71C334MA01_	GRM188R71C474MA88_

GRM31MR71E394KA01_	GRM188R71E474KA12_
GRM31MR71E394MA01_	GRM188R71E474MA12_
GRM31MR72A183JA01_	GRM188R72A223JAC4_
GRM31MR72A183KA01_	GRM188R72A223KAC4_
GRM31MR72A183KA26_	GRM188R72A223KAC4_
GRM31MR72A183MA01_	GRM188R72A223MAC4_
GRM31MR72A563KA01_	GRM188R72A104KA35_
GRM31ML81H474KA01_	GCM31ML81H474KA01_
GRM31ML81H474MA01_	GCM31ML81H474MA01_
GRM31MR72A563MA01_	GRM188R72A104MA35_
GRM31MR72A563JA01_	GRM188R72A104KA35_
GRM31MR72A683KA01_	GRM188R72A104KA35_
GRM31MR72A683MA01_	GRM188R72A104MA35_
GRM31MR72A683JA01_	GRM188R72A104KA35_
GRM31MR72A823KA01_	GRM188R72A104KA35_
GRM31MR72A823KA01_	GRM188R72A104KA35_
GRM31MR72A823MA01_	GRM188R72A104MA35_

GRM31MR72A823JA01_	GRM188R72A104KA35_
GRM31MR72A913KA01_	GRM188R72A104KA35_
GRM31MR72A913MA01_	GRM188R72A104MA35_
GRM31MB11C474KC01_	GRM188R71C474KA88_
GRM31MB11E474KA01_	GRM188R71E474KA12_
GRM31MB11E474KA01_	GRM188R71E474KA12_
GRM31MB11E474KA01_	GRM188R71E474KA12_
GRM31MB11E474KC01_	GRM188R71E474KA12_
GRM31MB11E474MA01_	GRM188R71E474MA12_
GRM31MB11E224JA01_	GRM188R71E224JA88_
GRM31MB11C474JC01_	GRM188R71C474KA88_
GRM31MB11H124KA01_	GRM188R71H224KAC4_
GRM31MB11H124KA01_	GRM188R71H224KAC4_
GRM31MB11H124MA01_	GRM188R71H224MAC4_

GRM31MB11H154KA01_	GRM188R71H224KAC4_
GRM31MB11H154KA01_	GRM188R71H224KAC4_
GRM31MB11H154MA01_	GRM188R71H224MAC4_
GRM31MB11C334KA01_	GRM188R71C474KA88_
GRM31MB11C334KA01_	GRM188R71C474KA88_
GRM31MB11C334MA01_	GRM188R71C474MA88_
GRM31MB11E394KA01_	GRM188R71E474MA12_
GRM31MB11E394MA01_	GRM188R71E474MA12_
GCM31MR11E154KA01_	GCM188R71E154KA37_
GCM31MR11E154KA26_	GCM188R71E154KA37_
GCM31MR11E154MA01_	GCM188R71E154MA37_
GCM31MR11H154KA01_	GCM188R71H154KA64_
GCM31MR11H154MA01_	GCM188R71H154MA64_
GRM31MR11E474KA01_	GRM188R71E474KA12_

GRM31MR11E474KC01_	GRM188R71E474KA12_
GRM31MR11E474MA01_	GRM188R71E474MA12_
GRM31MR11E224JA01_	GRM188R71E224JA88_
GRM31MR11E224KA01_	GRM188R71E224KA88_
GRM31MR11E224KA01_	GRM188R71E224KA88_
GRM31MR11E224MA01_	GRM188R71E224MA88_
GCM31MR11E124KA01_	GCM188R71E124KA37_
GCM31MR11E124MA01_	GCM188R71E124MA37_
GCM31MR11E184KA01_	GCM188R71E184KA55_
GCM31MR11E184MA01_	GCM188R71E184MA55_
GRM31MR11H124KA01_	GRM188R71H224KAC4_
GRM31MR11H124MA01_	GRM188R71H224MAC4_
GRM31MR11H154KA01_	GRM188R71H224KAC4_
GRM31MR11H154KA01_	GRM188R71H224KAC4_
GRM31MR11H154MA01_	GRM188R71H224MAC4_

GRM31MR11H184KA01_	GRM188R71H224KAC4_
GRM31MR11H184MA01_	GRM188R71H224MAC4_
GRM31MR11C334KA01_	GRM188R71C474KA88_
GRM31MR11C334KA01_	GRM188R71C474KA88_
GRM31MR11C334MA01_	GRM188R71C474MA88_
GRM31MR11E394KA01_	GRM188R71E474KA12_
GRM31MR11E394MA01_	GRM188R71E474MA12_
GCM31MR71H564JA55_	GCM188D71H105KE36_
GRM31MR71H684KA88_	GRM188D71H105KE01_
GRM31MR71H684KA88_	GRM188D71H105KE01_
GCM31MR71H824JA55_	GCM188D71H105KE36_
GRM31MR72A684MA35_	GRM188D72A105ME01_

GRM31MR72A684KA35_	GRM188D72A105KE01_
GRM31MR72A684KA35_	GRM188D72A105KE01_
GRM31MR72A684KA81_	GRM188D72A105KE01_
GCJ31MR71E124KA01_	GCJ188R71E124KA01_
GCJ31MR71E124MA01_	GCJ188R71E124MA01_
GCJ31MR71E154KA01_	GCJ188R71E154KA01_
GCJ31MR71E154MA01_	GCJ188R71E154MA01_
GCJ31MR71E184KA01_	GCJ188R71E184KA12_
GCJ31MR71E184MA01_	GCJ188R71E184MA12_
GCJ31MR11E124KA01_	GCJ188R71E124KA01_
GCJ31MR11E124MA01_	GCJ188R71E124MA01_
GCJ31MR11E154KA01_	GCJ188R71E154KA01_
GCJ31MR11E154MA01_	GCJ188R71E154MA01_
GCJ31MR11E184KA01_	GCJ188R71E184KA12_
GCJ31MR11E184MA01_	GCJ188R71E184MA12_
GCJ31MR11H124KA01_	GCJ188R91H124KA01_
GCJ31MR11H124MA01_	GCJ188R91H124MA01_

GCJ31MR71H124KA01_	GCJ188R91H124KA01_
GCJ31MR71H124MA01_	GCJ188R91H124MA01_
GRM31CR71H224KA01_	GRM188R71H224KAC4_
GRM3165C1H392JA01_	GRM2165C1H392JA01_
GRM3165C1H472JA01_	GRM2165C1H472JA01_
GRM3165C2A392JA01_	GRM2165C2A392JA01_
GRM3165C2A472JA01_	GRM2165C2A472JA01_
GRM3165C1H332JA01_	GRM2165C1H332JA01_
GRM3165C2A332JA01_	GRM2165C2A332JA01_
GRJ188R60J106KE11_	GCJ188D70J106ME02_
GRJ188R60J106ME11_	GCJ188D70J106ME02_
GCM319R71H273KA01_	GCM219R72A273KA37_
GCM319R71H273KA02_	GCM219R72A273KA37_
GCM319R71H273MA01_	GCM219R72A273MA37_
GCM319R71H273MA02_	GCM219R72A273MA37_
GRM316B31E225KA75_	GRM21BR71E225KE11_
GRM316B31E225MA75_	GRM21BR71E225ME11_
GRM316B31A475KE18_	GRM21BR71A475KE51_
GRM316B31A475ME18_	GRM21BR71A475ME51_
GRM316B31A335KE18_	GRM21BR71A475KE51_
GRM316B31A335KE18_	GRM21BR71A475KE51_
GRM316B31C225KA87_	GRM155R61C225KE11_

GRM316B31C225KA87_	GRM155R61C225KE11_
GRM316B31C225MA87_	GRM155R61C225ME11_
GRM316B31C225MA87_	GRM155R61C225ME11_
GRM316B31C225MA87_	GRM155R61C225ME11_
GRT316R61C225KE01_	GRT21BR71C225KE01_
GRT316R61E225KE01_	GRT21BR71E225KE13_
GRT316R61A475KE01_	GRT21BR71A475KE13_
GRM316R61E225KA12_	GRM21BR71E225KE11_
GRM316R61E225MA12_	GRM21BR71E225ME11_
GRM316R61A475KE19_	GRM21BR71A475KE51_
GRM316R61A475ME19_	GRM21BR71A475ME51_
GRT316R61C225ME01_	GRT21BR71C225KE01_
GRT316R61E225ME01_	GRT21BR71E225KE13_
GRT316R61A475ME01_	GRT21BR71A475KE13_
GRM316R61A335KE19_	GRM21BR71A475KE51_
GRT316R61A225KE01_	GRT21BR71C225KE01_

GRT316R61A225ME01_	GRT21BR71C225KE01_
GRM316R61C225KA88_	GRM155R61C225KE11_
GRM316R61C225MA88_	GRM155R61C225ME11_
GRT316C81C225KE01_	GRT21BR71C225KE01_
GRT316C81C225ME01_	GRT21BR71C225KE01_
GRM316C81C225KA12_	GRM155C81C225KE11_
GRM316C81C225MA12_	GRM155C81C225ME11_
GRM316D71C225KA12_	GRM188C71C225KE11_
GRM316D71C225MA12_	GRM188C71C225ME11_
GRM319B11H273JA01_	GRM2165C1H273JA01_
GRM319B11H333JA01_	GRM2165C1H333JA01_
GRM319B11H303JA01_	GRM2165C1H333JA01_
GRM319R11H273JA01_	GRM2165C1H273JA01_
GRM319R11H333JA01_	GRM2165C1H333JA01_
GRM319R11H303JA01_	GRM2165C1H333JA01_
GRM319R11H433JA01_	GRM21B7U1H433JA01_
GRM319R11H473JA01_	GRM21B7U1H473JA01_

GRM319R11H473KA01_	GRM21B7U1H473JA01_
GRM319R11H473MA01_	GRM21B7U1H473JA01_
GRM319R11H363JA01_	GRM21B7U1H393JA01_
GRM319R11H393JA01_	GRM21B7U1H393JA01_
GRM319R71H273JA01_	GRM2165C1H273JA01_
GRM319R71H273JA26_	GRM2165C1H273JA01_
GRM319R71H333JA01_	GRM2165C1H333JA01_
GRM319R71H243JA26_	GRM2165C1H273JA01_
GRM319R71H303JA01_	GRM2165C1H333JA01_
GRM319R71H393JA01_	GRM21B7U1H393JA01_
GRM319R71H433JA01_	GRM21B7U1H433JA01_
GRM319R71H473JA01_	GRM21B7U1H473JA01_
GRM319R71H473KA01_	GRM21B7U1H473JA01_
GRM319R71H473KA01_	GRM21B7U1H473JA01_

GRM319R71H473MA01_	GRM21B7U1H473JA01_
GRM319R71H363JA01_	GRM21B7U1H393JA01_
GRM319B11H272KA01_	GRM2165C1H272JA01_
GRM319B11H332KA01_	GRM2165C1H332JA01_
GRM319B11H392KA01_	GRM2165C1H392JA01_
GRM319B11H472KA01_	GRM2165C1H472JA01_
GRM319B11H472KA59_	GRM2165C1H472JA01_
GRM319B11H273KA01_	GRM2165C1H273JA01_
GRM319B11H273KA01_	GRM2165C1H273JA01_
GRM319B11H333KA01_	GRM2165C1H333JA01_
GRM319B11H333KA01_	GRM2165C1H333JA01_
GRM319B11H333KA01_	GRM2165C1H333JA01_

GRM319B11H333KA01_	GRM2165C1H333JA01_
GRM319B11H333KA01_	GRM2165C1H333JA01_
GRM319B11H333KA22_	GRM2165C1H333JA01_
GRM319B11H272MA01_	GRM2165C1H272JA01_
GRM319B11H332MA01_	GRM2165C1H332JA01_
GRM319B11H392MA01_	GRM2165C1H392JA01_
GRM319B11H472MA01_	GRM2165C1H472JA01_
GRM319B11H273MA01_	GRM2165C1H273JA01_
GRM319B11H333MA01_	GRM2165C1H333JA01_
GRM319B11E224KA01_	GRM188R71E224KA88_
GCM319R71H124KA01_	GCM21BR71H224KA01_
GRM319R71H274KA01_	GRM21BR71H474KA88_
GRM319R71H274KA26_	GRM21BR71H474KA88_

GRM319R71H274MA01_	GRM21BR71H474MA88_
GRM319R71H274JA01_	GRM21BR71H474KA88_
GRM319R71H334KA01_	GRM21BR71H474KA88_
GRM319R71H334KA01_	GRM21BR71H474KA88_
GRM319R71H334KA26_	GRM21BR71H474KA88_
GRM319R71H334MA01_	GRM21BR71H474MA88_
GRM319R71H334JA01_	GRM21BR71H474KA88_
GRM319B11H223KA01_	GRM21B5C1H223JA01_
GRM319B11H223KA01_	GRM21B5C1H223JA01_
GRM319B11H223KA01_	GRM21B5C1H223JA01_
GRM319B11H223KA01_	GRM21B5C1H223JA01_
GRM319B11H223KA01_	GRM21B5C1H223JA01_
GRM319B11H223KA22_	GRM21B5C1H223JA01_

GRM319B11H223MA01_	GRM21B5C1H223JA01_
GRM319B11H393JA01_	GRM21B7U1H393JA01_
GRM319B11H433JA01_	GRM21B7U1H433JA01_
GRM319B11H473JA01_	GRM21B7U1H473JA01_
GRM319B11H473KA01_	GRM21B7U1H473JA01_
GRM319B11H473KA01_	GRM21B7U1H473JA01_
GRM319B11H473KA01_	GRM21B7U1H473JA01_
GRM319B11H473KA01_	GRM21B7U1H473JA01_
GRM319B11H473KA22_	GRM21B7U1H473JA01_
GRM319B11H393KA01_	GRM21B7U1H393JA01_
GRM319B11H393KA01_	GRM21B7U1H393JA01_
GRM319B11H433KA01_	GRM21B7U1H433JA01_
GRM319B11H473MA01_	GRM21B7U1H473JA01_

GRM319B11H393MA01_	GRM21B7U1H393JA01_
GRM319B11H433MA01_	GRM21B7U1H433JA01_
GRM319B11H363JA01_	GRM21B7U1H393JA01_
GCM319R72A104KA01_	GCM21BR72A104KA37_
GCM319R72A104KA02_	GCM21BR72A104KA37_
GCM319R72A104KA14_	GCM21BR72A104KA37_
GCM319R72A104KA37_	GCM21BR72A104KA37_
GCM319R72A104MA01_	GCM21BR72A104MA37_
GCM319R72A104MA37_	GCM21BR72A104MA37_
GCM319R11H124KA01_	GCM21BR11H224KA01_
GCM319R11H124MA01_	GCM21BR11H224MA01_
GCM319R71H124KA37_	GCM21BR71H224KA37_
GCM319R71H124MA01_	GCM21BR71H224MA01_
GCM319R71H124MA37_	GCM21BR71H224MA37_
GCM319B11H104KA01_	GCM21BR72A104KA37_
GCJ319R72A104KA01_	GCJ21BR72A104KA01_
GCJ319R72A104KA14_	GCJ21BR72A104KA01_
GCJ319R72A104MA01_	GCJ21BR72A104MA01_

G CJ319R71H104KA01_	G CJ21BR72A104KA01_
G CJ319R71H104MA01_	G CJ21BR72A104MA01_
G CJ319R11H104KA01_	G CJ21BR72A104KA01_
G CJ319R11H104MA01_	G CJ21BR72A104MA01_
GRM31MB11H333JA01_	GRM2165C1H333JA01_
GRM31MR11H333JA01_	GRM2165C1H333JA01_
GRM31MR71H333JA01_	GRM2165C1H333JA01_
GRM31MR71H333JA26_	GRM2165C1H333JA01_
GRM31MB11E224KA01_	GRM188R71E224KA88_
GRM31MB11E224KA01_	GRM188R71E224KA88_
GRM31MB11E224KA01_	GRM188R71E224KA88_
GRM31MB11E224MA01_	GRM188R71E224MA88_
G CM31MR72A273KA01_	G CM219R72A273KA37_
G CM31MR72A273MA01_	G CM219R72A273MA37_
G CM31MR72A333KA01_	G CM219R72A333KA37_
G CM31MR72A333KA02_	G CM219R72A333KA37_
G CM31MR72A333KA26_	G CM219R72A333KA37_
G CM31MR72A333MA01_	G CM219R72A333MA37_

GCM31MR72A393KA01_	GCM219R72A393KA37_
GCM31MR72A393KA02_	GCM219R72A393KA37_
GCM31MR72A393MA01_	GCM219R72A393MA37_
GCM31MR71H334KA01_	GCM219R71H334KA55_
GCM31MR71H334KA37_	GCM219R71H334KA55_
GCM31MR71H334MA01_	GCM219R71H334MA55_
GCM31MR71H334MA37_	GCM219R71H334MA55_
GCM31MR71H334JA37_	GCM219R71H334KA55_
GCM31MR71H274KA01_	GCM219R71H334KA40_
GCM31MR71H274KA37_	GCM219R71H334KA55_
GCM31MR71H274MA01_	GCM219R71H334MA40_
GCM31MR71H274MA37_	GCM219R71H334MA55_
GCM31MR71H393KA01_	GCM219R72A393KA37_
GCM31MR71H393KA02_	GCM219R72A393KA37_
GCM31MR71H393MA01_	GCM219R72A393MA37_
GCM31MR71H393MA02_	GCM219R72A393MA37_
GCM31MR11H334KA01_	GCM219R71H334KA55_
GCM31MR11H334MA01_	GCM219R71H334MA55_

GCM31MR11H274KA01_	GCM219R71H334KA40_
GCM31MR11H274MA01_	GCM219R71H334MA40_
GCM31MR11H393KA01_	GCM219R72A393KA37_
GCM31MR11H393MA01_	GCM219R72A393MA37_
GRM31MR72A224KA01_	GRM21AR72A224KAC5_
GRM31MR72A224KA01_	GRM21AR72A224KAC5_
GRM31MR72A224KA01_	GRM21AR72A224KAC5_
GRM31MR72A224MA01_	GRM21AR72A224MAC5_
GRM31MR72A224JA01_	GRM21AR72A224KAC5_
GRM31MR72A124KA01_	GRM21AR72A224KAC5_
GRM31MR72A124MA01_	GRM21AR72A224MAC5_
GRM31MR72A154KA01_	GRM21AR72A224KAC5_
GRM31MR72A154KA01_	GRM21AR72A224KAC5_
GRM31MR72A154MA01_	GRM21AR72A224MAC5_
GRM31MR72A154JA01_	GRM21AR72A224KAC5_
GXM31MR71H474KA02_	GXM21BR71H474KA88_
GRM31MR72A473JA01_	GRM21BR72A473JA01_

GRM31MR72A473KA01_	GRM21BR72A473KA01_
GRM31MR72A473KA01_	GRM21BR72A473KA01_
GRM31MR72A473MA01_	GRM21BR72A473MA01_
GRM31MR71H474KA01_	GRM21BR71H474KA88_
GRM31MR71H474KA01_	GRM21BR71H474KA88_
GRM31MR71H474KA01_	GRM21BR71H474KA88_
GRM31MR71H474KA22_	GRM21BR71H474KA88_
GRM31MR71H474KA36_	GRM21BR71H474KA88_
GRM31MR71H474MA01_	GRM21BR71H474MA88_
GRM31MR71H474JA01_	GRM21BR71H474KA88_
GCM31MR71H124KA01_	GCM21BR71H224KA01_
GCM31MR11H184KA01_	GCM21BR11H224KA01_
GRM31MR71H394KA01_	GRM21BR71H474KA88_
GRM31MR71H394KA36_	GRM21BR71H474KA88_
GRM31MR71H394MA01_	GRM21BR71H474MA88_
GCM31MR71H684KA55_	GCM21BR71H105KA03_
GCM31MR71H684KA55_	GCM21BR71H105KA03_
GCM31MR71H684MA55_	GCM21BR71H105MA03_
GCM31MR71H684JA55_	GCM21BR71H105KA03_

GRM31MR72A273JA01_	GRM21BR72A473JA01_
GRM31MR72A273KA01_	GRM21BR72A473KA01_
GRM31MR72A273MA01_	GRM21BR72A473MA01_
GRM31MR72A333JA01_	GRM21BR72A473JA01_
GRM31MR72A333KA01_	GRM21BR72A473KA01_
GRM31MR72A333KA01_	GRM21BR72A473KA01_
GRM31MR72A333KA26_	GRM21BR72A473KA01_
GRM31MR72A333MA01_	GRM21BR72A473MA01_
GRM31MR72A393JA01_	GRM21BR72A473JA01_
GRM31MR72A393KA01_	GRM21BR72A473KA01_
GRM31MR72A393KA01_	GRM21BR72A473KA01_
GRM31MR72A393MA01_	GRM21BR72A473MA01_
GRM31MB11H393JA01_	GRM21B7U1H393JA01_
GRM31MB11H473JA01_	GRM21B7U1H473JA01_
GRM31MB11H473KA01_	GRM21B7U1H473JA01_
GRM31MB11H393KA01_	GRM21B7U1H393JA01_

GRM31MB11H393MA01_	GRM21B7U1H393JA01_
GRM31MB11H473MA01_	GRM21B7U1H473JA01_
GRM31MR11H393JA01_	GRM21B7U1H393JA01_
GRM31MR11H473JA01_	GRM21B7U1H473JA01_
GRM31MR11H473KA01_	GRM21B7U1H473JA01_
GRM31MR11H473MA01_	GRM21B7U1H473JA01_
GRM31MR71H393JA01_	GRM21B7U1H393JA01_
GRM31MR71H393JA26_	GRM21B7U1H393JA01_
GRM31MR71H433JA26_	GRM21B7U1H433JA01_
GRM31MR71H473JA01_	GRM21B7U1H473JA01_
GRM31MR71H473JA26_	GRM21B7U1H473JA01_
GRM31MR71H473KA01_	GRM21B7U1H473JA01_
GRM31MR71H473KA26_	GRM21B7U1H473JA01_
GRM31MR71H473MA01_	GRM21B7U1H473JA01_

GRM31MR71H363JA26_	GRM21B7U1H393JA01_
GCM31MR72A563KA01_	GCM21BR72A563KA37_
GCM31MR72A563MA01_	GCM21BR72A563MA37_
GCM31MR72A683KA01_	GCM21BR72A683KA37_
GCM31MR72A683MA01_	GCM21BR72A683MA37_
GCM31MR72A823KA01_	GCM21BR72A823KA37_
GCM31MR72A823MA01_	GCM21BR72A823MA37_
GCM31ML81H124KA01_	GCM21BL81H124KA37_
GCM31ML81H124KA37_	GCM21BL81H124KA37_
GCM31ML81H124MA01_	GCM21BL81H124MA37_
GCM31ML81H124MA37_	GCM21BL81H124MA37_
GCM31ML81H154KA01_	GCM21BL81H154KA37_
GCM31ML81H154KA37_	GCM21BL81H154KA37_
GCM31ML81H154MA01_	GCM21BL81H154MA37_
GCM31ML81H154MA37_	GCM21BL81H154MA37_
GCM31ML81H184KA01_	GCM21BL81H184KA37_
GCM31ML81H184KA37_	GCM21BL81H184KA37_
GCM31ML81H184MA01_	GCM21BL81H184MA37_
GCM31ML81H184MA37_	GCM21BL81H184MA37_
GCM31ML81H334KA01_	GCM21BL81H334KA56_
GCM31ML81H334KA37_	GCM21BL81H334KA56_
GCM31ML81H334MA01_	GCM21BL81H334MA56_
GCM31ML81H334MA37_	GCM21BL81H334MA56_

GCM31MR11H124KA01_	GCM21BR11H224KA01_
GCM31MR11H124MA01_	GCM21BR11H224MA01_
GCM31MR71H124KA37_	GCM21BR71H224KA37_
GCM31MR71H124MA01_	GCM21BR71H224MA01_
GCM31MR71H124MA37_	GCM21BR71H224MA37_
GCM31MR11H184MA01_	GCM21BR11H224MA01_
GCM31ML81H274KA01_	GCM21BL81H334KA42_
GCM31ML81H274KA37_	GCM21BL81H334KA56_
GCM31ML81H274MA01_	GCM21BL81H334MA42_
GCM31ML81H274MA37_	GCM21BL81H334MA56_
GCM31MR71H274JA37_	GCM21BR71H474KA55_
GCM31MR71H394KA01_	GCM21BR71H474KA40_
GCM31MR71H394KA37_	GCM21BR71H474KA55_
GCM31MR71H394MA01_	GCM21BR71H474MA40_
GCM31MR71H394MA37_	GCM21BR71H474MA55_
GCM31MR71H394JA37_	GCM21BR71H474KA55_

GCM31MR71H564KA55_	GCM21BR71H105KA03_
GCM31MR71H564MA55_	GCM21BR71H105MA03_
GCM31MR71H824KA55_	GCM21BR71H105KA03_
GCM31MR71H824MA55_	GCM21BR71H105MA03_
GCM31MR72A913KA01_	GCM21BR72A104KA37_
GCM31MR72A913MA01_	GCM21BR72A104MA37_
GCM31MR71H563KA01_	GCM21BR72A563KA37_
GCM31MR71H563KA02_	GCM21BR72A563KA37_
GCM31MR71H563MA01_	GCM21BR72A563MA37_
GCM31MR71H563MA02_	GCM21BR72A563MA37_
GCM31MR71H823KA01_	GCM21BR72A823KA37_
GCM31MR71H823KA02_	GCM21BR72A823KA37_
GCM31MR71H823MA01_	GCM21BR72A823MA37_
GCM31MR71H823MA02_	GCM21BR72A823MA37_
GRM31MB10J475KC11_	GRM155R61A475ME01_

GRM31MB10J475MC11_	GRM155R61A475ME01_
GCM31MR11H394KA01_	GCM21BR71H474KA40_
GCM31MR11H394MA01_	GCM21BR71H474MA40_
GCM31MR11H563KA01_	GCM21BR72A563KA37_
GCM31MR11H563MA01_	GCM21BR72A563MA37_
GCM31MR11H823KA01_	GCM21BR72A823KA37_
GCM31MR11H823MA01_	GCM21BR72A823MA37_
GRM31MR61A475KC31_	GRM21BR71A475KE51_
GRM31MR60J475KC11_	GRM155R61A475ME01_
GCM31MR72A154KA01_	GCM21BC72A105KE36_
GCM31MR72A154KA37_	GCM21BC72A105KE36_
GCM31MR72A154KA37_	GCM21BC72A105KE36_
GCM31MR72A154MA01_	GCM21BC72A105ME36_
GCM31MR72A154MA37_	GCM21BC72A105ME36_

GCM31MR72A154JA37_	GCM21BC72A105KE36_
GRM31MR72A474KA35_	GRM21BR72A474KA73_
GRM31MR72A474KA35_	GRM21BR72A474KA73_
GRM31MR72A474KA35_	GRM21BR72A474KA73_
GRM31MR72A474KA35_	GRM21BR72A474KA73_
GRM31MR72A474MA35_	GRM21BR72A474MA73_
GRM31XB11A335KAA7_	GRM21BR71A475KE51_
GRM31XB11A335KAA7_	GRM21BR71A475KE51_
GRM31XB11A335KC12_	GRM21BR71A475KE51_
GRM31XB11A335KC12_	GRM21BR71A475KE51_
GRM31XR61A335KAA7_	GRM21BR71A475KE51_
GRM31XR61A335KC12_	GRM21BR71A475KE51_
GCJ31MR71H334KA01_	GCJ219R71H334KA12_
GCJ31MR71H334KA14_	GCJ219R71H334KA12_
GCJ31MR71H334MA01_	GCJ219R71H334MA12_
GCJ31MR71H274KA01_	GCJ219R71H334KA12_
GCJ31MR71H274KA14_	GCJ219R71H334KA12_

GCJ31MR71H274MA01_	GCJ219R71H334MA12_
GCJ31MR11H334KA01_	GCJ219R71H334KA12_
GCJ31MR11H334MA01_	GCJ219R71H334MA12_
GCJ31MR11H274KA01_	GCJ219R71H334KA12_
GCJ31MR11H274MA01_	GCJ219R71H334MA12_
GCJ31MR71H184KA01_	GCJ21BR71H224KA01_
GCJ31MR11H184KA01_	GCJ21BR71H224KA01_
GCJ31MR71H154KA01_	GCJ21BR71H224KA01_
GCJ31MR71H154MA01_	GCJ21BR71H224MA01_
GCJ31MR71H184MA01_	GCJ21BR71H224MA01_
GCJ31MR71H394KA01_	GCJ21BR71H474KA12_
GCJ31MR71H394KA14_	GCJ21BR71H474KA12_
GCJ31MR71H394MA01_	GCJ21BR71H474MA12_
GCJ31MR11H154KA01_	GCJ21BR71H224KA01_
GCJ31MR11H154MA01_	GCJ21BR71H224MA01_

GCJ31MR11H184MA01_	GCJ21BR71H224MA01_
GCJ31MR11H394KA01_	GCJ21BR71H474KA12_
GCJ31MR11H394MA01_	GCJ21BR71H474MA12_
GRM154R61A565ME01_	GRM155R61A106ME18_
GRJ31AR61C176ME05_	GCJ31CC71C226ME02_
GRJ31MR71H474KE01_	GRJ21BC72A105KE11_
GRJ31CR61E106KE11_	GRJ21BR61E106KE01_
GRT316R61A335KE01_	GRT188R61C475KE13_
GRT316R61A335ME01_	GRT188R61C475KE13_
GRM31MB11H333KA01_	GRM2165C1H333JA01_
GRM31MB11H333MA01_	GRM2165C1H333JA01_
GRM319B11H103KA01_	GRM2195C1H103JA01_
GRM319B11H103KA01_	GRM2195C1H103JA01_

GRM319B11H103KA01_	GRM2195C1H103JA01_
GRM319B11H103KA59_	GRM2195C1H103JA01_
GRM319B11H562KA01_	GRM2195C1H562JA01_
GRM319B11H682KA01_	GRM2195C1H682JA01_
GRM319B11H822KA01_	GRM2195C1H822JA01_
GRM319B11H123KA01_	GRM2195C1H123JA01_
GRM319B11H153KA01_	GRM2195C1H153JA01_
GRM319B11H103MA01_	GRM2195C1H103JA01_
GRM319B11H562MA01_	GRM2195C1H562JA01_
GRM319B11H682MA01_	GRM2195C1H682JA01_
GRM319B11H822MA01_	GRM2195C1H822JA01_
GRM319B11H123MA01_	GRM2195C1H123JA01_
GRM319B11H153MA01_	GRM2195C1H153JA01_
GRM319B0YA105KC36_	GRM219R7YA105KA12_
GRM319B0YA105KC36_	GRM219R7YA105KA12_
GRM3162C1H392JA01_	GRM2165C1H392JA01_
GRM3162C1H472JA01_	GRM2165C1H472JA01_
GRM3162C2A392JA01_	GRM2165C2A392JA01_

GRM3162C2A472JA01_	GRM2165C2A472JA01_
GRM3162C1H332JA01_	GRM2165C1H332JA01_
GRM3162C2A332JA01_	GRM2165C2A332JA01_
GCM319R11H273KA01_	GCM219R72A273KA37_
GCM319R11H273MA01_	GCM219R72A273MA37_
GRM3161X1H392JA01_	GRM2165C1H392JA01_
GRM3161X1H472JA01_	GRM2165C1H472JA01_
GRM3161X2A392JA01_	GRM2165C2A392JA01_
GRM3161X2A472JA01_	GRM2165C2A472JA01_
GRM3161X1H332JA01_	GRM2165C1H332JA01_
GRM3161X2A332JA01_	GRM2165C2A332JA01_
GRM32RB11E225KA01_	GRM155R61E225KE11_
GRM32RB11E225KC01_	GRM155R61E225KE11_
GRM32RB11E225MA01_	GRM155R61E225ME11_
GRM32RB11E225MA01_	GRM155R61E225ME11_
GRM32D7U1A474JA01_	GRM155R71A474KE01_
GRM32ER61A106MA01_	GRM155R61A106ME18_
GRM32ER61A106MC01_	GRM155R61A106ME18_
GRM32EB11A106MA01_	GRM155R61A106ME18_
GRM32EB11A106MC01_	GRM155R61A106ME18_

GRM32RR61C475KA01_	GRM185R61C475KE11_
GRM32RR61C475KC01_	GRM185R61C475KE11_
GRM32RR61C475KC27_	GRM185R61C475KE11_
GRM32RB11C475KA01_	GRM185R61C475KE11_
GRM32RB11C475KA01_	GRM185R61C475KE11_
GRM32RB11C475KC01_	GRM185R61C475KE11_
GRM32RB11C475KC01_	GRM185R61C475KE11_
GRM32RB11C475KC18_	GRM185R61C475KE11_
GRM32RB11H824MA01_	GRM188D71H105ME01_
GRM32RB11H824MA01_	GRM188D71H105ME01_
GRM32RB11H824KA01_	GRM188D71H105KE01_
GRM32RB11H824KA01_	GRM188D71H105KE01_
GRM32RB11H824JA01_	GRM188D71H105KE01_
GRM32RR11H824MA01_	GRM188D71H105ME01_
GRM32RR11H824KA01_	GRM188D71H105KE01_

GRM32RR11H824JA01_	GRM188D71H105KE01_
GRM32RR71C475JA01_	GRM188C71C475KE21_
GRM32RR71H824MA01_	GRM188D71H105ME01_
GRM32RR71H824KA01_	GRM188D71H105KE01_
GRM32RR71H824JA01_	GRM188D71H105KE01_
GRT32DR60J226ME01_	GRT188R60J226ME13_
GRT32DR61A226ME01_	GRT188R61A226ME13_
GRT32DR60J226KE01_	GRT188R60J226ME13_
GRT32DR61A226KE01_	GRT188R61A226ME13_
GRM32DB11E335KA01_	GRM188R61E475KE11_
GRM32DB11E335KA01_	GRM188R61E475KE11_
GRM32DB11E335MA01_	GRM188R61E475ME11_
GRM32DB11E335MA01_	GRM188R61E475ME11_
GRT32ER60J226ME01_	GRT188R60J226ME13_

GRT32ER61A226ME01_	GRT188R61A226ME13_
GRT32ER60J226KE01_	GRT188R60J226ME13_
GRT32ER61A226KE01_	GRT188R61A226ME13_
GCM31MR71H184KA02_	GCM31MR91H224KA37_
GCM31MR71H184KA01_	GCM21BR71H224KA01_
GCM31MR71H184MA01_	GCM21BR71H224MA37_
GCM31MR72A184MA37_	GCM21BC72A105ME36_
GCM31MR72A184KA37_	GCM21BC72A105ME36_
GCM31MR72A184JA37_	GCM21BC72A105ME36_
GRM32RR71C475KA01_	GRM21BR71C475KE51_
GRM32RR71C475KC01_	GRM21BR71C475KE51_
GRM32RR71C475MA01_	GRM21BR71C475ME51_
GRM32RR71C475MC01_	GRM21BR71C475ME51_
GRM32RR71E225KA01_	GRM21BR71E225KE11_
GRM32RR71E225KA01_	GRM21BR71E225KE11_
GRM32RR71E225KA22_	GRM21BR71E225KE11_
GRM32RR71E225KC01_	GRM21BR71E225KE11_
GRM32RR71E225KC48_	GRM21BR71E225KE11_
GRM32RR71E225MA01_	GRM21BR71E225ME11_
GRM32RR71E225MA01_	GRM21BR71E225ME11_

GRM32RR71E225MC01_	GRM21BR71E225ME11_
GCM32RR71E824KA01_	GCM21BR71E824KA55_
GCM32RR71E824MA01_	GCM21BR71E824MA55_
GRM32RR11C475KA01_	GRM21BR71C475KE51_
GRM32RR11C475KA01_	GRM21BR71C475KE51_
GRM32RR11C475KC01_	GRM21BR71C475KE51_
GRM32RR11C475MA01_	GRM21BR71C475ME51_
GCM32RR11E824KA01_	GCM21BR71E824KA55_
GCM32RR11E824MA01_	GCM21BR71E824MA55_
GCM32DR71H474KA37_	GCM21BR71H474KA55_
GCM32DR71H474MA37_	GCM21BR71H474MA55_
GRT32DC81E335KE01_	GRT21BC81E335KE13_
GRT32DR61H335KE01_	GRT21BR61H475KE13_
GRT32DR61H335ME01_	GRT21BR61H475KE13_
GRM32DB31H335KA87_	GRM21BR61H475KE51_
GRM32DB31H335KA87_	GRM21BR61H475KE51_
GRM32DB31H335MA87_	GRM21BR61H475ME51_

GRM32DB31H335MA87_	GRM21BR61H475ME51_
GCM32DR11E335KA01_	GCM21BC71E475KE36_
GCM32DR11E335MA01_	GCM21BC71E475ME36_
GRT32DC81H335KE01_	GRT21BC71H475KE13_
GRT32DC81H335ME01_	GRT21BC71H475KE13_
GCM32DR71E335KA01_	GCM21BC71E475KE36_
GCM32DR71E335KA17_	GCM21BC71E475KE36_
GCM32DR71E335KA51_	GCM21BC71E475KE36_
GCM32DR71E335MA01_	GCM21BC71E475ME36_
GRM32DR72A155MA35_	GRM21BD72A225ME01_
GRM32DR72A155KA35_	GRM21BD72A225KE01_
GRM32EB11A106KA01_	GRM21BR71A106KA73_
GRM32EB11A106KA01_	GRM21BR71A106KA73_

GRM32EB11A106KC01_	GRM21BR71A106KA73_
GRM32ER61A106KA01_	GRM21BR71A106KA73_
GRM32ER61A106KC01_	GRM21BR71A106KA73_
GRM31ML81H394KA01_	GCM31ML81H394KA01_
GRM32RR61E475KA12_	GRM188R61E475KE11_
GRM32RR61E475KC31_	GRM188R61E475KE11_
GRM32RR61E475KC31_	GRM188R61E475KE11_
GRM32RR61E475MC31_	GRM188R61E475ME11_
GRM32DR61C226KE18_	GRM319R61C226KE15_
GRM32DR61C226KE18_	GRM319R61C226KE15_
GRM32DR61C226ME18_	GRM319R61C226ME15_
GRM32DB31C226KE18_	GRM319R61C226KE15_
GRM32DB31C226ME18_	GRM319R61C226ME15_
GRM32DB11E475KA61_	GRM188R61E475KE11_
GRM32DB11E475KA61_	GRM188R61E475KE11_
GRM32DB11E475MA61_	GRM188R61E475ME11_
GRM32DB11E475MA61_	GRM188R61E475ME11_
GCM32DR71E475KA14_	GCM31CR71E475KA55_
GCM32DR71E475KA40_	GCM31CR71E475KA55_
GCM32DR71E475KA41_	GCM31CR71E475KA55_
GCM32DR71E475KA55_	GCM31CR71E475KA55_

GCM32DR71E475MA40_	GCM31CR71E475MA55_
GCM32DR71E475MA55_	GCM31CR71E475MA55_
GRT32DR61E335KE01_	GRT31CR61E335KE01_
GCM32DR71H335JA55_	GCM31CC71H475KA03_
GRT32DR61E335ME01_	GRT31CR61E335KE01_
GCM32DR71E475JA55_	GCM31CR71E475KA55_
GRM32DR71H335KA36_	GRM31CR71H475KA12_
GRM32DR71H335KA88_	GRM31CR71H475KA12_
GRM32DR71H335KA88_	GRM31CR71H475KA12_
GRM32DR71H335KA88_	GRM31CR71H475KA12_
GRM32DR71H335KA88_	GRM31CR71H475KA12_
GRM32DR71H335KA88_	GRM31CR71H475KA12_
GRM32DR71H335MA88_	GRM31CR71H475MA12_
GRM32DR60J336ME19_	GRM31CR60J476ME19_
GRM32DR71E475KA61_	GRM21BC71E475KE11_
GRM32DR71E475MA61_	GRM21BC71E475ME11_
GRM32DR71E335KA01_	GRM21BC71E475KE11_

GRM32DR71E335MA01_	GRM21BC71E475ME11_
GRM32DB30J336ME18_	GRM31CR60J476ME19_
GRM32DB10J226KA01_	GRM31CR70J226KE19_
GRM32DB10J226KA01_	GRM31CR70J226KE19_
GRM32DB10J226MA01_	GRM31CR70J226ME19_
GRM32DB10J226MA01_	GRM31CR70J226ME19_
GRM32DB31A226KE18_	GRM31CR71A226KE15_
GCM32DR11E475KA40_	GCM31CR71E475KA55_
GCM32DR11E475MA40_	GCM31CR71E475MA55_
GRM32DR11E475KA61_	GRM188R61E475KE11_
GRM32DR11E475KA61_	GRM188R61E475KE11_
GRM32DR11E475MA61_	GRM188R61E475ME11_
GRM32DR11E335KA01_	GRM188R61E475KE11_
GRM32DR11E335KA01_	GRM188R61E475KE11_
GRM32DR11E335MA01_	GRM188R61E475ME11_

GRM32D1X1E474JA01_	GRM31C5C1E474JE01_
GRM32D7U1E474JA01_	GRM31C5C1E474JE01_
GRM32D3U1E474JA01_	GRM31C5C1E474JE01_
GRT32DR60J336ME01_	GRT31CC80J476KE13_
GXT32DR60J336ME01_	GXT31CC80J476KE13_
GRM32DR60J226KA01_	GRM31CR70J226KE19_
GRM32DR60J226KA36_	GRM31CR70J226KE19_
GRM32DR60J226MA01_	GRM31CR70J226ME19_
GRM32DR61A226KE18_	GRM31CR71A226KE15_
GRM32DR61A226ME18_	GRM31CR71A226ME15_
GRT32DC81E335ME01_	GRT31CR61E335KE01_
GCM32DR71H335KA40_	GCM31CC71H475KA49_
GCM32DR71H335KA51_	GCM31CC71H475KA03_
GCM32DR71H335KA55_	GCM31CC71H475KA03_

GCM32DR71H335KA55_	GCM31CC71H475KA03_
GCM32DR71H335MA40_	GCM31CC71H475KA49_
GCM32DR71H335MA55_	GCM31CC71H475KA03_
GRT32DR61C226ME01_	GRT31CC71C226ME13_
GRT32DR61C226KE01_	GRT31CC71C226ME13_
GCG32DR71E335JA01_	GCG31CR71E335JA01_
GCG32DR71E335KA15_	GCG31CR71E335KA01_
GCG32DR71E475KA15_	GCG31CR71E475KA01_
GRM32EB10J226KA14_	GRM31CR70J226KE19_
ZRA21MD71A475KE11_	#NV
ZRA21MD71A475ME11_	#NV
GRM32EB10J226MA14_	GRM31CR70J226ME19_
GRM32EB31A226KA76_	GRM31CR71A226KE15_
GRM32EB31A226KA76_	GRM31CR71A226KE15_
GRM32EB31A226MA76_	GRM31CR71A226ME15_
ZRA21MB31A226ME11_	#NV
GRM32EB31A226MA76_	GRM31CR71A226ME15_
ZRA21MR61A226ME11_	#NV
GRM32ER60J226KA14_	GRM31CR70J226KE19_

GRM32ER60J226MA14_	GRM31CR70J226ME19_
GRM32ER60J226MA33_	GRM31CR70J226ME19_
GRM32ER60J226MA53_	GRM31CR70J226ME19_
GRM32ER61A226KA65_	GRM31CR71A226KE15_
GRM32ER61A226MA65_	GRM31CR71A226ME15_
GRM32ER61C106KA12_	GRM21BR61C106KE15_
GRM32ER61C106KC27_	GRM21BR61C106KE15_
GRM32ER61C106KC31_	GRM21BR61C106KE15_
GRM32ER61C106KC31_	GRM21BR61C106KE15_
GRM32ER61C106KC31_	GRM21BR61C106KE15_
GRM32ER61C106MA12_	GRM21BR61C106ME15_
GRM32ER61C106MC31_	GRM188R61C106MA73_
GRT32ER61E226KE11_	GRT31CC71E226ME13_
GRJ31CR71E106KE11_	GCJ21BC71E106KE02_
GRJ31CR71E106ME11_	GCJ21BC71E106KE02_
GRJ319R72A104KE11_	GCJ21BR72A104KA01_
GRJ319R72A104ME11_	GCJ21BR72A104MA01_

GRJ319R71H104KE11_	GCJ21BR72A104KA01_
GRJ319R71H104ME11_	GCJ21BR72A104MA01_
GRJ31MR71H104KE01_	GCJ21BR72A104KA01_
GRJ31MR71H104ME01_	GCJ21BR72A104MA01_
GRJ31MR71H474ME01_	GCJ21BR71H474MA12_
GRJ31MR71H224KE01_	GCJ21BR71H224KA01_
GRJ31MR71H224ME01_	GCJ21BR71H224MA01_
GRJ31CR71C106KE11_	GCJ21BC71E106KE02_
GRJ31CR71C106ME11_	GCJ21BC71E106KE02_
GRM31ML81H104KA01_	GCM188L81H104KA57_
GRM31ML81H104MA01_	GCM188L81H104MA57_
GRM31ML81H124KA01_	GCM21BL81H124KA37_
GRM31ML81H184KA01_	GCM21BL81H224KA01_

GRM31ML81H274KA01_	GCM21BL81H334KA42_
GCM219R11A474JA01_	GCM155C71A474KE36_
GCM219R11A474KA01_	GCM155C71A474KE36_
GCM219R11A474MA01_	GCM155C71A474ME36_
GCM219R11A564JA01_	GCM155C71A105KE38_
GCM219R11A564KA01_	GCM155C71A105KE38_
GCM219R11A564MA01_	GCM155C71A105ME38_
GCM219R11A684JA01_	GCM155C71A105KE38_
GCM219R11A684KA01_	GCM155C71A105KE38_
GCM219R11A684MA01_	GCM155C71A105ME38_
GCM219R11C204JA01_	GCM155R71C224KE02_
GCM219R11C204KA01_	GCM155R71C224KE02_

GCM219R11C204MA01_	GCM155R71C224ME01_
GCM219R11C224JA01_	GCM155R71C224KE02_
GCM219R11C224KA01_	GCM155R71C224KE02_
GCM219R11C224KA01_	GCM155R71C224KE02_
GCM219R11C224MA01_	GCM155R71C224ME01_
GCM219R11C244JA01_	GCM188R71C274KA37_
GCM219R11C244KA01_	GCM188R71C274KA37_
GCM219R11C244MA01_	GCM188R71C274MA37_
GCM219R11C274JA01_	GCM188R71C274KA37_
GCM219R11C274KA01_	GCM188R71C274KA37_
GCM219R11C274MA01_	GCM188R71C274MA37_
GCM219R71A474JA01_	GCM155C71A474KE36_
GCM219R71A474KA01_	GCM155C71A474KE36_
GCM219R71A474MA01_	GCM155C71A474ME36_

GCM219R71A564JA01_	GCM155C71A105KE38_
GCM219R71A564KA01_	GCM155C71A105KE38_
GCM219R71A564MA01_	GCM155C71A105ME38_
GCM219R71A684JA01_	GCM155C71A105KE38_
GCM219R71A684KA01_	GCM155C71A105KE38_
GCM219R71A684MA01_	GCM155C71A105ME38_
GCM219R71C204JA01_	GCM155R71C224KE02_
GCM219R71C204JA37_	GCM155R71C224KE02_
GCM219R71C204KA01_	GCM155R71C224KE02_
GCM219R71C204KA37_	GCM155R71C224KE02_
GCM219R71C204MA01_	GCM155R71C224ME01_
GCM219R71C204MA37_	GCM155R71C224ME01_
GCM219R71C224JA01_	GCM155R71C224KE02_

GCM219R71C224JA37_	GCM155R71C224KE02_
GCM219R71C224KA01_	GCM155R71C224KE02_
GCM219R71C224KA02_	GCM155R71C224KE02_
GCM219R71C224KA37_	GCM155R71C224KE02_
GCM219R71C224KA51_	GCM155R71C224KE02_
GCM219R71C224MA01_	GCM155R71C224ME01_
GCM219R71C224MA37_	GCM155R71C224ME01_
GCM219R71C244JA01_	GCM188R71C274KA37_
GCM219R71C244JA37_	GCM188R71C274KA37_
GCM219R71C244KA01_	GCM188R71C274KA37_
GCM219R71C244MA01_	GCM188R71C274MA37_
GCM219R71C274JA01_	GCM188R71C274KA37_
GCM219R71C274JA37_	GCM188R71C274KA37_
GCM219R71C274KA01_	GCM188R71C274KA37_
GCM219R71C274KA37_	GCM188R71C274KA37_
GCM219R71C274MA01_	GCM188R71C274MA37_
GCM219R71C274MA37_	GCM188R71C274MA37_
GCM21BR11A824JA01_	GCM155C71A105KE38_

GCM21BR11A824KA01_	GCM155C71A105KE38_
GCM21BR11A824MA01_	GCM155C71A105ME38_
GCM21BR71A824JA01_	GCM155C71A105KE38_
GCM21BR71A824KA01_	GCM155C71A105KE38_
GCM21BR71A824MA01_	GCM155C71A105ME38_

相違点/difference
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.50mm to 0.35mm ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.50mm to 0.35mm ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.50mm to 0.35mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.50mm to 0.35mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.50mm to 0.35mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.50mm to 0.39mm
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.50mm to 0.39mm
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.12uF to 0.22uF

▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 0603M(0201inch) ▪ T size(Max):0.90mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ LW size:1608M(0603inch) to 1005M(0402inch)

[illegible]

▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Capacitance:0.18uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R

▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.18uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R

▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:1608M(0603inch) to 1005M(0402inch) ▪ T size(Max):0.90mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%

• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X5R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X5R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X5R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X5R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X5R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X5R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X5R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X7R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X7R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:B to X7R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:X5R to X7R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:X5R to X7R
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:X6S to X6T
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:X7T to X7S
• LW size:1608M(0603inch) to 1005M(0402inch) • Temperature characteristics:X7T to X7S
• LW size:2012M(0805inch) to 0603M(0201inch) • T size(Max):0.70mm to 0.33mm • Temperature characteristics:B to X5R
• LW size:2012M(0805inch) to 0603M(0201inch) • T size(Max):0.70mm to 0.33mm • Temperature characteristics:B to X5R
• LW size:2012M(0805inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:B to X5R
• LW size:2012M(0805inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:B to X5R
• LW size:2012M(0805inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:B to X5R
• LW size:2012M(0805inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:B to X5R

▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X5R
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X5R
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X5R
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X5R
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X5R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X5R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.33mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.35mm ▪ Capacitance Tolerance:±10% to ±20%

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.35mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature Characteristics:X5R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature Characteristics:X5R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.60mm ▪ Temperature characteristics:X7T to X7S
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.60mm ▪ Temperature characteristics:X7T to X7S
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.70mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.70mm ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.33mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:1.5uF to 2.2uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Rated Voltage:10V to 16V

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Rated Voltage:10V to 16V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF TOL:±10% to ±20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF TOL:±10% to ±20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Rated Voltage:6.3V to 10V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Rated voltage:6.3V to 10V ▪ Capacitance tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.33mm ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.33mm ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.82uF to 1uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.68uF to 1uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:10V to 16V ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:0.82uF to 1uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X5R ▪ Capacitance:0.68uF to 1uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.18uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.56uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.82uF to 1uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch)
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:B to X7R

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Rated Voltage:10V to 16V
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Rated Voltage:10V to 16V ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X5R to X7S ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X6S to X7R

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.90mm ▪ Temperature characteristics:X6S to X7R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm ▪ Temperature characteristics:B to X6S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm ▪ Temperature characteristics:B to X6S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm ▪ Temperature characteristics:B to X6S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm ▪ Temperature characteristics:B to X6S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm ▪ Temperature characteristics:X5R to X6S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm ▪ Temperature characteristics:X5R to X6S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.85mm to 0.55mm ▪ Temperature characteristics:X5R to X6S ▪ Capacitance Tolerance:±10% to ±20%

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.85mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to 20%

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X6S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X6S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X6S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X6S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X6S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X6S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X5R to X6S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X5R to X6S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X5R to X6S ▪ Capacitance Tolerance:±10% to ±20%

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:3.3uF to 4.7uF ▪ Capacitance Tolerance:±20% to ±10%

[illegible]

[illegible]

• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• Capacitance Tolerance: $\pm 5\%$ to $\pm 10\%$
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• Capacitance:0.27 μ F to 0.47 μ F
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• Capacitance:0.27 μ F to 0.47 μ F
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• Capacitance:0.27 μ F to 0.47 μ F
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• Capacitance:0.27 μ F to 0.47 μ F
• LW size:2012M(0805inch) to 1608M(0603inch)
• T size(Max):0.95mm to 0.90mm
• Temperature characteristics:B to X7R
• Capacitance:0.27 μ F to 0.47 μ F

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Rated Voltage:0G to 0J ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Rated Voltage:2.5V to 4V
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Rated Voltage:25V to 50V
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Rated Voltage:25V to 50V ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:B to X5R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:X5R to X7S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:X5R to X7S ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:X6S to X7S

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:X6S to X7S ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:X7T to X7S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 1.00mm ▪ Temperature characteristics:X7T to X7S
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.16uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm

▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):1.40mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF

▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R

[illegible]

▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF

[illegible]

[illegible]

• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
• LW size:3216M(1206inch) to 0603M(0201inch) • T size(Max):0.95mm to 0.33mm • Temperature characteristics:R to X7S • Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature Characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature Characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:82nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:82nF to 100nF
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.33mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.35mm ▪ Capacitance Tolerance:±10% to ±20%

▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.35mm ▪ Temperature Characteristics:B to X5R ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.35mm ▪ Temperature Characteristics:B to X5R ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):0.95mm to 0.35mm ▪ Temperature Characteristics:B to X5R ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):1.25mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):1.25mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):1.25mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):1.25mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):1.25mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 0603M(0201inch) ▪ T size(Max):1.25mm to 0.33mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.65mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.65mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.70mm to 0.65mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:1800pF to 2200pF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:2700pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:2700pF to 4700pF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3300pF to 4700pF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:36nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:36nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3900pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3900pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3900pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3900pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:3900pF to 4700pF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:43nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:43nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:51nF to 100nF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:51nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:51nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:62nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:62nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:62nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:6800pF to 10000pF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:75nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:75nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:75nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:8200pF to 10000pF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:51nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:51nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:62nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:62nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF

[illegible]

[illegible]

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:2700pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:30nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:30nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3300pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:36nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:36nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3900pF to 4700pF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:51nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:62nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:75nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:0.56uF to 1uF

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:1800pF to 2200pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:2700pF to 4700pF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:2700pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:2700pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:27nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:27nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:27nF to 47nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:30nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:30nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:3300pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:3300pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:3300pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:33nF to 47nF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:36nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:36nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:3900pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:3900pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:3900pF to 4700pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:43nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:43nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:51nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:51nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:51nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:62nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:62nF to 100nF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:62nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:75nF to 100nF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:75nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:75nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.68uF to 1uF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:39nF to 47nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:51nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:62nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:75nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:91nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:91nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Capacitance:91nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.18uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:87nF to 100nF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:91nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%

[illegible]

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:39nF to 47nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:91nF to 100nF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:91nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:91nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1uF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.18uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.12uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.55mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%

[illegible]

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:12nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:15nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:5600pF to 10000pF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:5600pF to 10000pF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:6800pF to 10000pF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:6800pF to 10000pF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:8200pF to 10000pF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:8200pF to 10000pF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X8R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X8R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature Characteristics:X7R to C0G
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature Characteristics:X7R to C0G ▪ Temperature Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:X7R to X8R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:X7R to X8R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.13uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.16uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.33uF to 0.47uF

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:18nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:18nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:18nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:18nF to 22nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:56nF to 100nF
▪ Series:GRM to GCM
▪ Series:GRM to GCM
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:56nF to 100nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:56nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:68nF to 100nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:68nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:87nF to 100nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:87nF to 100nF

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:87nF to 100nF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:0.12uF to 0.22uF

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.56uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.30mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.30mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.30mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.30mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.68uF to 1uF
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X8R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:R to X8R

▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X7R to X8R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.35mm to 0.90mm ▪ Temperature characteristics:X7R to X8R
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.80mm to 0.90mm
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ Series:GRJ to GCJ ▪ Temperature characteristics:X5R to X7T ▪ Capacitance Tolerance:±10% to ±20%
▪ Series:GRJ to GCJ ▪ Temperature Characteristics:X5R to X7T
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ Temperature characteristics:B to X5R

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ Temperature characteristics:B to X5R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Rated Voltage:10V to 16V

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Rated Voltage:10V to 16V ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch)
▪ LW size:3216M(1206inch) to 1005M(0402inch)
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X6S to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 1.40mm ▪ Temperature characteristics:X6S to X7R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 1005M(0402inch)
▪ LW size:3216M(1206inch) to 1005M(0402inch)
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 1.00mm ▪ Temperature characteristics:X7T to X7S
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 1.00mm ▪ Temperature characteristics:X7T to X7S
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:B to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:B to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:B to C0G ▪ Capacitance:30nF to 33nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to C0G ▪ Capacitance:30nF to 33nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to U2J

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to U2J ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to U2J ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to U2J ▪ Capacitance:36nF to 39nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature characteristics:R to U2J ▪ Capacitance:36nF to 39nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to C0G ▪ Capacitance:24nF to 27nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to C0G ▪ Capacitance:30nF to 33nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to U2J ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to U2J ▪ Capacitance Tolerance:±10% to ±5%

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to U2J ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.65mm ▪ Temperature Characteristics:X7R to U2J ▪ Capacitance:36nF to 39nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.7mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:B to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.35mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.35mm ▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.35mm ▪ Capacitance:0.27uF to 0.47uF

▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Capacitance:0.27uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Capacitance:0.27uF to 0.47uF
▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Capacitance:0.33uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Capacitance:0.33uF to 0.47uF
▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Temperature characteristics:B to C0G
▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Temperature characteristics:B to C0G
▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Temperature characteristics:B to C0G
▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Temperature characteristics:B to C0G
▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch)
▪ T size(Max):0.95mm to 1.35mm
▪ Temperature characteristics:B to C0G
▪ Capacitance Tolerance:±10% to ±5%

[illegible]

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.35mm ▪ Temperature characteristics:B to U2J ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.35mm ▪ Temperature characteristics:B to U2J ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.35mm ▪ Temperature characteristics:B to U2J ▪ Capacitance:36nF to 39nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.40mm ▪ Temperature characteristics:B to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.45mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.45mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.45mm

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Temperature characteristics:R to X7R

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.95mm ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.00mm ▪ Capacitance:0.15uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.68uF to 1.00uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.68uF to 1.00uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.68uF to 1.00uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:0.68uF to 1.00uF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:27nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:27nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:27nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:33nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Capacitance:39nF to 47nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:B to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:B to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:B to U2J ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:B to U2J ▪ Capacitance Tolerance:±10% to ±5%

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:B to U2J ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:B to U2J ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:R to U2J ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:R to U2J ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.35mm ▪ Temperature characteristics:X7R to U2J ▪ Capacitance Tolerance:±20% to ±5%

[illegible]

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.12uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.27uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.39uF to 0.47uF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.56uF to 1uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.82uF to 1uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:91nF to 100nF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.70mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:6.3V to 10V ▪ Capacitance Tolerance:±10% to 20%

▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.70mm ▪ Temperature characteristics:B to X5R ▪ Rated Voltage:6.3V to 10V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3216M(1206inch) to 1005M(0402inch) ▪ T size(Max):1.25mm to 0.70mm ▪ Rated Voltage:6.3V to 10V ▪ Capacitance Tolerance:±10% to 20%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Capacitance:0.15uF to 1.00uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Capacitance:0.15uF to 1.00uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Capacitance:0.15uF to 1.00uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Capacitance:0.15uF to 1.00uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Capacitance:0.15uF to 1.00uF

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Capacitance:0.15uF to 1.00uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm ▪ Temperature characteristics:B to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.30mm to 1.40mm ▪ Temperature characteristics:X5R to X7R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm ▪ Capacitance:0.27uF to 0.33uF

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm ▪ Temperature characteristics:R to X7R
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 0.95mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.35mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.35mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.15uF to 0.22uF

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.18uF to 0.22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.39uF to 0.47uF
▪ T size(Max):0.45mm to 0.70mm ▪ Capacitance:5.6uF to 10uF
▪ Series:GRJ to GCJ ▪ T size(Max):1.20mm to 2.00mm ▪ Temperature characteristics:X5R to X7S ▪ Capacitance:17uF to 22uF
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.50mm ▪ Temperature characteristics:X7R to X7S ▪ Rated Voltage:50V to 100V ▪ Capacitance:474 to 105
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.90mm to 1.45mm
▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):0.70mm to 0.95mm ▪ Rated Voltage:10V to 16V ▪ Capacitance:335 to 475
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.70mm to 0.95mm ▪ Rated Voltage:10V to 16V ▪ Capacitance:335 to 475 ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.65mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 0.65mm ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±20% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:B to C0G ▪ Capacitance Tolerance:±10% to ±5%

▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:CH to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:CH to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:CH to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:R to X7R ▪ Rated Voltage:50V to 100V
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:SL to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:SL to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:SL to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:SL to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:SL to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:SL to C0G
▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ Temperature characteristics:SL to C0G
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.00mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.00mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.00mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.00mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.20mm to 0.55mm ▪ Temperature characteristics:U2J to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.70mm to 0.70mm
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.70mm to 0.70mm
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.70mm to 0.70mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1005M(0402inch) ▪ T size(Max):2.70mm to 0.70mm ▪ Temperature characteristics:B to X5R

▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.55mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:B1 to D7 ▪ Capacitance:0.82uF to 1uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:B1 to D7 ▪ Capacitance:0.82uF to 1uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:B1 to D7 ▪ Capacitance:0.82uF to 1uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:B1 to D7 ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.82uF to 1uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.82uF to 1uF

▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:R to X7T ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.82uF to 1uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.82uF to 1uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 1.00mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:0.82uF to 1uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.70mm to 1.00mm

▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.00mm to 1.40mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm ▪ Capacitance:3.3uF to 4.7uF TOL:±20% to ±10%
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF

▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.40mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X6S to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X6S to X7S ▪ Capacitance:3.3uF to 4.7uF TOL:±20% to ±10%
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:1.5uF to 2.2uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature characteristics:X7R to X7T ▪ Capacitance:1.5uF to 2.2uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.40mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.40mm ▪ Temperature characteristics:B to X7R

▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.40mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.40mm ▪ Temperature characteristics:X5R to X7R
▪ Series:GRM→GCM
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.95mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.95mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.95mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.00mm to 0.95mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 0.95mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 0.95mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 0.95mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:B to X5R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm

▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm TC.:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Capacitance:33uF to 47uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF

▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.20mm to 1.45mm ▪ Temperature Characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:B to X5R ▪ Capacitance:33uF to 47uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:R to X7R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:R to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:R to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:R to X5R
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.20mm to 0.95mm ▪ Temperature characteristics:R to X5R ▪ Capacitance:3.3uF to 4.7uF

▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:SL to C0G
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:U2J to C0G
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:UJ to C0G
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X5R to X6S ▪ Capacitance:33uF to 47uF TOL:±20% to ±10%
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X5R to X6S ▪ Capacitance:33uF to 47uF TOL:±20% to ±10%
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X6S to X5R ▪ Capacitance Tolerance:±20% to ±10%
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF

▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.80mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:3.3uF to 4.7uF
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.90mm ▪ Temperature characteristics:X5R to X7S
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.20mm to 1.90mm ▪ Temperature characteristics:X5R to X7S ▪ Capacitance Tolerance:±10% to ±20%
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.3mm to 1.90mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.3mm to 1.90mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.3mm to 1.90mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:B to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:X5R to X7R

▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:X5R to X7R
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.35mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.35mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.35mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.35mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.35mm
▪ LW size:3225M(1210inch) to 2012M(0805inch) ▪ T size(Max):2.70mm to 1.35mm
▪ LW size:3225M(1210inch) to 1608M(0603inch) ▪ T size(Max):2.70mm to 1.00mm
▪ LW size:3225M(1210inch) to 3216M(1206inch) ▪ T size(Max):2.70mm to 1.80mm ▪ Temperature characteristics:X5R to X7S ▪ Capacitance Tolerance:±10% to ±20%
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.90mm to 1.50mm ▪ Temperature characteristics:X7R to X7S
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.90mm to 1.50mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance Tolerance:±20% to ±10%
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.45mm
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.45mm

▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.45mm ▪ Rated Voltage:50V to 100V
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):0.95mm to 1.45mm ▪ Rated Voltage:50V to 100V
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Rated Voltage:50V to 100V
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.45mm ▪ Rated Voltage:50V to 100V
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.40mm
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.35mm to 1.45mm
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.90mm to 1.50mm ▪ Temperature characteristics:X7R to X7S ▪ Rated Voltage:16V to 25V
▪ Series:GRJ to GCJ ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.90mm to 1.50mm ▪ Temperature characteristics:X7R to X7S ▪ Rated Voltage:16V to 25V ▪ Capacitance Tolerance:±20% to ±10%
▪ Series:GRM to GCM ▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm
▪ Series:GRM to GCM ▪ LW size:3216M(1206inch) to 1608M(0603inch) ▪ T size(Max):1.25mm to 0.90mm
▪ Series:GRM to GCM ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm
▪ Series:GRM to GCM ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.18uF to 0.22uF

▪ Series:GRM→GCM ▪ LW size:3216M(1206inch) to 2012M(0805inch) ▪ T size(Max):1.25mm to 1.40mm ▪ Capacitance:0.27uF to 0.33uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.60mm ▪ Temperature characteristics:R to X7S ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.60mm ▪ Temperature characteristics:R to X7S
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.60mm ▪ Temperature characteristics:R to X7S
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1.0uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.56uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1.0uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.68uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.20uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.20uF to 0.22uF

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.20uF to 0.22uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.24uF to 0.27uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.24uF to 0.27uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance:0.24uF to 0.27uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Temperature characteristics:R to X7R
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.60mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.60mm ▪ Temperature characteristics:X7R to X7S
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.60mm ▪ Temperature characteristics:X7R to X7S

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1.0uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.56uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1.0uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.68uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:0.20uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:0.20uF to 0.22uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:0.20uF to 0.22uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:0.20uF to 0.22uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:0.20uF to 0.22uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance:0.20uF to 0.22uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):0.95mm to 0.55mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.24uF to 0.27uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.24uF to 0.27uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.24uF to 0.27uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.24uF to 0.27uF
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.24uF to 0.27uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm ▪ Capacitance:0.24uF to 0.27uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1608M(0603inch) ▪ T size(Max):0.95mm to 0.90mm
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1.0uF ▪ Capacitance Tolerance:±5% to ±10%

▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.70mm ▪ Temperature characteristics:R to X7S ▪ Capacitance:0.82uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1.0uF ▪ Capacitance Tolerance:±5% to ±10%
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1.0uF
▪ LW size:2012M(0805inch) to 1005M(0402inch) ▪ T size(Max):1.35mm to 0.70mm ▪ Temperature characteristics:X7R to X7S ▪ Capacitance:0.82uF to 1.0uF

Affected PN
GRM185R61A105*
GRM185B31A105*
GRM185C80G225*
GRM185C80J105*
GRM188R61A124*
GRM188R61A154*
GRM188R61A184*
GRM188B11A124*
GRM188B11A154*
GRM188B11A184*
GRM185R61E105*
GRM185R61A225*
GRM185R60G475*
GRM185R60J475*
GRM185C81A105*
GRM185R61C105*
GRM185R60J225*
GRM185B31E105*
GRM185R60J105*
GRM185B10J105*
GRM185B30J105*
GRM188R71A224*
GRM188B11A224*
GRM188R71A124*
GRM188R71A154*
GRM188R71A184*
GXM188B11A224*
GRM188R11A224*
GRM188R11A124*
GRM188R11A154*
GRM188R11A184*
GRM188R61A224*
GRM185B31C105*
GRM185B30J225*
GRM185B31A225*
GRM185B30G475*
GRM185B30J475*
GRM185C80E475*
GRM185D71A105*
GRM216B11A224*
GRM219B11C224*
GRM219R11C224*
GRM216R11A334*
GRM216R61A105*
GRM216B11A105*
GRM216R71A224*
GRM216C81C105*
GRM216R61C105*
GRM216R61E105*

GRM216R71A334*
GRM216B31C105*
GRM216B31E105*
GRM216B11A274*
GRM216B11A334*
GRM216B11A394*
GRM216R11A224*
GRM216R11A274*
GRM216R11A394*
GRM216R61A334*
GRM216D71C105*
GRT216R61A225*
GRM219R61A105*
GRM219B11A105*
GRM219R71C224*
GRT219R61A225*
GRM219C80G106*
GRM219R60J155*
GRM219B11C564*
GRM219B11C684*
GRM219B31A335*
GRM219R11C564*
GRM219R11C684*
GRM219R71C564*
GRM219R71C684*
GRT219C80J475*
GRM21BR61A684*
GRM21BR61A824*
GRM21BB11A684*
GRM21BB11A824*
GRM21BR61C824*
GRM21BB31H154*
GRM21BB31H184*
GRM21BB31E564*
GRM21BB31E684*
GXM21BB31E684*
GRM21BB31E824*
GRM21BB11C824*
GRM21BB11E334*
GRM21BR11E564*
GRM21BR11E684*
GRM21BR11E824*
GRM21BR11A684*
GRM21BR11A824*
GRM21BR11C824*
GRM21BR71E684*
GRM21BR71E824*
GRM21BR71A684*
GRM21BR71A824*
GRM21BR71C824*

GRM21BR71H154*
GRM21BR71H184*
GRM21BR71E564*
GRM216R61C225*
GRM216B31C225*
GRM216B31A225*
GRT216R61C105*
GRM216R61A225*
GRT216R61E105*
GRT216R61A105*
GRT216R61C225*
GRT216C81C105*
GRM219C80J475*
GRM219R61A475*
GRM219B31A475*
GRM219B30J475*
GRM219B10J475*
GRM219R60J475*
GRM219C81A475*
GRM219R61A335*
GRM219R61C335*
GRM219B31C335*
GRM219R71C474*
GRM219R60J106*
GRT219C80G106*
GRT219R61A226*
GRM219C81C225*
GRM219R61E225*
GRM219D71A475*
GRM219R71E224*
GRT219R60J106*
GRM219R71C274*
GRM219R71E274*
GRT219R61C335*
GRT219C81A475*
GRM219R61C225*
GRT219R61A335*
GRM219B30J106*
GRM219B31E225*
GRM219B31C225*
GRM219B11C474*
GRM219B11A225*
GRM219B11E224*
GRM219B11C274*
GRM219B11E274*
GRM219R11C474*
GRM219R11E224*
GRM219R11C274*
GRM219R11E274*
GRM219R61E474*

GRM219R61A225*
GRM219R60J226*
GRM219R61A226*
GRM219R60G226*
GRM219C80E226*
GRT219R61E225*
GRM219B30J226*
GRM219B31A226*
GRM219B30G226*
GRT219R61C225*
GRT219C81C225*
GRM219D71C225*
GRM21BR71H124*
GRM21BR71H164*
GRM21BR71C334*
GRM21BR71E334*
GRM21BR71C394*
GRM21BR71E394*
GRM21BB11C334*
GRM21BB11C394*
GRM21BB11E394*
GRM21BR11C334*
GRM21BR11E334*
GRM21BR11C394*
GRM21BR11E394*
GRM21BR61C334*
GRM21BR61C394*
GCM21BR71C334*
GCM21BR71E154*
GCM21BR71E184*
GCM21BR11E154*
GCM21BR11E184*
GRM319R71H221*
GRM319R71H331*
GRM319R71H391*
GRM319R71H471*
GRM319R71H561*
GRM319R71H681*
GRM319R71H821*
GRM319R71H102*
GRM319R71H152*
GRM319R71H122*
GRM319R71H271*
GRM319B11C104*
GRM319B11C683*
GRM319B11C823*
GRM319B11H221*
GRM319B11H331*
GRM319B11H471*
GRM319B11H681*

GRM319B11H102*
GRM319B11H152*
GRM319B11E104*
GRM319B11C224*
GRM319B11E563*
GRM319B11E683*
GRM319B11E823*
GRM319B11H391*
GRM319B11H561*
GRM319B11H821*
GRM319B11H122*
GRM319B11H271*
GRM319R11C104*
GRM319R11C224*
GRM319R11C683*
GRM319R11C823*
GRM319R11H221*
GRM319R11H331*
GRM319R11H391*
GRM319R11H471*
GRM319R11H561*
GRM319R11H681*
GRM319R11H821*
GRM319R11H102*
GRM319R11H152*
GRM319R11H122*
GRM319R11H271*
GRM319R71C104*
GRM319R71C683*
GRM319R71C823*
GRM319R61A105*
GRM319B11A105*
GRM31MB11E104*
GRM31MB11C224*
GRM316R61A225*
GRM316B11A225*
GRM316R61A335*
GRM316B31A335*
GRM319R72A221*
GRM319R72A471*
GRM319R72A102*
GRM319R71H222*
GRM319R71H472*
GRM319R72A222*
GRM319R72A472*
GCM319R71H104*
GCM319R71H153*
GCM319R71H223*
GRM319R71E104*
GRM319R71H104*

GRM319R71H224*
GRM319R61A225*
GRM319R61E105*
GCM319R71H221*
GCM319R72A221*
GCM319R71H331*
GCM319R72A331*
GCM319R71H391*
GCM319R72A391*
GCM319R71H471*
GCM319R72A471*
GCM319R71H561*
GCM319R72A561*
GCM319R71H681*
GCM319R72A681*
GCM319R71H821*
GCM319R72A821*
GCM319R71H102*
GCM319R72A102*
GCM319R71H152*
GCM319R72A152*
GCM319R71H182*
GCM319R71H222*
GCM319R71H272*
GCM319R71H332*
GCM319R71H392*
GCM319R71H472*
GCM319R71H562*
GCM319R71H682*
GCM319R71H822*
GCM319R72A182*
GCM319R72A222*
GCM319R72A272*
GCM319R72A332*
GCM319R72A392*
GCM319R72A472*
GRM319R71H103*
GCM319R71H123*
GCM319R71H183*
GRM319R71E473*
GRM319R71H223*
GRM319R71C224*
GRM319R61C105*
GCM319R71H122*
GCM319R71H271*
GCM319R72A122*
GCM319R72A271*
GCM319R71H103*
GRM319R71H123*
GRM319R71H153*

GRM319R71H182*
GRM319R72A182*
GRM319R71H272*
GRM319R72A272*
GRM319R71H273*
GCM319R71H273*
GRM319R71H303*
GRM319R71H332*
GRM319R72A332*
GRM319R71H333*
GRM319R71H363*
GRM319R71H392*
GRM319R72A392*
GRM319R71H393*
GRM319R71H433*
GRM319R71H513*
GRM319R71H562*
GRM319R71E563*
GRM319R71H563*
GRM319R71H623*
GRM319R71H682*
GRM319R71E683*
GRM319R71H683*
GRM319R71H753*
GRM319R71H822*
GRM319R71E823*
GRM319R71H823*
GRM319B11H182*
GRM319B11A225*
GRM319B31E105*
GRM319B11C105*
GRM319B11E564*
GRM319B11C564*
GRM319B11E684*
GRM319B11H513*
GRM319B11H563*
GRM319B11H623*
GRM319B11H683*
GRM319B11H753*
GRM319B11H823*
GRM319B11H222*
GRM319B11H472*
GRM319B11H104*
GRM319B11H103*
GRM319B11E473*
GRM319B11H223*
GRM319B11H123*
GRM319B11H153*
GRM319B11H272*
GRM319B11H303*

GRM319B11H332*
GRM319B11H363*
GRM319B11H392*
GRM319B11H562*
GRM319B11H682*
GRM319B11H822*
GRM319R11C564*
GRM319R11E564*
GRM319R11E684*
GRM319R11H222*
GRM319R11H472*
GCM319R11H153*
GCM319R11H223*
GRM319R11E104*
GRM319R11H104*
GCM319R11H221*
GCM319R11H331*
GCM319R11H391*
GCM319R11H471*
GCM319R11H561*
GCM319R11H681*
GCM319R11H821*
GCM319R11H102*
GCM319R11H152*
GCM319R11H103*
GCM319R11H182*
GCM319R11H222*
GCM319R11H272*
GCM319R11H332*
GCM319R11H392*
GCM319R11H472*
GCM319R11H562*
GCM319R11H682*
GCM319R11H822*
GRM319R11H103*
GCM319R11H104*
GCM319R11H123*
GCM319R11H183*
GRM319R11E473*
GRM319R11H223*
GCM319R11H122*
GCM319R11H271*
GRM319R11H123*
GRM319R11H153*
GRM319R11H182*
GRM319R11H272*
GRM319R11H273*
GCM319R11H273*
GRM319R11H303*
GRM319R11H332*

GRM319R11H333*
GRM319R11H363*
GRM319R11H392*
GRM319R11H393*
GRM319R11H433*
GRM319R11H513*
GRM319R11H562*
GRM319R11E563*
GRM319R11H563*
GRM319R11H623*
GRM319R11H682*
GRM319R11E683*
GRM319R11H683*
GRM319R11H753*
GRM319R11H822*
GRM319R11E823*
GRM319R11H823*
GRM319R11C105*
GRM319R11A105*
GRM319R72A331*
GRM319R72A391*
GRM319R72A561*
GRM319R72A681*
GRM319R72A821*
GRM319R72A122*
GRM319R72A271*
GRM319R71A105*
GRM319R71C105*
GRM319R71C564*
GCM319R71H124*
GRM319R71E564*
GRM319R71E684*
GRM31MR71E104*
GRM31MR71H104*
GCM31MR71H333*
GCM31MR71H683*
GRM31MR71C224*
GRM31MR61C564*
GRM31MR61C684*
GRM31MR61C824*
GRM31MR71H333*
GRM31MR71H393*
GCM31MR71H393*
GRM31MR71H513*
GRM31MR71H563*
GCM31MR71H563*
GRM31MR71H623*
GRM31MR71H683*
GRM31MR71H753*
GRM31MR71H823*

GCM31MR71H823*
GRM31MR71H913*
GCM31MR71H913*
GRM31MB11H224*
GRM31MB11H124*
GRM31MB11H154*
GRM31MB11H184*
GRM31MB11C564*
GRM31MB11C684*
GRM31MB11E824*
GRM31MB11C824*
GRM31MB11H563*
GRM31MB11H683*
GRM31MB11H823*
GRM31MB11H913*
GRM31MB11H104*
GRM31MR11H224*
GRM31MR11C684*
GRM31MR11C824*
GRM31MR11E824*
GRM31MR11E104*
GRM31MR11H104*
GCM31MR11H333*
GCM31MR11H683*
GRM31MR11C224*
GRM31MR11H333*
GRM31MR11H393*
GCM31MR11H393*
GRM31MR11H563*
GCM31MR11H563*
GRM31MR11H683*
GRM31MR11H823*
GCM31MR11H823*
GRM31MR11H913*
GCM31MR11H913*
GRM31MR11C564*
GRM31MR11H124*
GRM31MR11H154*
GRM31MR11H184*
GRM31MR71C564*
GRM31MR71C684*
GRM31MR71C824*
GRM31MR71H224*
GRM31MR71H124*
GCM31MR71H124*
GRM31MR71H154*
GRM31MR71H184*
GCM31MR71H184*
GRM31MR71E824*
GRM31XR61A335*

GRM31XB11A335*
GRM31CB11H224*
GCM319R72A103*
GCM319R72A562*
GCM319R72A682*
GCM319R72A822*
GRM319R72A103*
GCM319R72A123*
GCM319R72A153*
GRM319R72A104*
GRM319R71C474*
GRM319R71E474*
GRM319R71H124*
GRM319R71E274*
GRM319R71C334*
GRM319R71E334*
GRM319R71E394*
GRM319R72A123*
GRM319R72A153*
GRM319R72A562*
GRM319R72A682*
GRM319R72A822*
GRM319B11C474*
GRM319B11E474*
GRM319B11H124*
GRM319B11E274*
GRM319B11C334*
GRM319B11E334*
GRM319B11E394*
GRM319R11C474*
GRM319R11E474*
GRM319R11E224*
GRM319R11H124*
GRM319R11E274*
GRM319R11C334*
GRM319R11E334*
GRM319R11E394*
GCJ319R11H124*
GRM319R72A152*
GCJ319R71H124*
GRM31MR72A223*
GCM31MR71E154*
GCM31MR71H154*
GCM31MR72A183*
GRM31MR71E474*
GRM31MR71E224*
GCM31MR71E124*
GCM31MR71E184*
GRM31MR71H134*
GRM31MR71H164*

GRM31MR71C334*
GRM31MR71E394*
GRM31MR72A183*
GRM31MR72A563*
GRM31ML81H474*
GRM31MR72A683*
GRM31MR72A823*
GRM31MR72A913*
GRM31MB11C474*
GRM31MB11E474*
GRM31MB11E224*
GRM31MB11C334*
GRM31MB11E394*
GCM31MR11E154*
GCM31MR11H154*
GRM31MR11E474*
GRM31MR11E224*
GCM31MR11E124*
GCM31MR11E184*
GRM31MR11C334*
GRM31MR11E394*
GCM31MR71H564*
GRM31MR71H684*
GCM31MR71H824*
GRM31MR72A684*
GCJ31MR71E124*
GCJ31MR71E154*
GCJ31MR71E184*
GCJ31MR11E124*
GCJ31MR11E154*
GCJ31MR11E184*
GCJ31MR11H124*
GCJ31MR71H124*
GRM31CR71H224*
GRM3165C1H392*
GRM3165C1H472*
GRM3165C2A392*
GRM3165C2A472*
GRM3165C1H332*
GRM3165C2A332*
GRJ188R60J106*
GRM316B31E225*
GRM316B31A475*
GRM316B31C225*
GRT316R61C225*
GRT316R61E225*
GRT316R61A475*
GRM316R61E225*
GRM316R61A475*
GRT316R61A225*

GRM316R61C225*
GRT316C81C225*
GRM316C81C225*
GRM316D71C225*
GRM319B11H273*
GRM319B11H333*
GRM319R11H473*
GRM319R71H243*
GRM319R71H473*
GRM319B11E224*
GRM319R71H274*
GRM319R71H334*
GRM319B11H393*
GRM319B11H433*
GRM319B11H473*
GCM319R72A104*
GCM319R11H124*
GCM319B11H104*
GCJ319R72A104*
GCJ319R71H104*
GCJ319R11H104*
GRM31MB11H333*
GCM31MR72A273*
GCM31MR72A333*
GCM31MR72A393*
GCM31MR71H334*
GCM31MR71H274*
GCM31MR11H334*
GCM31MR11H274*
GRM31MR72A224*
GRM31MR72A124*
GRM31MR72A154*
GXM31MR71H474*
GRM31MR72A473*
GRM31MR71H474*
GCM31MR11H184*
GRM31MR71H394*
GCM31MR71H684*
GRM31MR72A273*
GRM31MR72A333*
GRM31MR72A393*
GRM31MB11H393*
GRM31MB11H473*
GRM31MR11H473*
GRM31MR71H433*
GRM31MR71H473*
GRM31MR71H363*
GCM31MR72A563*
GCM31MR72A683*
GCM31MR72A823*

GCM31ML81H124*
GCM31ML81H154*
GCM31ML81H184*
GCM31ML81H334*
GCM31MR11H124*
GCM31ML81H274*
GCM31MR71H394*
GCM31MR72A913*
GRM31MB10J475*
GCM31MR11H394*
GRM31MR61A475*
GRM31MR60J475*
GCM31MR72A154*
GRM31MR72A474*
GCJ31MR71H334*
GCJ31MR71H274*
GCJ31MR11H334*
GCJ31MR11H274*
GCJ31MR71H184*
GCJ31MR11H184*
GCJ31MR71H154*
GCJ31MR71H394*
GCJ31MR11H154*
GCJ31MR11H394*
GRM154R61A565*
GRJ31AR61C176*
GRJ31MR71H474*
GRJ31CR61E106*
GRT316R61A335*
GRM319B0YA105*
GRM3162C1H392*
GRM3162C1H472*
GRM3162C2A392*
GRM3162C2A472*
GRM3162C1H332*
GRM3162C2A332*
GRM3161X1H392*
GRM3161X1H472*
GRM3161X2A392*
GRM3161X2A472*
GRM3161X1H332*
GRM3161X2A332*
GRM32RB11E225*
GRM32D7U1A474*
GRM32ER61A106*
GRM32EB11A106*
GRM32RR61C475*
GRM32RB11C475*
GRM32RB11H824*
GRM32RR11H824*

GRM32RR71C475*
GRM32RR71H824*
GRT32DR60J226*
GRT32DR61A226*
GRM32DB11E335*
GRT32ER60J226*
GRT32ER61A226*
GCM31MR72A184*
GRM32RR71E225*
GCM32RR71E824*
GRM32RR11C475*
GCM32RR11E824*
GCM32DR71H474*
GRT32DC81E335*
GRT32DR61H335*
GRM32DB31H335*
GCM32DR11E335*
GRT32DC81H335*
GCM32DR71E335*
GRM32DR72A155*
GRM31ML81H394*
GRM32RR61E475*
GRM32DR61C226*
GRM32DB31C226*
GRM32DB11E475*
GCM32DR71E475*
GRT32DR61E335*
GCM32DR71H335*
GRM32DR71H335*
GRM32DR60J336*
GRM32DR71E475*
GRM32DR71E335*
GRM32DB30J336*
GRM32DB10J226*
GRM32DB31A226*
GCM32DR11E475*
GRM32DR11E475*
GRM32DR11E335*
GRM32D1X1E474*
GRM32D7U1E474*
GRM32D3U1E474*
GRT32DR60J336*
GXT32DR60J336*
GRM32DR60J226*
GRM32DR61A226*
GRT32DR61C226*
GCG32DR71E335*
GCG32DR71E475*
GRM32EB10J226*
ZRA21MD71A475*

GRM32EB31A226*
ZRA21MB31A226*
ZRA21MR61A226*
GRM32ER60J226*
GRM32ER61A226*
GRM32ER61C106*
GRT32ER61E226*
GRJ31CR71E106*
GRJ319R72A104*
GRJ319R71H104*
GRJ31MR71H104*
GRJ31MR71H224*
GRJ31CR71C106*
GRM31ML81H104*
GRM31ML81H124*
GRM31ML81H184*
GRM31ML81H274*
GCM219R11A474*
GCM219R11A564*
GCM219R11A684*
GCM219R11C204*
GCM219R11C224*
GCM219R11C244*
GCM219R11C274*
GCM219R71A474*
GCM219R71A564*
GCM219R71A684*
GCM219R71C204*
GCM219R71C224*
GCM219R71C244*
GCM219R71C274*
GCM21BR11A824*
GCM21BR71A824*