

Resistors Product Change Notification

PCN Number	PCN-2025-RBU16
PCN Title	EOL Announcement – CAR7 family
PCN Date	11 th November 2025
Type of Change	<input checked="" type="checkbox"/> End of Life Notification <input type="checkbox"/> Material Change <input type="checkbox"/> Manufacturing Facility Change or Addition <input type="checkbox"/> Process Change <input type="checkbox"/> Datasheet Specification Change <input type="checkbox"/> Design Change <input type="checkbox"/> Other:
Manufacturing Location(s) Affected	TT Electronics Bedlington
Date of Change Implementation	11 th of November 2025

Products Affected	
TT Series	Datasheet Link
CAR7	https://www.ttelectronics.com/TTElectronics/media/ProductFiles/Datasheet/CAR.pdf

Change Detail	
Description of Change	TT Electronics is announcing that the family CAR7 is being taken End of Life, (EOL). This applies ONLY CAR7 family. Families CAR5 and CAR6 will continue to be available in all the variants.
Reason for Change	Declining volumes do not justify long-term manufacture of this product group.
Implementation Plan	A Last Time Buy is not available
Customer Impact	All part numbers of CAR7 family are EOL and unavailable to order from TT Electronics.
Recommendations	Please contact your local Sales / FAE team for assistance in selecting the best alternative product.
Availability of Previously Manufactured Product	N/A
Availability of Approval Samples	N/A
Sales Contacts	Americas: Shannon Rosene shannon.rosene@ttelectronics.com Europe: Simon Webb simon.webb@ttelectronics.com Asia: Praveen Kumar Praveen.Kumar@ttelectronics.com

Approvals			
	Name	Title	Date
Issued by	Mario Garsi	Product Line Manager	11 th November 2025
Approved by	Adam Royles	Product Line Director	11 th November 2025
Approved by	Klaus Zwerschina	VP Sales	11 th November 2025

CAR Series

Features:

- Tolerance down to 0.01%
- TCR down to 5ppm/°C
- High reliability
- Superior moisture performance
- Non-standard values available
- High stability metal film
- Matched sets available



All Pb-free parts comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)


Electrical Data

		CAR5	CAR6
Power rating @70°C	W	0.25	0.33
Power rating @85°C	W	0.125	0.25
Resistance range	ohms	10R – 3M0	10R – 5M0
Limiting element voltage	V	250	350
TCR (20 - 70°C) ¹	ppm/°C	5, 10, 15, 25, 50	
Resistance tolerance ¹	%	0.01, 0.02, 0.05, 0.1, 0.25, 0.5, 1	
Standard values ²		E24 & E96 preferred	
Thermal impedance	°C/W	110	70
Ambient temperature range	°C	-55 to 155	

Note 1: See table of resistance restrictions

Note 2: Non-standard values may be requested

Physical Data

Dimensions in mm and weight in g								
Type	L max	D max	f min ¹	d nom	PCB mounting centres	Min. bend radius	Wt. nom	
CAR5	7.2	2.5	30	0.6	10.2	0.6	0.24	
CAR6	10	3.7	30	0.6	12.7	0.6	0.4	

Note 1: Dimension relates only to bulk packed products

Construction

A metal film is deposited onto a high quality ceramic rod. Nickel-plated steel caps are force fitted to the rod and termination wires are welded to the caps. The resistor is adjusted to value by a helical cut in the film and the body is protected with a specially formulated epoxy coating.

Marking

Type reference, TCR code, resistance value and tolerance code are legend marked. The resistance values conform to IEC 60062.

Terminations

Terminations are copper wire with Sn or SnPb finish. They meet the strength requirements of IEC 60115-1 clause 9.5 and the solderability requirements of IEC 60115-1 clause 11.1.

Solvent Resistance

The body protection and marking are resistant to all normal industrial cleaning solvents suitable for printed circuit boards.

Performance Data

		Values ≤250K		Values >250K	
		Maximum	Typical	Maximum	Typical
Load at rated power: Load, 1000 hours at 70°C / 85°C	±ΔR%	0.05	0.02	0.25	0.05
Load at rated power: Load, 8000 hours at 70°C / 85°C	±ΔR%	0.1	0.04	0.5	0.1
Dry heat: No load, 1000 hours at 155°C	±ΔR%	0.15	0.08	1	0.2
Shelf life test: 12 months at room temperature	±ΔR%	0.01	0.003	0.04	0.02
Derating from rated power at 70°C / 85°C		Zero @155°C			
Short term overload: Lesser of 6.25xPr or 2.5xLEV for 5s	±ΔR%	0.01	0.001	0.08	0.01
Climatic	±ΔR%	0.05	0.02	0.2	0.05
Climatic category		55/155/56			
Long term damp heat	±ΔR%	0.05	0.02	0.2	0.05
Temperature rapid change	±ΔR%	0.04	0.02	0.25	0.05
Resistance to solder heat	±ΔR%	0.02	0.003	0.05	0.005
Vibration	±ΔR%	0.02	0.002	0.06	0.02
Bump	±ΔR%	0.02	0.002	0.06	0.02
Noise in a decade of frequency	μV/V	0.2	0.03	1	0.1
Voltage coefficient of resistance	ppm/V	0.3	<0.05	0.2	<0.05

Table of Resistance Restrictions

TCR ppm/°C	Tolerance %					
	CAR5			CAR6		
	0.01 – 0.02	0.05	0.1 - 1	0.01 – 0.02	0.05	0.1 - 1
5 ¹	50R to 300K	10R to 500K		50R to 500K	10R to 500K	
10		10R to 1M0	10R to 1M0		10R to 1M0	10R to 1M0
15			10R to 1M5			10R to 3M0
25			10R to 3M0			10R to 5M0
50						

Note 1: Based on sampling. 100% screened product is available.


Application Notes

Matched Sets

TT Electronics has many years' experience in the supply of matched sets of precision resistors. Resistors can be supplied matched for tolerance and TCR down to ±0.005% and ±1ppm/°C.

Packaging


CAR5 and CAR6 standard packing is in tape, as shown below.



CAR Series

Ordering Procedure

Global Part Number Example: **CAR5V-31K6** (CAR5 with TCR $\pm 5\text{ppm}/^\circ\text{C}$ at 31.6 kilohms $\pm 0.02\%$, Pb-free)



1	2	3	4	5		
Type	TCR (ppm/°C)	Value	Tolerance	Finish, Screening & Packing		
CAR5	V = ± 5	E24 = 3/4 characters	L = $\pm 0.01\%$	I	Pb-free (RoHS)	
CAR6	T = ± 10	E96 = 3/4 characters	P = $\pm 0.02\%$	SC	Pb-free with screened TCR (5ppm only)	
	Y = ± 15	Custom values may use more than 4 characters R = ohms K = kilohms M = megohms	W = $\pm 0.05\%$	PB	Sn(95)Pb(5) finish	
	D = ± 25		B = $\pm 0.1\%$	All above in Standard Packing		
	C = ± 50		C = $\pm 0.25\%$	CAR5	Ammo	Up to 5000/box
			D = $\pm 0.5\%$	CAR6		Up to 2500/box
			F = $\pm 1\%$			

Legacy Part Numbers

This product has a legacy part number format. This is still available for ordering, but for new designs use of the Global Part Number is recommended.

Legacy Part Number Example: **CAR5LFV3162PA** (CAR5 with TCR $\pm 5\text{ppm}/^\circ\text{C}$ at 31.6 kilohms $\pm 0.02\%$, Pb-free)



1	2	3	4	5	6		
Type	Termination	TCR (ppm/°C)	Value	Tolerance	Packing		
CAR5	Omit for Sn(95)Pb(5) LF = Pb-free	V = ± 5	3 digits + multiplier	L = $\pm 0.01\%$	A	CAR5	Ammo, up to 5000/box
CAR6		T = ± 10	R = ohms for values <100 ohms	P = $\pm 0.02\%$		CAR6	Ammo, up to 2500/box
		Y = ± 15		W = $\pm 0.05\%$			
		D = ± 25		B = $\pm 0.1\%$			
		C = ± 50		C = $\pm 0.25\%$			
			D = $\pm 0.5\%$				
			F = $\pm 1\%$				

Parts currently available in our system:

Part Number
CAR5T-316KBI
CAR5T-499KBI