



The DNA of tech.™

Product Change Notification

Product Group: SF/Tuesday June 30, 2026/PCN-SF-498-2026-REV-0



M63 General product evolution

For further information, please contact your regional Vishay office.

CONTACT INFORMATION

Americas

Pierre Lesur
71 chemin de la Mauniere
-
Hyerres France 83400
Phone: +33494123050
Fax: +33494123051
pierre.lesur@vishay.com

Europe

Pierre Lesur
71 chemin de la Mauniere
-
Hyerres France 83400
Phone: +33494123050
Fax: +33494123051
pierre.lesur@vishay.com

Asia

Pierre Lesur
71 chemin de la Mauniere
-
Hyerres France 83400
Phone: +33494123050
Fax: +33494123051
pierre.lesur@vishay.com

Description of Change: Product, Packaging and manufacturing site change

Reason for Change: Product range Rationalization to avoid obsolescence

Expected Influence on Quality/Reliability/Performance: No influence on Quality / Reliability / Performance

Part Numbers/Series/Families Affected: M63*

Vishay Brand(S): Vishay Sfernice

Time Schedule:

Start Shipment Date: Monday July 5, 2027

Sample Availability: W18 2027

Product Identification: trimmer marking

Qualification Data: Available on request

This PCN is considered approved, without further notification, unless we receive specific customer concerns before Wednesday October 7, 2026 or as specified by contract.

Issued By: Pierre Lesur, pierre.lesur@vishay.com

PRODUCT CHANGE

Characteristics	Before PCN	After PCN
Resistance range	100 ohms to 2Mohms	10 ohms to 2Mohms
Power rating	0.5W at 70°C	0.5W at 85°C
Limiting element voltage	250V	300v
Electrical travel	270°	280°
Dielectric withstand voltage	1000 VAC at sea level; 250 VAC at 80 000 ft (24 000 m)	900 VAC at sea level; 350 VAC at 70 000 ft (21 000 m)
Mechanical travel	300°	310°
Temperature Range	-55°C to +125°C	-65°C to 150°C
Electrical endurance	1000h at rated power- ambient temp. 70°C	1000h at rated power- ambient temp. 85°C
Vibration	10g	30 g
Shock	-	100 g
Mechanical life	200 cycles	200 cycles
Damp heat steady state	21 days	MIL-STD-202 method 103 s

VISUAL CHANGE :

Before PCN	After PCN
	

PACKAGING CHANGE

Before PCN

- B40 = box 200 pieces
- B30 = box 100 pieces
- T20 = tube 50 pieces



After PCN

- T20 = tube 50 pieces

UPDATED PRODUCT DRAWING

Before PCN - inch (mm)	After PCN - mm (inch)
Common dimensions	
63P (Bottom View)	
63X	
63M (Bottom View)	
Knob option: T607	Knob option: T607

PCN Appendix : CHANGES (before / after PCN)

Knob option: T614 	Knob option: T614 
--	---

Vishay Material Code	Customer Material	Location
M63P101KB40	VSPM63P101KB40	Ft Worth
M63P103KB30T607	VSPM63P103KB30T607	Ft Worth
M63P103KB40	VSPM63P103KB40	Ft Worth
M63P201KB40	VSPM63P201KB40	Ft Worth
M63M103KB30T607	VSPM63M103KB30T607	Maisach Gernlinden
M63P101KB40	VSPM63P101KB40	Maisach Gernlinden
M63P203KB40	VSPM63P203KB40	Maisach Gernlinden
M63P502KB40	VSPM63P502KB40	Maisach Gernlinden
M63P503KB40	VSPM63P503KB40	Maisach Gernlinden
M63X201KB40	VSPM63X201KB40	Maisach Gernlinden
M63P103KB40	M63P103KB40	Singapore
M63P103KB30T640	M63P103KB30T640	Singapore